

Date of last issue: 26.09.2022	Version 6.1	Print Date 23.03.2024
Revision Date: 28.11.2023		

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : DB560

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Product is not intended for consumer use

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

#### **1.4 Emergency telephone number**

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)				
Acute toxicity, Category 4	H332: Harmful if inhaled.			
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.			
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.			
Short-term (acute) aquatic hazard, Cate- gory 1	H400: Very toxic to aquatic life.			
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.			

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)



Date of last issue: 26.09.2022 Revision Date: 28.11.2023	22 Version 6.1 Print Da		
Hazard pictograms :		!	
Signal word :	Danger	• •	
Hazard statements :	H317 H332 H334 H410	May cause an allergic skin Harmful if inhaled. May cause allergy or asthr breathing difficulties if inha Very toxic to aquatic life w effects.	ma symptoms or aled.
Precautionary statements :	<b>Prevention:</b> P261 P273 P280	Avoid breathing mist or va Avoid release to the enviro Wear protective gloves.	•
	<b>Response:</b> P304 + P340 + P342 + P311	P312 IF INHALED: Remo air and keep comfortable f POISON CENTER/ doctor If experiencing respiratory POISON CENTER/ doctor	or breathing. Call a if you feel unwell. symptoms: Call a
	P391	Collect spillage.	

#### Hazardous components which must be listed on the label:

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate 4-morpholinecarbaldehyde

#### **Additional Labelling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Date of last issue: 26.09.2022	Version 6.1	Print Date 23.03.2024
Revision Date: 28.11.2023		

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components			
Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenyl tolyl phosphate MCS	Not Assigned 945-730-9 01-2119511174-52- XXXX	Aquatic Acute 1; H400 Aquatic Chronic 3; H412	>= 40 - < 60
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 40 - < 60
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 0,031 mg/l	>= 0,5 - < 1
2-ethylhexanoic acid, zirconium salt	22464-99-9 245-018-1 01-2119979088-21- XXXX	Repr. 2; H361d	< 1



Date of last issue: 26.09.2022 Revision Date: 28.11.2023	Version 6	Print Date 23.03.2024	
4-morpholinecarbaldehyde	4394-85-8 224-518-3 01-2119987993-12- XXXX	Skin Sens. 1; H317	< 1
For explanation of abbreviations	s see section 16.		

# SECTION 4: First aid measures

#### 4.1 Description of first aid measures

Genera	al advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhal	ed	:	Move to fresh air. Consult a physician after significant exposure.
In case	e of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case	e of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swall	lowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most im	nportant symptoms ar	nd e	effects, both acute and delayed
Sympto	oms	:	Asthmatic appearance Respiratory disorder Allergic reactions Headache See Section 11 for more detailed information on health effects and symptoms.
Risks		:	sensitising effects
			May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
4.3 Indicati	on of any immediate I	med	lical attention and special treatment needed
Treatm	nent	:	Treat symptomatically.



Date of last issue: 26.09.2022 Revision Date: 28.11.2023		Version 6.1	Print Date 23.03.2024
SECTION 5: Firefighting meas	ur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/c ide/sand/foam/alcohol resistant foam/chemical p extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter dr courses.	ains or water
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathin	g apparatus.
Further information	:	Collect contaminated fire extinguishing water semust not be discharged into drains. Fire residues and contaminated fire extinguishir be disposed of in accordance with local regulation	ng water must

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protect	ive	equipment and emergency procedures
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions		
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for cont	tair	nment and cleaning up
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.



Date of last issue: 26.09.2022 Revision Date: 28.11.2023 Version 6.1

Print Date 23.03.2024

#### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling Advice on safe handling Avoid formation of aerosol. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products Normal measures for preventive fire protection. Advice on protection against 1 fire and explosion Handle in accordance with good industrial hygiene and safety Hygiene measures practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage Keep container tightly closed in a dry and well-ventilated 2 areas and containers place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations. Further information on stor-No decomposition if stored and applied as directed. age stability 7.3 Specific end use(s) Specific use(s) Consult most current local Product Data Sheet prior to any use.

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	TWA (inhalable	10 mg/m3	GB EH40

Date of last issue: 26.09.2022 Revision Date: 28.11.2023

	1	L	I	1	
		dust)			
		TWA (Respirable	4 mg/m3	GB EH40	
		dust)			
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,02 mg/m3 (NCO)	GB EH40	
	Eurthor inform	L ation: Substances th		unational	
		nown as asthmage			
		tate of specific airwa			
		-responsive, further			
		en in tiny quantities,			
		ymptoms can range			
		I workers who are e			
		sponsive and it is in			
		likely to become hy occupational asthn			
		lich may trigger the			
		ng airway hyper-res			
		ease themselves. T			
	classified as asthmagens or respiratory sensitisers. Further infor- mation can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to sub- stances that can cause occupational asthma should be prevented.				
	Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma,				
		es that exposure be			
		able. Activities givin			
		ould receive particul			
		considered. Health			
		osed or liable to be			
		cupational asthma a			
		th an occupational			
		and level of surveilla			
	pational asthma., The 'Sen' notation in the list of WELs has been				
	assigned only to those substances which may cause occupational				
	asthma in the categories shown in Table 1. It should be remem-				
	bered that other substances not in these tables may cause occu-				
	pational asthma. HSE's asthma web pages				
	(www.hse.gov.	uk/asthma) provide		on.	
		STEL	0,07 mg/m3	GB EH40	
			(NCO)		

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### **Biological occupational exposure limits**

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	isocyanate- derived diamine (Isocyanates): 1	At the end of the period of expo- sure	GB EH40 BAT



Version 6.1

Print Date 23.03.2024



Date of last issue: 26.09.2022 Revision Date: 28.11.2023		Versi	on 6.1	Print Date 23.03.2024	
			µmol/mol creati- nine (Urine)		
3.2 Exposure controls					
Engineering measures					
Maintain air concentration Ensure adequate ventilati					
Personal protective equ	ipme	t			
Eye/face protection		Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water		to EN166	
Hand protection		Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.		vhen handling	

Suitable for short time use or protection against splashe	s:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)	
Contaminated gloves should be removed.	
Suitable for permanent exposure:	
Viton gloves (0.4 mm),	
breakthrough time >30 min.	

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection In case of inadequate ventilation wear respiratory protection. 1 Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

#### **Environmental exposure controls**

	-
General advice	

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform



Date of last issue: 26.09.2022 Revision Date: 28.11.2023	Version 6.1	Print Date 23.03.2024
	respective authorities.	

## **SECTION 9: Physical and chemical properties**

•	Physical state Colour	:	liquid various
	Odour	:	characteristic
	Melting point/range / Freezing point	:	No data available
	Boiling point/boiling range	:	No data available
	Flammability (solid, gas)	:	No data available
	Upper/lower flammability or e	exp	losive limits
	Upper explosion limit / Upper flammability limit	:	No data available
	Lower explosion limit / Lower flammability limit	:	No data available
	Flash point	:	> 101 °C Method: closed cup
	Auto-ignition temperature	:	No data available
	Decomposition temperature	:	No data available
	рН	:	Not applicable
	Viscosity Viscosity, kinematic	:	> 7 mm2/s (40 °C)
	<b>Solubility(ies)</b> Water solubility	:	No data available
	Partition coefficient: n-	:	No data available



Date of last issue: 26.09.2022 Revision Date: 28.11.2023	Version 6.1	Print Date 23.03.2024
octanol/water		
Vapour pressure	: 0,01 hPa	
Density	: ca. 1,8 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
<b>9.2 Other information</b> No data available		

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

#### 10.4 Conditions to avoid

Conditions to avoid	:	No data available
---------------------	---	-------------------

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Harmful if inhaled.



of last issue: 26.09.2022 sion Date: 28.11.2023		Version 6.1	Print Date 23.03.
Components:			
Diphenyl tolyl phosphate	MCS:		
Acute oral toxicity	: L	.D50 Oral (Rat): > 5.000 mg/kg	
Acute dermal toxicity	: L	.D50 Dermal (Rat): > 2.000 mg/kg	
3-isocyanatomethyl-3,5,5-	trimeth	ylcyclohexyl isocyanate:	
Acute oral toxicity	: L	.D50 Oral (Rat): 4.814 mg/kg	
Acute inhalation toxicity	E	C50 (Rat): 0,031 mg/l exposure time: 4 h est atmosphere: dust/mist	
	Т	Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity	: L	.D50 Dermal (Rat): > 7.000 mg/kg	
Skin corrosion/irritation Not classified based on ava	ilable in	formation.	
Serious eye damage/eye i Not classified based on ava			
Respiratory or skin sensit	isation		
Skin sensitisation May cause an allergic skin r	eaction		
Respiratory sensitisation			
May cause allergy or asthm	a sympt	oms or breathing difficulties if inhaled.	
Germ cell mutagenicity Not classified based on ava	ilable in	formation.	
<b>Carcinogenicity</b> Not classified based on ava	ilabla in	formation	
	navie In		
Reproductive toxicity Not classified based on ava	ilable in	formation.	
STOT - single exposure			
Not classified based on ava	ilable in	formation.	
STOT - repeated exposure Not classified based on ava		formation.	
Aspiration toxicity			
Not classified based on ava	ilahla in	formation	



Date of last issue: 26.09.2022 Revision Date: 28.11.2023	Version 6.1	Print Date 23.03.2024
11.2 Information on other hazards		

#### **Endocrine disrupting properties**

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Endocrine disrupting properties

#### Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation
		(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at
		levels of 0.1% or higher.

#### 12.7 Other adverse effects

#### Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Very toxic to aquatic life with long lasting effects.



Date of last issue: 26.09.2022 Revision Date: 28.11.2023 Version 6.1

Print Date 23.03.2024

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product

:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### **SECTION 14: Transport information**

14.1 UN number or ID number					
ADR	:	UN 3082			
IMDG	:	UN 3082			
ΙΑΤΑ	:	UN 3082	UN 3082		
14.2 UN proper shipping name					
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (diphenyl tolyl phosphate, triphenyl phosphate)			
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (diphenyl tolyl phosphate, triphenyl phosphate)			
ΙΑΤΑ	:	Environmentally hazardous substance, liquid, n.o.s. (diphenyl tolyl phosphate, triphenyl phosphate)			
14.3 Transport hazard class(es)					
		Class	Subsidiary risks		
ADR	:	9			
IMDG	:	9			
ΙΑΤΑ	:	9			
14.4 Packing group					
ADR					



Date of last issue: 26.09.2022 Revision Date: 28.11.2023	Version 6.1	Print Date 23.03.2024
Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	: III : M6 : 90 : 9 : (-)	
<b>IMDG</b> Packing group Labels EmS Code	: III : 9 : F-A, S-F	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	: 964 : Y964 : III : Miscellaneous	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	: 964 : Y964 : III : Miscellaneous	
14.5 Environmental hazards		
<b>ADR</b> Environmentally hazardous	: yes	
<b>IMDG</b> Marine pollutant	: yes	
IATA (Passenger) Environmentally hazardous	: yes	
IATA (Cargo) Environmentally bazardous		

Environmentally hazardous : yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high : Not applicable



Date of last issue: 26.09.2022 Revision Date: 28.11.2023	Version 6.1	Print Date 23.03.2024					
concern (SVHC) for Authorisation							
	The Persistent Organic Pollutants Regulations (retained : Not applicable Regulation (EU) 2019/1021 as amended for Great Britain)						
	International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors						
Regulation (EC) No 1005/2009 or plete the ozone layer	Regulation (EC) No 1005/2009 on substances that de- : Not applicable plete the ozone layer						
UK REACH List of substances su (Annex XIV)	bject to authorisation : Not applicable						
Volatile organic compounds :	Law on the incentive tax for volatile organic (VOCV) Volatile organic compounds (VOC) content no VOC duties Directive 2010/75/EU of 24 November 201 emissions (integrated pollution prevention Volatile organic compounds (VOC) content	t: 0,1% w/w 0 on industrial and control)					
If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.							
Health, safety and environ- : mental regulation/legislation specific for the substance or mixture:	Environmental Protection Act 1990 & Subs Health and Safety at Work Act 1974 & Sub Control of Substances Hazardous to Healt (COSHH)	osidiary Regulations h Regulations					

# 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.



Pate of last issue: 26.09.2022 Revision Date: 28.11.2023		Version 6.1	Print Date 23.03.2024	
H334	:	May cause allergy or asthma symptoms or t ties if inhaled.	oreathing difficul-	
H335	:	May cause respiratory irritation.		
H361d	:	Suspected of damaging the unborn child.		
H400	:	Very toxic to aquatic life.		
H411	:	Toxic to aquatic life with long lasting effects		
H412	:	Harmful to aquatic life with long lasting effect		
Full text of other abbreviati	ions			
Acute Tox.	:	Acute toxicity		
Aquatic Acute	:	Short-term (acute) aquatic hazard		
Aquatic Chronic	:	Long-term (chronic) aquatic hazard		
Eye Irrit.		Eye irritation		
Repr.		Reproductive toxicity		
Resp. Sens.		Respiratory sensitisation		
Skin Irrit.		Skin irritation		
Skin Sens.	:	Skin sensitisation		
STOT SE	:	Specific target organ toxicity - single exposu	Ire	
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limit		
GB EH40 BAT	:	UK. Biological monitoring guidance values		
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA refer	rence period)	
GB EH40 / STEL	:	Short-term exposure limit (15-minute refere		
ADR	:	European Agreement concerning the Interna		
	•	Dangerous Goods by Road	ational Gamage of	
CAS	:	Chemical Abstracts Service		
DNEL	:	Derived no-effect level		
EC50	:	Half maximal effective concentration		
GHS	:	Globally Harmonized System		
ΙΑΤΑ	:	International Air Transport Association		
IMDG	:	International Maritime Code for Dangerous		
LD50	:	Median lethal dosis (the amount of a materia once, which causes the death of 50% (one l test animals)		
LC50		Median lethal concentration (concentrations	of the chemical in	
2030	•	air that kills 50% of the test animals during t period)		
MARPOL		International Convention for the Prevention	of Pollution from	
	•	Ships, 1973 as modified by the Protocol of 1		
OEL		Occupational Exposure Limit		
PBT	:	Persistent, bioaccumulative and toxic		
PNEC	:	Predicted no effect concentration		
REACH	:	Regulation (EC) No 1907/2006 of the Europ	ean Parliament	
		and of the Council of 18 December 2006 co istration, Evaluation, Authorisation and Rest cals (REACH), establishing a European Che	ncerning the Reg- triction of Chemi-	
SVHC	:	Substances of Very High Concern		
vPvB	:	Very persistent and very bioaccumulative		
Further information				
Classification of the mixtur	e:	Classification pro	cedure:	



Date of last issue: 26.09.2022 Revision Date: 28.11.2023		Version 6.1	Print Date 23.03.2024
Acute Tox. 4	H332	Calculation method	
Resp. Sens. 1	H334	Calculation method	
Skin Sens. 1	H317	Calculation method	
Aquatic Acute 1	H400	Calculation method	
Aquatic Chronic 3	H412	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN