

## PRODUCT DATA SHEET

# Sika® Igoflex® P-10 EL UK

## High Penetration Primer

### PRODUCT DESCRIPTION

Synthetic rubber based primer for use with SikaShield® Hot Melt 50/70.

### USES

High penetration primer for improving the adhesion of SikaShield® Hot Melt 50/70

### CHARACTERISTICS / ADVANTAGES

- Quick drying
- Enhances adhesion
- Suitable for use at low temperatures
- Easily applied

### PRODUCT INFORMATION

Packaging	25 Litre Tin
Shelf Life	12 Months
Storage Conditions	The product should be stored unopened in a dry condition at a temperature of 5°C - 25°C.
Colour	Red

### APPLICATION INFORMATION

Consumption	4-6m <sup>2</sup> /Litre (coverage rates may vary depending on substrate porosity)
Ambient Air Temperature	5°C - 30°C
Pot Life	4 hours
Drying time	15-30 minutes @ 20°C

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

## APPLICATION INSTRUCTIONS

### EQUIPMENT

Sika® Igolflex® P-10 EL UK is applied by roller or brush in a uniform coat to the required area.

### SUBSTRATE PREPARATION

Surfaces should be clean, dry, and free from frost, oil and any other contaminants.

### APPLICATION

Allow primer to dry tack free. Strictly follow Sika Limited installation procedures as defined in specifications, application manuals and working instructions which must always be adjusted to the actual site conditions.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



Product Data Sheet  
Sika® Igolflex® P-10 EL UK  
May 2023, Version 02.01  
020915797000000013

SikalgolflexP-10ELUK-en-GB-(05-2023)-2-1.pdf