

| Date of last issue: 05.01.2023 | Version 3.6 | Print Date 05.01.2023 |
|--------------------------------|-------------|-----------------------|
| Revision Date: 05.01.2023 | | |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Parex Tecgrip V (A) Winter

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Grouting mortar

1.3 Details of the supplier of the safety data sheet

| Company name of supplier | : | Sika Limited Watchmead Welwyn Garden City |
|---|---|--|
| | | Hertfordshire. AL7 1BQ |
| Telephone | : | +44 (0)1707 394444 |
| Telefax | : | +44 (0)1707 329129 |
| E-mail address of person responsible for the SDS | : | EHS@uk.sika.com |

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| Flammable liquids, Category 3 Skin irritation, Category 2 | H226: Flammable liquid and vapour. H315: Causes skin irritation. |
|---|--|
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Reproductive toxicity, Category 2 | H361d: Suspected of damaging the unborn child. |
| Specific target organ toxicity - single ex- posure, Category 3, Respiratory system | H335: May cause respiratory irritation. |
| Specific target organ toxicity - repeated exposure, Category 1, hearing organs | H372: Causes damage to organs through pro- longed or repeated exposure. |
| Aspiration hazard, Category 1 | H304: May be fatal if swallowed and enters air- ways. |
| Long-term (chronic) aquatic hazard, Cat- egory 3 | H412: Harmful to aquatic life with long lasting effects. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



| Date of last issue: 05.01.2023 Revision Date: 05.01.2023 | V | ersion 3.6 | Print Date 05.01.2023 |
|---|---|--|---|
| Hazard pictograms : | | | |
| Signal word : | Danger | • • | |
| Hazard statements : | H226 H304 H315 H319 H335 H361d H372 H412 | Flammable liquid and vapour. May be fatal if swallowed and en Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging the unb Causes damage to organs (hea through prolonged or repeated en Harmful to aquatic life with long fects. | orn child. ring organs) exposure. |
| Precautionary statements : | Prevention: P210 P260 | Keep away from heat, hot surfact open flames and other ignition s smoking. Do not breathe dust/ fume/ gas/ | ources. No |
| | P280 | pours/ spray. Wear protective gloves/ protecti eye protection/ face protection. | |
| | Response: P301 + P310 P331 P370 + P378 | IF SWALLOWED: Immediately of POISON CENTER/ doctor. Do NOT induce vomiting. In case of fire: Use dry sand, dry alcohol-resistant foam to extingu | y chemical or |

Hazardous components which must be listed on the label:

styrene

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Date of last issue: 05.01.2023 Revision Date: 05.01.2023 Version 3.6

Print Date 05.01.2023

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. | Classification | Concentration |
|---------------|--|--|---------------|
| | EC-No. | | (% w/w) |
| | Registration number | | , , |
| styrene | 100-42-5 202-851-5 01-2119457861-32- XXXX | Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation tox- icity (vapour): 11,8 mg/l | >= 25 - < 40 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

| General advice | : | Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. |
|-------------------------|---|--|
| If inhaled | : | Move to fresh air. Consult a physician after significant exposure. |
| In case of skin contact | : | Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. |
| In case of eye contact | : | Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. |



| Date of last issue: 05.01.2023 Revision Date: 05.01.2023 | Version 3.6 | Print Date 05.01.202 |
|---|--|------------------------|
| If swallowed | : Do not induce vomiting without medica Rinse mouth with water. Do not give milk or alcoholic beverages Never give anything by mouth to an un | S. |
| 4.2 Most important symptoms ar | d effects, both acute and delayed | |
| Symptoms | Aspiration may cause pulmonary oeder Cough Respiratory disorder Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed informand symptoms. | |
| Risks | : Risk of serious damage to the lungs (b irritant effects | y aspiration). |
| | May be fatal if swallowed and enters a Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging the unborn chi Causes damage to organs through pro exposure. | ild. |
| 4.3 Indication of any immediate r Treatment | nedical attention and special treatment r : Treat symptomatically. | needed |
| SECTION 5: Firefighting meas | sures | |
| 5.1 Extinguishing media Suitable extinguishing media | : Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical | |
| Unsuitable extinguishing media | : Water | |
| 5.2 Special hazards arising from | the substance or mixture | |
| | : No hazardous combustion products are | e known |
| 5.3 Advice for firefighters | | |
| Special protective equipment for firefighters | : In the event of fire, wear self-contained | J breathing apparatus. |
| Country GB 100000034495 | | 4 / 14 |



| Date of last issue: 05.01.2023 Revision Date: 05.01.2023 | | Version 3.6 | Print Date 05.01.2023 |
|---|------|--|-----------------------|
| Further information | : | Use water spray to cool unopened containers. | |
| SECTION 6: Accidental releas | e | neasures | |
| 6.1 Personal precautions, protect | tiv | e equipment and emergency procedures | |
| Personal precautions | : | Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explos tions. Vapours can accumulate in low areas. | sive concentra- |
| 6.2 Environmental precautions | | | |
| Environmental precautions | : | Prevent product from entering drains. If the product contaminates rivers and lakes or respective authorities. | drains inform |
| 6.3 Methods and material for con | itai | nment and cleaning up | |
| Methods for cleaning up | : | Contain spillage, and then collect with non-com sorbent material, (e.g. sand, earth, diatomaceo miculite) and place in container for disposal acc / national regulations (see section 13). | us earth, ver- |

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

| Advice on safe handling | : | Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products |
|---|---|---|
| Advice on protection against fire and explosion | : | Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges. |



_

| Date of last issue: 05.01.2023 Revision Date: 05.01.2023 | Version 3.6 | Print Date 05.01.2023 |
|---|---|-----------------------|
| Hygiene measures : | Handle in accordance with good industrial hyg practice. When using do not eat or drink. Whe smoke. Wash hands before breaks and at the | n using do not |
| 7.2 Conditions for safe storage, inc | luding any incompatibilities | |
| Requirements for storage : areas and containers | Keep container tightly closed in a dry and wel place. Containers which are opened must be sealed and kept upright to prevent leakage. S ance with local regulations. | carefully re- |
| Further information on stor- : age stability | No decomposition if stored and applied as dire | ected. |
| 7.3 Specific end use(s) | | |

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parame- ters * | Basis * |
|------------|----------|----------------------------------|---------------------------|---------|
| styrene | 100-42-5 | TWA | 100 ppm 430 mg/m3 | GB EH40 |
| | | STEL | 250 ppm 1.080 mg/m3 | GB EH40 |

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

| Eye protection | : | Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water |
|--------------------------|---|---|
| Hand protection | : | Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. |
| | | Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. |
| Skin and body protection | | Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work. In case of inadequate ventilation wear respiratory protection. |
| Respiratory protection | • | |
| ountry GB 10000034495 | | 6 / |



| Date of last issue: 05.01.2023 Revision Date: 05.01.2023 | Version 3.6 | Print Date 05.01.2023 |
|---|--|--|
| | Respirator selection must be based on k exposure levels, the hazards of the proc ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < Ensure adequate ventilation. This can b exhaust extraction or by general ventilat ods for determining inhalation exposure ticular to the mixing / stirring area. In cas to keep the concentrations under the oc limits then respiration protection measure | duct and the safe work- = 10000 ppm e achieved by local tion. (EN 689 - Meth-). This applies in par- se this is not sufficent cupational exposure |
| Environmental exposure of | controls | |
| General advice | : Prevent product from entering drains. If the product contaminates rivers and la respective authorities. | akes or drains inform |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Physical state Colour Odour | : | liquid No data available aromatic |
|---|-----|---|
| Melting point/range / Freezing point | : | No data available |
| Initial boiling point and boiling range | : | > 145 °C |
| Flammability (solid, gas) | : | No data available |
| Upper/lower flammability or | eyn | losive limits |
| Upper explosion limit / Up- per flammability limit | - | |
| Lower explosion limit / Lower flammability limit | : | Lower flammability limit 1,1 %(V) |
| Flash point | : | ca. 31 °C Method: closed cup |
| Auto-ignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| рН | : | No data available |
| Viscosity | | |



| Date of last issue: 05.01.2023 Revision Date: 05.01.2023 | | Version 3.6 | Print Date 05.01.2023 |
|---|---|---------------------|-----------------------|
| Viscosity, kinematic | : | No data available | |
| Solubility(ies) | | | |
| Water solubility | : | No data available | |
| Partition coefficient: n- octanol/water | : | No data available | |
| Vapour pressure | : | 5,9995 hPa | |
| Density | : | ca. 1 g/cm3 (20 °C) | |
| Relative vapour density | : | No data available | |
| Particle characteristics | : | No data available | |
| 9.2 Other information | | | |
| No data available | | | |

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

| Hazardous reactions | : | Stable under recommended storage conditions. |
|--|---|--|
| | | Vapours may form explosive mixture with air. |
| 10.4 Conditions to avoid Conditions to avoid | : | Heat, flames and sparks. |
| 10.5 Incompatible materials | | |

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.



Date of last issue: 05.01.2023 Revision Date: 05.01.2023 Version 3.6

Print Date 05.01.2023

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

styrene:

Acute inhalation toxicity

: LC50 (Rat): 11,8 mg/l Exposure time: 4 h Test atmosphere: vapour

> Acute toxicity estimate: 11,8 mg/l Test atmosphere: vapour Method: Calculation method

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Causes damage to organs (hearing organs) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

11.2 Information on other hazards



Date of last issue: 05.01.2023 Revision Date: 05.01.2023 Version 3.6

Print Date 05.01.2023

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

| Additional ecological infor- | : | An environmental hazard cannot be excluded in the event of |
|------------------------------|---|--|
| mation | | unprofessional handling or disposal. |
| | | Harmful to aquatic life with long lasting effects. |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

| : | The generation of waste should be avoided or minimized wherever possible. |
|---|---|
| | Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe |
| | way. |
| | Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. |
| | Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. |
| | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |



Date of last issue: 05.01.2023 Revision Date: 05.01.2023 Version 3.6

Print Date 05.01.2023

| SECTION 14: Transport information | | | | | | |
|---|---|---|--|--|--|--|
| 14.1 UN number or ID number | | | | | | |
| ADR | : | UN 1866 | | | | |
| IMDG | : | UN 1866 | | | | |
| ΙΑΤΑ | : | UN 1866 | | | | |
| 14.2 UN proper shipping name | | | | | | |
| ADR | : | RESIN SOLUTION (styrene) | | | | |
| IMDG | : | RESIN SOLUTION (styrene) | | | | |
| ΙΑΤΑ | : | Resin solution (styrene) | | | | |
| 14.3 Transport hazard class(es) | | | | | | |
| ADR | : | 3 | | | | |
| IMDG | : | 3 | | | | |
| ΙΑΤΑ | : | 3 | | | | |
| 14.4 Packing group | | | | | | |
| ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code | : | III F1 30 3 (D/E) | | | | |
| IMDG Packing group Labels EmS Code | : | III 3 F-E, <u>S-E</u> | | | | |
| IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels | : | 366 Y344 III Flammable Liquids | | | | |
| IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group | : | 355 Y344 III | | | | |

no



Parex Tecgrip V (A) Winter

| Date of last issue: 05.01.2023 Revision Date: 05.01.2023 | | Version 3.6 | Print Date 05.01.2023 |
|---|---|-------------------|-----------------------|
| Labels | : | Flammable Liquids | |
| 14.5 Environmental hazards | | | |
| ADR Environmentally hazardous | : | no | |
| IMDG Marine pollutant | : | no | |

IATA (Passenger) Environmentally hazardous

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

| International Chemical Weapons Schedules of Toxic Chemicals ar | : | Not applicable | |
|---|------|--|---|
| Regulation (EC) No 1005/2009 o plete the ozone layer | : | Not applicable | |
| (VOCV) | | | or volatile organic compounds ds (VOC) content: < 0% w/w |
| | poll | 4 November 2010 on industrial ution prevention and control) ds (VOC) content: < 0% w/w | |

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

| Health, safety and environ- | : | Environmental Protection Act 1990 & Subsidiary Regulations |
|-------------------------------|---|---|
| mental regulation/legislation | | Health and Safety at Work Act 1974 & Subsidiary Regulations |
| specific for the substance or | | Control of Substances Hazardous to Health Regulations |



Parex Tecgrip V (A) Winter

| e of last issue: 05.01.2023 /ision Date: 05.01.2023 | Version 3.6 | Print Date 05.01.20 |
|--|--|------------------------------|
| mixture: | (COSHH) May be subject to the Control of Ma Regulations (COMAH), and amend | |
| 2 Chamical asfaty assass | nt | |
| 2 Chemical safety assessme | ment has been carried out for this mixture | by the supplier |
| NO Chemical Salety Assess | | by the supplier. |
| CTION 16: Other informa | ion | |
| Full text of H-Statements | | |
| H226 | : Flammable liquid and vapour. | |
| H304 | : May be fatal if swallowed and enter | s airways. |
| H315 | : Causes skin irritation. | |
| H319 | : Causes serious eye irritation. | |
| H332 | : Harmful if inhaled. | |
| H335 | : May cause respiratory irritation. | |
| H361d | : Suspected of damaging the unborn | |
| H372 | : Causes damage to organs through | prolonged or repeated |
| | exposure. | |
| H412 | : Harmful to aquatic life with long last | ting effects. |
| Full text of other abbrevia | ions | |
| Acute Tox. | : Acute toxicity | |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard | |
| Asp. Tox. | : Aspiration hazard | |
| Eye Irrit. | : Eye irritation | |
| Flam. Liq. | : Flammable liquids | |
| Repr. | : Reproductive toxicity | |
| Skin Irrit. | : Skin irritation | |
| STOT RE | : Specific target organ toxicity - repea | |
| STOT SE | : Specific target organ toxicity - single | |
| GB EH40 | : UK. EH40 WEL - Workplace Expos | |
| GB EH40 / TWA | : Long-term exposure limit (8-hour T) | |
| GB EH40 / STEL | : Short-term exposure limit (15-minut | |
| ADR | : European Agreement concerning th | e International Carriage of |
| 040 | Dangerous Goods by Road | |
| CAS DNEL | : Chemical Abstracts Service | |
| EC50 | : Derived no-effect level : Half maximal effective concentration | |
| GHS | : Globally Harmonized System | 11 |
| IATA | : International Air Transport Associat | ion |
| IMDG | : International Maritime Code for Dar | |
| LD50 | : Median lethal dosis (the amount of a | |
| 2200 | once, which causes the death of 50 | |
| | test animals) | |
| LC50 | : Median lethal concentration (conce | ntrations of the chemical in |
| | air that kills 50% of the test animals | |
| | period) | 5 |
| MARPOL | : International Convention for the Pre | wantion of Dollution from |



| Date of last issue: 05.01.2023 Revision Date: 05.01.2023 | Version 3.6 | ; | Print Date 05.01.2023 |
|---|---|--|------------------------------|
| OEL PBT PNEC REACH | Ships, 1973 as modified Occupational Exposure I Persistent, bioaccumulat Predicted no effect conce Regulation (EC) No 1907 and of the Council of 18 istration, Evaluation, Aut cals (REACH), establishi | Limit ive and toxic entration 7/2006 of the European F December 2006 concerr horisation and Restriction | ning the Reg- n of Chemi- |
| SVHC | : Substances of Very High | Concern | |
| vPvB | : Very persistent and very | bioaccumulative | |
| Further information Classification of the mixture | Y | Classification procedu | ire: |
| Flam. Liq. 3 | | Based on product data of | |

| Flam. Liq. 5 | H220 | based on product data of assessment |
|-------------------|-------|-------------------------------------|
| Skin Irrit. 2 | H315 | Calculation method |
| Eye Irrit. 2 | H319 | Calculation method |
| Repr. 2 | H361d | Calculation method |
| STOT SE 3 | H335 | Calculation method |
| STOT RE 1 | H372 | Calculation method |
| Asp. Tox. 1 | H304 | Calculation method |
| Aquatic Chronic 3 | H412 | Calculation method |
| | | |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN