

PRODUCT DATA SHEET

SikaShield® Roof Access Layer

SBS MODIFIED BITUMINOUS PROTECTION MEMBRANE

PRODUCT DESCRIPTION

SikaShield® Roof Access Layer is a sand surfaced, glass-fibre reinforced, SBS access layer

USES

SikaShield® Roof Access Layer is used as a 'roll-in' protection layer as part of the SikaShield® Hot Melt Structural Waterproofing system.

CHARACTERISTICS / ADVANTAGES

- Easy to install

PRODUCT INFORMATION

Packaging	Roll
Shelf Life	36 months
Storage Conditions	Must be stored upright and protected from sunlight, rain and snow.
Top surface	Sanded
Length	20m
Width	1m
Thickness	≤1mm
Weight	1.8kg/m ²

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SikaShield® Roof Access Layer is a roll-in protection layer that is installed into the newly laid SikaShield® Hot Melt 50/70 in strict accordance with the SikaShield® ProMelt Installation Guide.

The SikaShield® Roof Access Layer should be covered by the roof finishes within 6 weeks of installation. For longer periods, please consult Technical Services for further advice.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
SikaShield® Roof Access Layer
March 2024, Version 02.02
020920011990001973

SikaShieldRoofAccessLayer-en-GB-(03-2024)-2-2.pdf