

Date of last issue: 08.07.2022	Version 6.0	Print Date 03.08.2022
Revision Date: 03.08.2022		

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name

SikaPower<sup>®</sup>-477 R (A)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

#### **1.4 Emergency telephone number**

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

## **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat-	H411: Toxic to aquatic life with long lasting effects.
egory 2	

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	LZ	!
Signal word	:	Danger	• •
Hazard statements	:	H315 H317 H318 H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Toxic to aquatic life with long lasting effects.



Date of last issue: 08.07.2022 Revision Date: 03.08.2022	Version 6.0 Print		Print Date 03.08.2022
Precautionary statements :	<b>Prevention:</b> P261 P264 P273 P280	Avoid breathing mist or vapours Wash skin thoroughly after hand Avoid release to the environmer Wear protective gloves/ eye prot protection.	lling. t.
	Response:		
	P305 + P351 + F P391	P338 + P310 IF IN EYES: Rinse with water for several minutes. F tact lenses, if present and easy tinue rinsing. Immediately call a CENTER/ doctor. Collect spillage.	Remove con- to do. Con-

### Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane Aliphatic Polyurethane Prepolymer, blocked 1,4-bis(2,3 epoxypropoxy)butane

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Date of last issue: 08.07.2022 Revision Date: 03.08.2022 Version 6.0

Print Date 03.08.2022

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	>= 40 - < 60
Aliphatic Polyurethane Prepoly- mer, blocked	1613260-86-8 Not Assigned	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 M-Factor (Chronic aquatic toxicity): 1	>= 25 - < 40
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8 219-371-7 01-2119494060-45- XXXX	Aquatic Chronic 3; H412 Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Dam. 1; H318 Acute toxicity esti- mate Acute oral toxicity: 1.163 mg/kg	>= 1 - < 2,5
[3-(2,3- epoxypro- poxy)propyl]trimethoxysilane Contains: methanol <= 0,2 %	2530-83-8 219-784-2 01-2119513212-58- XXXX	Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 1 - < 2,5

For explanation of abbreviations see section 16.



## SikaPower®-477 R (A)

Date of last issue: 08.07.2022 Revision Date: 03.08.2022 Version 6.0

Print Date 03.08.2022

### **SECTION 4: First aid measures**

4.1 Description of first aid meas	sures	6
General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms a	and e	ffects, both acute and delayed
Symptoms	:	Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	:	irritant effects sensitising effects
		Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.
4.3 Indication of any immediate	e med	lical attention and special treatment needed
Treatment		Treat symptomatically.



Date of last issue: 08.07.2022 Revision Date: 03.08.2022		Version 6.0	Print Date 03.08.2022
SECTION 5: Firefighting meas	sur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water ide/sand/foam/alcohol resistant foam/chemi extinction.	
5.2 Special hazards arising from	the	substance or mixture	
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter courses.	er drains or water
Hazardous combustion prod- ucts	:	No hazardous combustion products are kno	own
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained brea	athing apparatus.
Further information	:	Collect contaminated fire extinguishing wate must not be discharged into drains. Fire residues and contaminated fire extingu be disposed of in accordance with local region	ishing water must

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, protection	ive	equipment and emergency procedures
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions		
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for cont	tair	nment and cleaning up
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.



Date of last issue: 08.07.2022 Revision Date: 03.08.2022 Version 6.0

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling Advice on safe handling Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products Advice on protection against Normal measures for preventive fire protection. 1 fire and explosion Handle in accordance with good industrial hygiene and safety Hygiene measures practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage Keep container tightly closed in a dry and well-ventilated areas and containers place. Store in accordance with local regulations. Further information on stor-No decomposition if stored and applied as directed. age stability 7.3 Specific end use(s) Specific use(s) Consult most current local Product Data Sheet prior to any use.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
methanol	67-56-1	TWA	200 ppm	2006/15/EC
			260 mg/m3	
	Further information: Indicative, Identifies the possibility of signifi-			
	cant uptake the	rough the skin		
		TŴA	200 ppm	GB EH40
			266 mg/m3	
	Further information: Can be absorbed through the skin. The as-		kin. The as-	



Date of last issue: 08.07.2022 Revision Date: 03.08.2022	Version 6.0	Print D	Print Date 03.08.2022		
	signed substances are those dermal absorption will lead t		oncerns that		
	STEL	250 ppm 333 mg/m3	GB EH40		
*The above mentioned values are in	accordance with the legislation in	effect at the date of t			

The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment	t			
Eye protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water			
Hand protection	<ul> <li>Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.</li> </ul>			
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.			
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.			
Respiratory protection	: No special measures required.			
Environmental exposure controls				
General advice	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.			

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state Appearance Colour Odour	:	liquid paste red odourless
Melting point/range / Freezing point	:	No data available



# SikaPower®-477 R (A)

\_

Date of last issue: 08.07.2022 Revision Date: 03.08.2022		Version 6.0	Print Date 03.08.2022
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or e	exp	losive limits	
Upper explosion limit / Up- per flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	> 101 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity			
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	soluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Density	:	ca. 1,05 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	
9.2 Other information			

## 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.



# SikaPower®-477 R (A)

Date of last issue: 08.07.2022 Revision Date: 03.08.2022		Version 6.0	Print Date 03.08.2022
10.3 Possibility of hazardous rea	octio	ons	
Hazardous reactions		Stable under recommended storage conditions.	
10.4 Conditions to avoid			
Conditions to avoid	:	No data available	
10.5 Incompatible materials			
Materials to avoid	:	Oxidizing agents	
10.6 Hazardous decomposition p	oroc	lucts	
Hazardous decomposition products			

# SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute toxicity

Not classified based on available information.

## **Components:**

bis-[4-(2,3-epoxipropoxi)phenyl]propane:						
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg				
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg				
Aliphatic Polyurethane Prepo	oly	mer, blocked:				
	•	LD50 Oral (Rat): > 5.000 mg/kg				
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg				
1,4-bis(2,3 epoxypropoxy)butane:						
Acute oral toxicity	:	LD50 Oral (Rat): 1.163 mg/kg				
		Acute toxicity estimate: 1.163 mg/kg Method: Calculation method				
[3-(2,3-epoxypropoxy)propyl]	]tri	imethoxysilane:				
	-	LD50 Oral (Rat): 7.010 mg/kg				
Acute inhalation toxicity	:	LC50 (Rat): > 5,3 mg/l Exposure time: 4 h Test atmosphere: dust/mist				



Print Date 03.08.2022

## SikaPower®-477 R (A)

Date of last issue: 08.07.2022

Revision Date: 03.08.2022			
Acute dermal toxicity	: LD50	0 Dermal (Rabbit): 4.248 mg/kg	
Skin corrosion/irritation Causes skin irritation.			
Serious eye damage/eye Causes serious eye dama			
Respiratory or skin sens	itisation		
<b>Skin sensitisation</b> May cause an allergic skir	reaction.		
<b>Respiratory sensitisatio</b> Not classified based on av		nation.	
Germ cell mutagenicity Not classified based on av	ailable inforn	nation.	
<b>Carcinogenicity</b> Not classified based on av	ailable inforn	nation.	
<b>Reproductive toxicity</b> Not classified based on av	ailable inforn	nation.	
STOT - single exposure Not classified based on av	ailable inforn	nation.	
STOT - repeated exposu Not classified based on av		nation.	
Aspiration toxicity Not classified based on av	ailable inforn	nation.	
11.2 Information on other ha	zards		
Endocrine disrupting pr	operties		
Product: Assessment	ered REA (EU)	substance/mixture does not conta to have endocrine disrupting prop CH Article 57(f) or Commission De 2017/2100 or Commission Regula Is of 0.1% or higher.	erties according to elegated regulation

Version 6.0



Date of last issue: 08.07.2022
Revision Date: 03.08.2022

Version 6.0

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

	exitery			
	Components:			
	<b>bis-[4-(2,3-epoxipropoxi)phe</b> Toxicity to fish	-	<b>I]propane:</b> LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h	
	Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h	
	Aliphatic Polyurethane Prep	oly	mer, blocked:	
	Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h	
	Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h	
	Toxicity to algae/aquatic plants	:	ErC50 (Scenedesmus capricornutum (fresh water algae)): 11 mg/l Exposure time: 72 h	
	M-Factor (Chronic aquatic toxicity)	:	1	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:				
	Toxicity to fish	:	LC50 (Cyprinus carpio (Carp)): 55 mg/l Exposure time: 96 h	

## 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..



Date of last issue: 08.07.2022 Revision Date: 03.08.2022	Version 6.0	Print Date 03.08.2022
12.6 Endocrine disrupting prope	ties	
Product:		
Assessment	<ul> <li>The substance/mixture does not conference of the endocrine disrupting proceed to have endocrine disrupting proceeding (EU) 2017/2100 or Commission Regulation (EU) 2017/2100 or Commission Regulation (EU) 2017/2100 or higher.</li> </ul>	operties according to Delegated regulation
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	: An environmental hazard cannot be a unprofessional handling or disposal. Toxic to aquatic life with long lasting	
SECTION 13: Disposal consid		

# 13.1 Waste treatment methods

13.1			
F	Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
E	European Waste Catalogue	:	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
(	Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

### **SECTION 14: Transport information**

	ΙΑΤΑ	:	UN 3082
	IMDG	:	UN 3082
	ADR	:	UN 3082
14. <sup>,</sup>	1 UN number		



Date of last issue: 08.07.2022 Revision Date: 03.08.2022	Version 6.0	Print Date 03.08.202
14.2 UN proper shipping name		
ADR	: ENVIRONMENTALLY HAZARDOU N.O.S. (epoxy resin)	JS SUBSTANCE, LIQUID,
IMDG	: ENVIRONMENTALLY HAZARDOU N.O.S. (epoxy resin)	JS SUBSTANCE, LIQUID,
ΙΑΤΑ	: Environmentally hazardous substar (epoxy resin)	nce, liquid, n.o.s.
14.3 Transport hazard class(es)		
ADR	: 9	
IMDG	: 9	
ΙΑΤΑ	: 9	
14.4 Packing group		
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks	: III : M6 : 90 : 9 : (-) : Transport in accordance with speci	al provision 375
<b>IMDG</b> Packing group Labels EmS Code Remarks	: III : 9 : F-A, S-F : Transport in accordance with 2.10 <i>.</i> 2	2.7 of the IMDG-Code
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	: 964 : Y964 : III : Miscellaneous	
Remarks IATA (Passenger)	: Transport in accordance with speci	a regulation A 197
Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	: 964 : Y964 : III : Miscellaneous	
14.5 Environmental hazards		
<b>ADR</b> Environmentally hazardous	: yes	



Date of last issue: 08.07.2022 Revision Date: 03.08.2022	Version 6.0	Print Date 03.08.2022

## IMDG

Marine pollutant: yesIATA (Passenger)Environmentally hazardous: yes

**IATA (Cargo)** Environmentally hazardous

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

: yes

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

### **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** Relevant EU provisions transposed through retained EU law

Control of Major Accident Hazar 2015 (COMAH)	ds Regulations E2 ENVIRONMENTAL HAZARDS	
Volatile organic compounds	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: < 0% w/w no VOC duties	
	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0% w/w	

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ-	: Environmental Protection Act 1990 & Subsidiary Regulations
mental regulation/legislation	Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or	Control of Substances Hazardous to Health Regulations
mixture:	(COSHH)
	May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.



## SikaPower®-477 R (A)

Date of last issue: 08.07.2022 Revision Date: 03.08.2022 Version 6.0

Print Date 03.08.2022

## **SECTION 16: Other information**

Full text of H-Statements         H302       :         H312       :         H315       :         H317       :         H318       :         H319       :         H332       :         H411       :         H412       :	Harmful if swallowed. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
Full text of other abbreviationsAcute Tox.:Aquatic Chronic:Eye Dam.:Eye Irrit.:Skin Irrit.:Skin Sens.:2006/15/EC:GB EH40:2006/15/EC / TWA:GB EH40 / TWA:GB EH40 / STEL:ADR:CAS:DNEL:	Acute toxicity Long-term (chronic) aquatic hazard Serious eye damage Eye irritation Skin irritation Skin sensitisation Europe. Indicative occupational exposure limit values UK. EH40 WEL - Workplace Exposure Limits Limit Value - eight hours Long-term exposure limit (8-hour TWA reference period) Short-term exposure limit (15-minute reference period) Short-term exposure limit (15-minute reference period) European Agreement concerning the International Carriage of Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level
EC50 : GHS : IATA : IMDG : LD50 :	Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation
MARPOL : OEL : PBT : PNEC : REACH :	period) International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 Occupational Exposure Limit Persistent, bioaccumulative and toxic Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC : vPvB :	Substances of Very High Concern Very persistent and very bioaccumulative

Date of last issue: 08.07.2022 Revision Date: 03.08.2022	Version 6.0	Print Date 03.08.2022

Further information				
Classification of the mixture:		Classification procedure:		
Skin Irrit. 2	H315	Calculation method		
Eye Dam. 1	H318	Calculation method		
Skin Sens. 1	H317	Calculation method		
Aquatic Chronic 2	H411	Calculation method		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN

