according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-14 Pronto

1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Flooring system.

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ

United Kingdom

Telephone : +44 (0)1707394444

1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Skin sensitisation, Category 1

Specific target organ toxicity - single exH317: May cause an allergic skin reaction.
H335: May cause respiratory irritation.

posure , Category 3, Respiratory system

Classification (67/548/EEC, 1999/45/EC)

Highly flammable R11: Highly flammable.

Sensitising R43: May cause sensitisation by skin contact.

Irritant R37/38: Irritating to respiratory system and skin.

2.2 Label elements

Sikafloor®-14 Pronto

Revision Date 07.08.2014 Print Date 07.08.2014

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

(!)

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water/shower.

P312 Call a POISON CENTER or doctor/ physi-

cian if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

• 201-297-1 methyl methacrylate

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	Classification Classification		Concentration	
CAS-No.	(67/548/EEC)	(REGULATION	[%]	
EC-No.		(EC) No		
Registration number		1272/2008)		
methyl methacrylate	F; R11	Flam. Liq.2; H225	>= 50 - <= 100	
80-62-6	Xi; R37/38 R43	STOT SE3; H335		
201-297-1		Skin Irrit.2; H315		
		Skin Sens.1; H317		
1,1'-(p-tolylimino)dipropan-2-ol	T; R25	Acute Tox.3; H301	>= 1 - < 2,5	

according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto



Revision Date 07.08.2014 Print Date 07.08.2014

38668-48-3 254-075-1	R52/53	Aquatic Chronic3; H412	

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough

Respiratory disorder Allergic reactions

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO2), Dry chemical

according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto

Revision Date 07.08.2014 Print Date 07.08.2014

Unsuitable extinguishing

media

: Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not use a solid water stream as it may scatter and spread

fire.

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

> Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

> sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding of the

given occupational exposure limits (see section 8). Do not get

according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto





in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion

: Use explosion-proof equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store

in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parame-	Basis *
			ters *	
methyl methacrylate	80-62-6	TWA	50 ppm	GB EH40
			208 mg/m3	
		STEL	100 ppm	GB EH40
			416 mg/m3	
		TWA	50 ppm	2009/161/EU
		STEL	100 ppm	2009/161/EU

8.2 Exposure controls

according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto

Revision Date 07.08.2014 Print Date 07.08.2014

Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : dark blue

according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto

Revision Date 07.08.2014

Print Date 07.08.2014

Odour : unpleasant

Odour Threshold : No data available

Flash point : ca. 10 °C

Autoignition temperature : ca. 430 °C

Lower explosion limit 2 %(V)

Upper explosion limit : 12,5 %(V)

Flammability (solid, gas) : No data available

: No data available Oxidizing properties

: No data available Auto-ignition temperature

: Note: not determined

Melting point/range / Freez-

ing point

: No data available

: No data available Boiling point/boiling range

Vapour pressure : ca.38,7 hPa

at 20 °C

Density : ca.0,99 g/cm3

at 20 °C

Water solubility : Note: insoluble

Partition coefficient: n-

Viscosity, dynamic

octanol/water

: No data available

: ca.300 mPa.s at 20 °C

Viscosity, kinematic > 20.5 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

Self-heating : , no

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto



No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Skin corrosion/irritation

Product

Causes skin irritation.

Serious eye damage/eye irritation

Product

No data available

Respiratory or skin sensitisation

Product

May cause an allergic skin reaction.

Germ cell mutagenicity

Product

Mutagenicity : No data available

Carcinogenicity

Product

Carcinogenicity : No data available

according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto

Revision Date 07.08.2014 Print Date 07.08.2014



Reproductive toxicity : No data available

No data available

Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

No data available

according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto

Revision Date 07.08.2014 Print Date 07.08.2014

Print Date 07 08 2014

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

wav.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1247

14.2 Description of the goods : METHYL METHACRYLATE MONOMER, STABILIZED

14.3 Class: 314.4 Packing group: IIClassification Code: F1Labels: 3Tunnel restriction code: (D/E)

14.5 Environmentally hazard- : no

ous

IATA

14.1 UN number : 1247

14.2 Description of the goods : Methyl methacrylate monomer, stabilized

14.3 Class : 3 **14.4 Packing group** : II

Labels : 3

14.5 Environmentally hazard- : no

ous

IMDG

14.1 UN number : 1247

14.2 Description of the goods : METHYL METHACRYLATE, MONOMER, STABILIZED

14.3 Class : 3

according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto



14.4 Packing group: IILabels: 3EmS Number 1: F-EEmS Number 2: S-D14.5 Marine pollutant: no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Labelling according to EC Directives (1999/45/EC)

Hazard pictograms





Highly flammable

Irritant

R-phrase(s) : R11 Highly flammable.

R37/38 Irritating to respiratory system and skin.
R43 May cause sensitisation by skin contact.

S-phrase(s) : S24 Avoid contact with skin.

S37 Wear suitable gloves.

Hazardous components which must be listed on the label:

• 201-297-1 methyl methacrylate

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

: not applicable

REACH - List of substances subject to authorisation : not applicable

(Annex XIV)

REACH Information: All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/orexcluded from the regulation, and/or

- exempted from the registration.

according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto

Revision Date 07.08.2014



VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Sup-

ply) Regulations 2002

Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations

1999

Health and Safety at Work Act 1974

Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of R-Phrases

R11 Highly flammable. R25 Toxic if swallowed.

R37/38 Irritating to respiratory system and skin.
R43 May cause sensitisation by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

Full text of H-Statements

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Chronic
Flam. Liq.
Skin Irrit.
Skin Sens.
Chronic aquatic toxicity
Flammable liquids
Skin irritation
Skin sensitisation

STOT SE Specific target organ toxicity - single exposure

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.

according to Regulation (EC) No. 1907/2006

Sikafloor®-14 Pronto

Print Date 07.08.2014

Revision <u>Date 07.08.2014</u>

Changes as compared to previous version!