

Sikafloor®-125 Level Flex

DECLARATION OF PERFORMANCE No. 80771115

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	80771115
2	INTENDED USE/S	
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	4
6a	DESIGNATED STANDARD:	BS EN 13813:2002
	Approved body/ies:	N/A

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Designated Technical Specification
Reaction to fire	A1 _{fl}		BS EN 13813: 2002
Release of corrosive substances	CT		
Water permeability	NPD		
Water Vapour permeability	NPD		
Compressive Strength	C25		
Flexural Strength	F6		
Abrasion / Wear Resistance	NPD		
Sound insulation	NPD		
Sound absorption	NPD		
Thermal resistance	NPD		
Chemical resistance	NPD		

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -
SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product
Coordinator
At Leeds on 18 September 2024

Name : Sarah Buchanan
Function: Product Manager
At Leeds on 18 September 2024

S Buchanan

.....



End of information as required by UKCA

Declaration of Performance

Sikafloor®-125 Level Flex
80771115
2024/09 , ver. 01
1088





Sika Services AG, Zurich, Switzerland

DoP No. 80771115

BS EN 13813:2002

Approved Body(ies): N/A

Reaction to fire	A1fl
Release of corrosive substances	CT
Water permeability	NPD
Water Vapour permeability	NPD
Compressive Strength	C25
Flexural Strength	F6
Abrasion / Wear Resistance	NPD
Sound insulation	NPD
Sound absorption	NPD
Thermal resistance	NPD
Chemical resistance	NPD

[sika.co.uk](https://www.sika.co.uk)

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

Sikafloor®-125 Level Flex
80771115
2024/09, ver. 01
1088

Declaration of Performance

Sikafloor®-125 Level Flex

80771115

2024/09 , ver. 01

1088

4/4

BUILDING TRUST

