

## PRODUCT DATA SHEET

# Sarnafil® T Control Pipe Set

Control pipe set for inspecting flat roof layer build-up

### PRODUCT DESCRIPTION

The Sarnafil® T Control Pipe Set comprises of 3 parts. A rigid high quality polypropylene (PP) pipe and cap, an expanded polyethylene (EPE) insulation plug and a prefabricated Sarnafil® T (FPO) flashing.

### USES

Sarnafil® T Control Pipe Set may only be used by experienced professionals

- The Sarnafil® T Control Pipe Set provides an inspection point to check the watertightness of a flat roof from the rooftop

### CHARACTERISTICS / ADVANTAGES

- Easily installed

### PRODUCT INFORMATION

<b>Chemical Base</b>	Pipe, base plate, cap	Polypropylene (PP)	
	Insulation plug	Expanded polyethylene (EPE)	
	Sarnafil® T Pipe flashing	Flexible Polyolefins (FPO-PP)	
<b>Packaging</b>	The Sarnafil® T Control Pipe Set consists of: <ul style="list-style-type: none"> <li>▪ Pipe with base plate (one piece)</li> <li>▪ Cap with integrated insulation plug</li> <li>▪ Prefabricated Sarnafil® T flashing</li> </ul>		
<b>Appearance / Colour</b>	Colour	Pipe with base plate	beige
		Cap with integrated insulation plug	black
		Prefabricated Sarnafil® T Pipe flashing	beige and ~RAL 7040
<b>Shelf Life</b>	5 years from date of production		

## Storage Conditions

The product must be stored in original, unopened and undamaged packaging in dry conditions and temperatures between +5 °C and +30 °C. Always refer to packaging.

## Dimensions

Control pipe outside diameter	110 mm
Control pipe flange outside diameter	260 mm
Control pipe height	550 mm
Sarnafil® T pipe flashing inside diameter	112 mm

## APPLICATION INFORMATION

**Ambient Air Temperature** -20 °C min. / +60 °C max.

**Substrate Temperature** -30 °C min. / +60 °C max.

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LIMITATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- The use of Sarnafil® T Control Pipe Set is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.
- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the appropriate Product Data Sheets.
- Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

## ECOLOGY, HEALTH AND SAFETY

Fresh air ventilation must be ensured, when working (welding) in closed rooms.

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION

Strictly follow installation procedures as defined in

method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

Refer to the relevant section in the Installation instructions: Sarnafil® T roofing membranes

- Apply the vapour control layer / barrier to the roof structure
- Directly fasten the control pipe flange (using 4 fasteners) onto the vapour control layer / barrier to the roof deck
- Finish the build-up with the for the project selected additional parts

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



Product Data Sheet  
Sarnafil® T Control Pipe Set  
July 2026, Version 02.01  
020945032150000011

SarnafilTControlPipeSet-en-GB-(07-2026)-2-1.pdf