

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaPower®-880 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited
Watchmead Welwyn Garden City
Hertfordshire. AL7 1BQ
Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person responsible for the SDS : EHS@uk.sika.com

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)
24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|--|
| Skin corrosion, Sub-category 1C | H314: Causes severe skin burns and eye damage. |
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Specific target organ toxicity - repeated exposure, Category 2 | H373: May cause damage to organs through prolonged or repeated exposure. |
| Long-term (chronic) aquatic hazard, Category 2 | H411: Toxic to aquatic life with long lasting effects. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

| | |
|------|--|
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

| | | |
|--------------------------|---|--|
| Precautionary statements | : | Prevention: |
| | | |
| | | P260 Do not breathe mist or vapours. |
| | | P273 Avoid release to the environment. |
| | | P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. |
| | | Response: |
| | | P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. |
| | | P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. |
| | | P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. |
| | | P391 Collect spillage. |

Hazardous components which must be listed on the label:

2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated

Carbomonocyclic alkylated mixtures of poly-aza-alcanes, hydrogenated
1,3-Benzenedimethanamine, N-(2-phenylethyl) derivs.

3-aminopropyldiethylamine

2-piperazin-1-ylethylamine

m-phenylenebis(methylamine)

Amines, polyethylenepoly-, triethylenetetramine fraction

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|--|---|--|--------------------------|
| 2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated | 68683-29-4 Not Assigned | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 | >= 10 - < 20 |
| Carbomonocyclic alkylated mixtures of poly-aza-alcanes, hydrogenated | 1173092-74-4 630-554-4 | Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 M-Factor (Acute aquatic toxicity): 1 Acute toxicity estimate Acute oral toxicity: 500 mg/kg | >= 10 - < 20 |
| Polyoxypropylene diamine | 9046-10-0 618-561-0 01-2119557899-12-XXXX | Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412 | >= 5 - < 10 |
| 2,4,6-tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 % | 90-72-2 202-013-9 603-069-00-0 01-2119560597-27-XXXX | Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1.999 mg/kg | >= 5 - < 10 |
| aluminium dihydrogen triphosphate | 13939-25-8 237-714-9 01-2119970565-28-XXXX | Eye Irrit. 2; H319 | >= 1 - < 2,5 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

| | | | |
|--|--|---|---------------------------|
| <p>1,3-Benzenedimethanamine, N-(2-phenylethyl) derivs.</p> | <p>404362-22-7 445-790-1 01-0000018826-60-XXXX</p> | <p>Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1A; H317 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1</p> <hr/> <p>Acute toxicity estimate</p> <hr/> <p>Acute oral toxicity: 1.000 mg/kg</p> | <p>>= 1 - < 2,5</p> |
| <p>3-aminopropyldiethylamine</p> | <p>104-78-9 203-236-4 612-062-00-1 01-2119965402-39-XXXX</p> | <p>Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Repr. 2; H361d STOT SE 3; H335</p> <hr/> <p>Acute toxicity estimate</p> <hr/> <p>Acute oral toxicity: 1.410 mg/kg Acute dermal toxicity: 524 mg/kg</p> | <p>>= 1 - < 2,5</p> |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

| | | | |
|--|--|--|------------------------------|
| <p>2-piperazin-1-ylethylamine Contains: 2-(2-aminoethylamino)ethanol <= 0,29 %</p> | <p>140-31-8 205-411-0 612-105-00-4 01-2119471486-30-XXXX</p> | <p>Repr. 2; H361 STOT RE 1; H372 Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412</p> <hr/> <p>Acute toxicity estimate</p> <p>Acute oral toxicity: 1.999 mg/kg Acute dermal toxicity: 866 mg/kg</p> | <p>>= 0,5 - < 1</p> |
| <p>m-phenylenebis(methylamine)</p> | <p>1477-55-0 216-032-5 01-2119480150-50-XXXX</p> | <p>Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071</p> <hr/> <p>Acute toxicity estimate</p> <p>Acute oral toxicity: 930 mg/kg Acute inhalation toxicity (dust/mist): 1,34 mg/l</p> | <p>>= 0,25 - < 0,5</p> |
| <p>Amines, polyethylenepoly-, triethylenetetramine fraction Contains: 2-(2-aminoethylamino)ethanol <= 0,3 %</p> | <p>90640-67-8 292-588-2 01-2119487919-13-XXXX</p> | <p>Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071</p> <hr/> <p>Acute toxicity estimate</p> <p>Acute oral toxicity: 1.716 mg/kg Acute dermal toxicity: 1.465 mg/kg</p> | <p>>= 0,1 - < 0,25</p> |

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Health injuries may be delayed.
corrosive effects
sensitising effects
- May cause an allergic skin reaction.
Causes serious eye damage.
May cause damage to organs through prolonged or repeated exposure.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Appropriate engineering controls

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Safety glasses with side-shields conforming to EN166
Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the spe-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

Respiratory protection : cific work-place.
: In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : paste
Colour : grey
Odour : amine-like

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : ca. 200.000 mPa.s (20 °C)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

| | | |
|--|---|------------------------------------|
| Viscosity, kinematic | : | > 20,5 mm ² /s (40 °C) |
| Solubility(ies) | | |
| Water solubility | : | insoluble |
| Partition coefficient: n-octanol/water | : | No data available |
| Vapour pressure | : | 0,01 hPa |
| Density | : | ca. 1,26 g/cm ³ (20 °C) |
| Relative vapour density | : | No data available |
| Particle characteristics | : | No data available |

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Carbomonocyclic alkylated mixtures of poly-aza-alcanes, hydrogenated:

Acute oral toxicity : LD50 Oral (Rat): 500 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

Polyoxypropylene diamine:

Acute oral toxicity : LD50 Oral (Rat): 2.880 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg
Remarks: Harmful if swallowed.
Annex VI - Harmonised
REGULATION (EC) No 1272/2008

1,3-Benzenedimethanamine, N-(2-phenylethyl) derivs.:

Acute oral toxicity : LD50 Oral (Rat): 1.000 mg/kg

Acute toxicity estimate: 1.000 mg/kg
Method: Calculation method

3-aminopropyldiethylamine:

Acute oral toxicity : LD50 Oral (Rat): 1.410 mg/kg

Acute toxicity estimate: 1.410 mg/kg
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rabbit): 524 mg/kg

Acute toxicity estimate: 524 mg/kg
Method: Calculation method

2-piperazin-1-ylethylamine:

Acute oral toxicity : LD50 Oral (Rat): > 1.999 mg/kg

Acute toxicity estimate: 1.999 mg/kg
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rabbit): ca. 866 mg/kg

Acute toxicity estimate: 866 mg/kg
Method: Calculation method

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute toxicity estimate: 930 mg/kg
Method: Calculation method

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Corrosive to the respiratory tract.

Acute toxicity estimate: 1,34 mg/l
Test atmosphere: dust/mist
Method: Calculation method

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

Amines, polyethylenepoly-, triethylenetetramine fraction:

Acute oral toxicity : LD50 Oral (Rat): 1.716 mg/kg

Acute toxicity estimate: 1.716 mg/kg
Method: Calculation method

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 Dermal (Rabbit): 1.465 mg/kg

Acute toxicity estimate: 1.465 mg/kg
Method: Calculation method

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Corrosive
Method : OECD Test Guideline 404

Assessment : irritating
Remarks : Annex VI - Harmonised
REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Causes serious eye damage.

Assessment : irritating
Remarks : Annex VI - Harmonised
REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated:

Toxicity to algae/aquatic plants : EC50 (Raphidocelis subcapitata (freshwater green alga)): 0,56 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC50 (Raphidocelis subcapitata (freshwater green alga)):

2,7662 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)):

0,26 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)):

0,445 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Polyoxypropylene diamine:

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 80 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

1,3-Benzenedimethanamine, N-(2-phenylethyl) derivs.:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4 mg/l
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,14 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

M-Factor (Chronic aquatic toxicity) : 1

2-piperazin-1-ylethylamine:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3259
IMDG : UN 3259
IATA : UN 3259

14.2 UN proper shipping name

ADR : AMINES, SOLID, CORROSIVE, N.O.S.
(Carbomonocyclic alkylated mixtures of poly-aza-alcanes, hydrogenated)
IMDG : AMINES, SOLID, CORROSIVE, N.O.S.
(Carbomonocyclic alkylated mixtures of poly-aza-alcanes, hydrogenated)
IATA : Amines, solid, corrosive, n.o.s.
(Carbomonocyclic alkylated mixtures of poly-aza-alcanes, hydrogenated)

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|------|-------|------------------|
| ADR | : 8 | |
| IMDG | : 8 | |
| IATA | : 8 | |

14.4 Packing group

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

ADR

Packing group : II
Classification Code : C8
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

IMDG

Packing group : II
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo aircraft) : 863
Packing instruction (LQ) : Y844
Packing group : II
Labels : Corrosive

IATA (Passenger)

Packing instruction (passenger aircraft) : 859
Packing instruction (LQ) : Y844
Packing group : II
Labels : Corrosive

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

Number on list 3

Number on list 40

This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Not applicable

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

| | |
|-------|---|
| H226 | : Flammable liquid and vapour. |
| H302 | : Harmful if swallowed. |
| H311 | : Toxic in contact with skin. |
| H312 | : Harmful in contact with skin. |
| H314 | : Causes severe skin burns and eye damage. |
| H315 | : Causes skin irritation. |
| H317 | : May cause an allergic skin reaction. |
| H318 | : Causes serious eye damage. |
| H319 | : Causes serious eye irritation. |
| H332 | : Harmful if inhaled. |
| H335 | : May cause respiratory irritation. |
| H361 | : Suspected of damaging fertility or the unborn child. |
| H361d | : Suspected of damaging the unborn child. |
| H372 | : Causes damage to organs through prolonged or repeated exposure. |
| H373 | : May cause damage to organs through prolonged or repeated exposure. |
| H373 | : May cause damage to organs through prolonged or repeated exposure if swallowed. |
| H400 | : Very toxic to aquatic life. |
| H410 | : Very toxic to aquatic life with long lasting effects. |
| H411 | : Toxic to aquatic life with long lasting effects. |
| H412 | : Harmful to aquatic life with long lasting effects. |

Full text of other abbreviations

| | |
|-----------------|---|
| Acute Tox. | : Acute toxicity |
| Aquatic Acute | : Short-term (acute) aquatic hazard |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Eye Dam. | : Serious eye damage |
| Eye Irrit. | : Eye irritation |
| Flam. Liq. | : Flammable liquids |
| Repr. | : Reproductive toxicity |
| Skin Corr. | : Skin corrosion |
| Skin Irrit. | : Skin irritation |
| Skin Sens. | : Skin sensitisation |
| STOT RE | : Specific target organ toxicity - repeated exposure |
| STOT SE | : Specific target organ toxicity - single exposure |
| ADR | : European Agreement concerning the International Carriage of Dangerous Goods by Road |
| CAS | : Chemical Abstracts Service |
| DNEL | : Derived no-effect level |
| EC50 | : Half maximal effective concentration |
| GHS | : Globally Harmonized System |
| IATA | : International Air Transport Association |
| IMDG | : International Maritime Code for Dangerous Goods |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaPower®-880 Part B

Date of last issue: -
Revision Date: 13.04.2026

Version 1.0

Print Date 13.04.2026

| | | |
|--------|---|--|
| LD50 | : | Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
| LC50 | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | : | Occupational Exposure Limit |
| PBT | : | Persistent, bioaccumulative and toxic |
| PNEC | : | Predicted no effect concentration |
| REACH | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC | : | Substances of Very High Concern |
| vPvB | : | Very persistent and very bioaccumulative |

Further information

Classification of the mixture:

| | |
|-------------------|------|
| Skin Corr. 1C | H314 |
| Eye Dam. 1 | H318 |
| Skin Sens. 1 | H317 |
| STOT RE 2 | H373 |
| Aquatic Chronic 2 | H411 |

Classification procedure:

| |
|--------------------|
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

GB / EN