
according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B



# Print Pate 22 00 2014

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikafloor® Garage Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Epoxy coating.

#### 1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Telephone : +44 (0)1707 394444

#### 1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Type of product : Mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2

H315: Causes skin irritation.

Eye irritation, Category 2

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

Chronic aquatic toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects.

#### Classification (67/548/EEC, 1999/45/EC)

Sensitising R43: May cause sensitisation by skin contact.

Irritant R36/38: Irritating to eyes and skin.

Dangerous for the environment R51/53: Toxic to aquatic organisms, may cause

long-term adverse effects in the aquatic environ-

ment.

#### 2.2 Label elements

according to Regulation (EC) No. 1907/2006

## Sikafloor® Garage Part B

Revision Date 15.09.2014 Version 0.0



#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

¥2>

Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention**:

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P391 Collect spillage.

Hazardous components which must be listed on the label:

500-033-5 reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number

average molecular weight <= 700)

• 500-006-8 reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number

average molecular weight <= 700)

271-846-8 oxirane, mono[(C12-14-alkyloxy)methyl]derivs

#### **Additional Labelling:**

Contains epoxy constituents. May produce an allergic reaction.

#### 2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

#### **SECTION 3: Composition/information on ingredients**


#### 3.2 Mixtures

#### **Hazardous components**

Chemical Name CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
9	V'. D00/00	/	05 50
reaction product: bisphenol-A-	Xi; R36/38	Eye Irrit.2; H319	>= 25 - < 50

according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B



(epichlorhydrin) and epoxy resin (number average molecular weight <= 700) 25068-38-6 500-033-5 01-2119456619-26-XXXX	R43 N; R51/53	Skin Irrit.2; H315 Skin Sens.1; H317 Aquatic Chronic2; H411	
reaction product: bisphenol F- (epichlorhydrin) epoxy resin (number average molecular weight <= 700) 9003-36-5 500-006-8 01-2119454392-40-XXXX	Xi; R38 N; R51/53 R43	Skin Irrit.2; H315 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 10 - < 20
oxirane, mono[(C12-14- alkyloxy)methyl]derivs 68609-97-2 271-846-8 01-2119485289-22-XXXX	Xi; R38 R43	Skin Irrit.2; H315 Skin Sens.1; H317	>= 2,5 - < 5

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B

Revision Date 15.09.2014 Version 0.0 Print Date 23

and symptoms.

Risks irritant effects

sensitising effects

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- : No hazardous combustion products are known

#### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accord-

ance with local regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

#### 6.2 Environmental precautions

**Environmental precautions** : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B

Revision Date 15.09.2014 Version 0.0



acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding of the

given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene

measures when handling chemical products

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

 Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B

Revision Date 15.09.2014 Version 0.0 Print Date 23.09.20



#### Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

#### **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance : liquid

Odour : very faint

Odour Threshold : No data available

Flash point : Note: not applicable

Autoignition temperature : Remarks: not applicable

white

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Colour

according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B

Revision Date 15.09.2014 Version 0.0 Print Date 23.09.2014

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

Auto-ignition temperature : No data available

pH : Note: not applicable

Melting point/range / Freez-

ing point

Boiling point/boiling range

: No data available: No data available

Vapour pressure : No data available

Density : ca.1,07 g/cm3

at 20 °C

Water solubility : Note: soluble

Partition coefficient: n-

octanol/water

Viscosity, dynamic

: No data available

: No data available

Viscosity, kinematic : > 20,5 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

#### 9.2 Other information

No data available

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B

Revision Date 15.09.2014 Version 0.0



#### 10.6 Hazardous decomposition products

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

#### **Components:**

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular

weight <= 700) :

Acute oral toxicity : LD50 Oral rat: > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal rabbit: > 20.000 mg/kg

#### Skin corrosion/irritation

#### **Product**

Causes skin irritation.

#### Serious eye damage/eye irritation

#### **Product**

Causes serious eye irritation.

#### Respiratory or skin sensitisation

#### **Product**

May cause an allergic skin reaction.

#### Germ cell mutagenicity

#### **Product**

Mutagenicity : No data available

#### Carcinogenicity

#### **Product**

Carcinogenicity : No data available

### Reproductive Toxicity/Fertility

Reproductive toxicity : No data available

No data available

#### Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B

Revision Date 15.09.2014 Version 0.0



No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

**Aspiration toxicity** 

No data available

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Other adverse effects

No data available

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should

according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B



at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

: 08 01 11\* waste paint and varnish containing organic sol-European Waste Catalogue

vents or other dangerous substances

: 15 01 10\* packaging containing residues of or contaminated Contaminated packaging

by dangerous substances

#### **SECTION 14: Transport information**

**ADR** 

14.1 UN number : 3082

14.2 Description of the goods : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

14.3 Class 14.4 Packing group : 111 Classification Code M6 Labels : 9 Tunnel restriction code : (E) 14.5 Environmentally hazard-: yes

**IATA** 

14.1 UN number

14.2 Description of the goods Environmentally hazardous substance, liquid, n.o.s.

(epoxy resin)

**14.3 Class** 9 14.4 Packing group Ш 9 14.5 Environmentally hazard-: yes

ous

**IMDG** 

14.1 UN number : 3082

14.2 Description of the goods : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

14.3 Class 9 14.4 Packing group Ш Labels 9 EmS Number 1 F-A EmS Number 2 S-F 14.5 Marine pollutant : yes

#### 14.6 Special precautions for user

according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B

Revision Date 15.09.2014 Version 0.0 Print Date 23.09.201

No data available

# 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Labelling according to EC Directives (1999/45/EC)

Hazard pictograms





Irritant

Dangerous for the environment

R-phrase(s) : R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.
R51/53 Toxic to aquatic organisms, may cause

long-term adverse effects in the aquatic

environment.

S-phrase(s) : S24 Avoid contact with skin.

S37 Wear suitable gloves.

Hazardous components which must be listed on the label:

500-033-5 reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number

average molecular weight <= 700)

500-006-8 reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number

average molecular weight <= 700)

271-846-8 oxirane, mono[(C12-14-alkyloxy)methyl]derivs

Special labelling of certain

mixtures

: Contains epoxy constituents. See information supplied by the

manufacturer.

#### **Prohibition/Restriction**

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Banned and/or restricted

(ethylene oxide)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation : not applicable

(Annex XIV)

All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

- preregistered or registered by us, and/or

**REACH Information:** 

according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B

Revision Date 15.09.2014 Version 0.0 Print

Print Date 23.09.2014

excluded from the regulation, and/orexempted from the registration.

VOC-CH (VOCV) : < 0,01 %

no VOC duties

VOC-EU (solvent) : < 0,01 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Sup-

ply) Regulations 2002

Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations

1999

Health and Safety at Work Act 1974

Environmental Protection Act 1990 & Subsidiary Regulations

#### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

#### **SECTION 16: Other information**

#### Full text of R-Phrases

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

#### **Full text of H-Statements**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic Chronic aquatic toxicity

Eye Irrit. Eye irritation
Skin Irrit. Skin irritation
Skin Sens. Skin sensitisation

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.

Changes as compared to previous version!

according to Regulation (EC) No. 1907/2006

# Sikafloor® Garage Part B

Revision Date 15.09.2014 Version 0.0

