

PRODUCT DATA SHEET

Cromar® Acrypol+ Scrim

A polyester mesh for use with Cromar Acrypol+

PRODUCT DESCRIPTION

A 100 % polyester flexible mesh for use with Acrypol+ for filling and creating a seamless finish of any voids.

USES

For uses where extra reinforcement is needed:

- Cracks in gutters.
- Splits in felt and asphalts.
- Cracks in asbestos sheets.
- Over-filling voids.

CHARACTERISTICS / ADVANTAGES

- Enhances Acrypol+ applications by effectively bridging splits and cracks in roofs and gutters.
- Exhibits strength, providing support over holes in roof sheets when combined with Cromar Acrypol+.
- Easily cut to size with scissors and effortlessly forms to various surfaces.
- The edges of the mesh remain flat without curling up, contributing to a clean and neat finish.
- Easy to apply.

PRODUCT INFORMATION

Fibre type	Polyester mesh.
Packaging	Supplied in boxes of 5 rolls.
Colour	White.
Shelf Life	2 years.
Storage Conditions	<ul style="list-style-type: none"> ▪ Do not store in direct sunlight or in a high temperature, high-humidity atmosphere. ▪ Storage temperature should preferably remain below +25 °C. ▪ Rolls should be stored unopened/sealed in original packaging in a clean, dry and dust free storage area.
Dimensions	15 cm x 20 m
Weight	100 g/m ²

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of

the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

- Before applying the scrim, it is crucial to clear the area of loose dirt, moss, and lichen.
- Begin by applying a 20 cm wide coat of Acrypol+ over splits, cracks, and holes.
- Subsequently, lay the 15 cm x 20 m reinforcement mesh into the wet Acrypol+, using a paint-brush to press it into position.
- The final step involves reloading the brush and applying another coat of Acrypol+ onto the mesh, ensuring a secure and durable result.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED
Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® Acrypol+ Scrim
January 2026, Version 01.01
020915952000246231

CromarAcrypol+Scrim-en-GB-(01-2026)-1-1.pdf

BUILDING TRUST

