

Date of last issue: 06.03.2025	Version 5.5	Print Date 11.03.2025
Revision Date: 11.03.2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaBiresin® MC100 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Tooling system, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ
Telephone Telefax E-mail address of person	:	+44 (0)1707 394444 +44 (0)1707 329129 EHS@uk.sika.com
responsible for the SDS		

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12 Acute toxicity, Category 4	72/2008) H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure.

SikaBiresin[®] MC100 Part B

Date of last issue: 06.03.2025 Revision Date: 11.03.2025			Print Date 11.03.2025
2.2 Label elements			
Labelling (REGULATION (EC) Hazard pictograms :	No 1272/2008)		
Signal word :	Danger		
Hazard statements :	H317 M H319 Ca H332 Ha H334 M H335 M H351 Sa H373 M	auses skin irritation. ay cause an allergic skin reaction. auses serious eye irritation. armful if inhaled. ay cause allergy or asthma sympto g difficulties if inhaled. ay cause respiratory irritation. uspected of causing cancer. ay cause damage to organs throug repeated exposure.	
Precautionary statements :	Prevention: P201 P260 P264 P280 Response: P304 + P340 +	air and keep comfortable for bre POISON CENTER/ doctor if you	dling. ive clothing/ rson to fresh eathing. Call a u feel unwell.
	P342 + P311	If experiencing respiratory symp POISON CENTER/ doctor.	otoms: Call a

Hazardous components which must be listed on the label:

1,3-Butanediol, polymer with 1,1'-methylenebis[isocyanatobenzene], 2,2'-oxybis[ethanol] and

1,2-propanediol

Diphenylmethanediisocyanate, isomeres and homologues

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.





Date of last issue: 06.03.2025	Version 5.5	Print Date 11.03.2025
Revision Date: 11.03.2025		

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Components			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
1,3-Butanediol, polymer with 1,1'-	155662-82-1	Acute Tox. 4; H332	>= 60 - < 80
meth-	Not Assigned	Skin Irrit. 2; H315	
ylenebis[isocyanatobenzene],	01-2119480402-45-	Eye Irrit. 2; H319	
2,2'-oxybis[ethanol] and 1,2-	XXXX	Resp. Sens. 1; H334	
propanediol		Skin Sens. 1; H317	
		Carc. 2; H351	
		STOT SE 3; H335	
		(Respiratory system)	
		STOT RE 2; H373	



of last issue: 06.03.2025 sion Date: 11.03.2025	Versio	n 5.5	Print Date 11.03.	
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % specific concentration limit Resp. Sens. 1; H334 >= 0,1 % specific concentration limit Skin Irrit. 2; H315 >= 5 % specific concentration limit Stot SE 3; H335 >= 5 %	>= 40 - < 60	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid me	easures
General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.



Date of last issue: 06.03.2025 Revision Date: 11.03.2025		Version 5.5	Print Date 11.03.202
In case of eye contact	:	Immediately flush eye(s) with plenty of water Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	r.
If swallowed	:	Do not induce vomiting without medical advi Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconse	
4.2 Most important sympto	ms and e	ffects, both acute and delayed	
Symptoms	:	Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Headache Dermatitis See Section 11 for more detailed information and symptoms.	n on health effects
Risks	:	irritant effects sensitising effects	
		Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or b ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolot exposure.	-
1.3 Indication of any imme	liato mor	lical attention and special treatment neede	ad .
Treatment		Treat symptomatically.	

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.



Date of last issue: 06.03.2025 Revision Date: 11.03.2025		Version 5.5	Print Date 11.03.202
5.2 Special hazards arising from	h th	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are know	n
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breath	ing apparatus.
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental relea	se	measures	
6.1 Personal precautions, prote	ctiv	e equipment and emergency procedures	
6.1 Personal precautions, protect Personal precautions	ctiv :		
		Use personal protective equipment.	
Personal precautions		Use personal protective equipment.	
Personal precautions 6.2 Environmental precautions	:	Use personal protective equipment. Deny access to unprotected persons. Do not flush into surface water or sanitary sev If the product contaminates rivers and lakes or respective authorities.	
Personal precautions 6.2 Environmental precautions Environmental precautions	:	Use personal protective equipment. Deny access to unprotected persons. Do not flush into surface water or sanitary sev If the product contaminates rivers and lakes or respective authorities.	r drains inform nd, silica gel,
Personal precautions 6.2 Environmental precautions Environmental precautions 6.3 Methods and material for co	:	Use personal protective equipment. Deny access to unprotected persons. Do not flush into surface water or sanitary sev If the product contaminates rivers and lakes o respective authorities. inment and cleaning up Soak up with inert absorbent material (e.g. sa acid binder, universal binder, sawdust).	r drains inform nd, silica gel,

7.1 Precautions for safe handling

Advice on safe handling	: Avoid formation of aerosol.
	Avoid exceeding the given occupational exposure limits (see section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
	Smoking, eating and drinking should be prohibited in the application area.
	Provide sufficient air exchange and/or exhaust in work rooms.



SikaBiresin[®] MC100 Part B

_

Date of last issue: 06.03.2025 Revision Date: 11.03.2025		Version 5.5	Print Date 11.03.2025
		Follow standard hygiene measures when handlin products	g chemical
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Hygiene measures	:	Handle in accordance with good industrial hygien practice. When using do not eat or drink. When u smoke. Wash hands before breaks and at the en	ising do not
7.2 Conditions for safe storage, i	nc	uding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ve place. Containers which are opened must be care sealed and kept upright to prevent leakage. Store ance with local regulations.	efully re-
Further information on stor- age stability	:	No decomposition if stored and applied as directed	ed.
7.3 Specific end use(s)			
Specific use(s)	:	Cleaning with aprotic polar solvents must be avoi Consult most current local Product Data Sheet pr use.	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
1,3-Butanediol, polymer with 1,1'- methylenebis[isocyanatobenzene], 2,2'- oxybis[ethanol] and 1,2-propanediol	155662-82-1	TWA	0,02 mg/m3 (NCO)	GB EH40
	asthma (also k can induce a s immunological become hyper- sometimes eve toms. These sy asthma. Not al come hyper-re those who are that can cause substances wh	ation: Substances the nown as asthmage tate of specific airw irritant or other me responsive, further en in tiny quantities, ymptoms can range I workers who are e sponsive and it is in likely to become hy occupational asthm ich may trigger the ng airway hyper-res	ns and respiratory ay hyper-respons chanism. Once the exposure to the s may cause respire in severity from a exposed to a sensi- npossible to identi- oper-responsive. na should be distin- symptoms of asth	v sensitisers) iveness via an e airways have substance, ratory symp- a runny nose to itiser will be- ify in advance Substances nguished from ma in people



Date of last issue: 06.03.2025 Revision Date: 11.03.2025 Version 5.5

Print Date 11.03.2025

	classified as as mation can be assessments of asthma., When stances that ca Where this is r standards of cor responsive. For COSHH requir sonably practic centrations sho ment is being of employees exp may cause occ consultation w degree of risk pational asthma assigned only asthma in the bered that othe pational asthma (www.hse.gov) Further informa	ease themselves. T sthmagens or respir found in the HSE p of the evidence for a rever it is reasonably an cause occupation not possible, the prir ontrol to prevent wo or substances that c res that exposure be cable. Activities givin ould receive particul considered. Health s oosed or liable to be cupational asthma a ith an occupational and level of surveilla to those substances categories shown in a. HSE's asthma w uk/asthma) provide STEL TWA ation: Skin, Dermal	atory sensitisers. ublication Asthma agents implicated y practicable, exp hal asthma should nary aim is to app rkers from becom an cause occupat e reduced to as low- ng rise to short-ter lar attention when surveillance is app e exposed to a sub health professiona ance., Capable of on in the list of WE s which may cause Table 1. It should these tables may eb pages further informatic 0,07 mg/m3 (NCO) 0,02 mg/m3 (NCO)	Further infor- igen? Critical in occupational osure to sub- l be prevented. bly adequate ing hyper- ional asthma, w as is rea- rm peak con- risk manage- propriate for all ostance which e appropriate al over the causing occu- ELs has been e occupational d be remem- y cause occu- on. GB EH40 98/24/EC 1 ensitisation,
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3 (NCO)	GB EH40
	Further inform	ation: Capable of ca		al asthma.
		STEL	0,07 mg/m3 (NCO)	GB EH40

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
1,3-Butanediol, polymer with 1,1'- methylenebis[isocyanatobenzene], 2,2'-oxybis[ethanol] and 1,2- propanediol	155662-82-1	isocyanate- derived diamine (Isocyanates): 1 µmol/mol creati- nine (Urine)	At the end of the period of expo- sure	GB EH40 BAT
Diphenylmethanediisocyanate, iso- meres and homologues	9016-87-9	isocyanate- derived diamine (Isocyanates): 1 μmol/mol creati- nine	At the end of the period of expo- sure	GB EH40 BAT



ision Date: 11.03.2025			
		(Urine)	
Exposure controls			
Engineering measures			
Maintain air concentrations Ensure adequate ventilation		occupational exposure standards. ecially in confined areas.	
Personal protective equip	ment		
Eye/face protection	:	Safety glasses with side-shields conforming Eye wash bottle with pure water	g to EN166
Hand protection	:	Chemical-resistant, impervious gloves comproved standard must be worn at all times in chemical products. Reference number EN is facturer specifications. Suitable for short time use or protection against butyl rubber/nitrile rubber gloves (> 0,1 mm Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	when handling 374. Follow manu- ainst splashes:
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. long-sleeved working clothing, long trouser and protective boots are additionally recom and stirring work.	s). Rubber aprons
Respiratory protection	:	In case of inadequate ventilation wear resp Respirator selection must be based on kno exposure levels, the hazards of the product ing limits of the selected respirator. Use a properly fitted NIOSH approved air-p respirator complying with an approved stan sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10 Ensure adequate ventilation. This can be a exhaust extraction or by general ventilation ods for determining inhalation exposure). T ticular to the mixing / stirring area. In case to to keep the concentrations under the occup limits then respiration protection measures Ensure adequate ventilation, especially in o	wn or anticipated t and the safe work- burifying or air-fed adard if a risk as- 0000 ppm chieved by local b. (EN 689 - Meth- his applies in par- this is not sufficent bational exposure must be used.
Environmental exposure of	ontre	als	
General advice		Do not flush into surface water or sanitary s	-

If the product contaminates rivers and lakes or drains inform

respective authorities.



Date of last issue: 06.03.2025 Revision Date: 11.03.2025 Version 5.5

Print Date 11.03.2025

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

 Physical state Colour		liquid red brown
Odour	:	characteristic
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	avn	losive limits
Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	ca. 175 mPa.s (25 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble



SikaBiresin[®] MC100 Part B

Date of last issue: 06.03.2025 Revision Date: 11.03.2025		Version 5.5	Print Date 11.03.2025
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Density	:	ca. 1,23 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid	: No data available
---------------------	---------------------

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.



Devision Dates 44.00.0005	Date of last issue: 06.03.2025
Revision Date: 11.03.2025	Revision Date: 11.03.2025

Version 5.5

Print Date 11.03.2025

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity	:	LD50 Oral (Rat): > 10.000 mg/kg
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.



Date of last issue: 06.03.2025	Version 5.5	Print Date 11.03.2025
Revision Date: 11.03.2025		

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation



Date of last issue: 06.03.2025 Revision Date: 11.03.2025	Version 5.5	Print Date 11.03.2025
	(EU) 2017/2100 or Commission Regulation levels of 0.1% or higher.	า (EU) 2018/605 at
12.7 Other adverse effects		
Product: Additional ecological infor- mation	: There is no data available for this product.	
SECTION 13: Disposal conside	erations	
13.1 Waste treatment methods		
Product	 The generation of waste should be avoided wherever possible. Empty containers or liners may retain some This material and its container must be disp way. Dispose of surplus and non-recyclable prod waste disposal contractor. Disposal of this product, solutions and any at all times comply with the requirements o protection and waste disposal legislation and local authority requirements. Avoid dispersal of spilled material and runct soil, waterways, drains and sewers. 	e product residues. posed of in a safe ducts via a licensed by-products should f environmental nd any regional

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good



Date of last issue: 06.03.2025 Revision Date: 11.03.2025	Version 5.5	Print Date 11.03.2025
14.4 Packing group		
ADR	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
IATA (Cargo)	: Not regulated as a dangerous good	
IATA (Passenger)	: Not regulated as a dangerous good	
14.5 Environmental hazards Not regulated as a dange	rous good	
14.6 Special precautions for Not applicable	user	
14.7 Maritime transport in bu Not applicable for product	Ik according to IMO instruments as supplied.	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 56: Diphenylme- thanediisocyanate, isomeres and homologues
		Number on list 74: Diphenylme- thanediisocyanate, isomeres and homologues
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable



Date of last issue: 06.03.2025 Revision Date: 11.03.2025	Version 5.5	Print Date 11.03.2025			
GB Export and import of hazardo Informed Consent (PIC) Regulati					
Control of Major Accident Hazards Regulations Not applicable 2015 (COMAH)					
Volatile organic compounds :	Law on the incentive tax for volatile organi (VOCV) no VOC duties	c compounds			
	Directive 2010/75/EU of 24 November 201 livestock rearing emissions (integrated pol and control) Not applicable				
If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.					
Health, safety and environ- mental regulation/legislation specific for the substance or mixture:	sidiary Regulations osidiary Regulations h Regulations cident Hazards				

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
Full text of other abbreviations		
A auto Tax		

Acute Tox.	: Acute toxicity
------------	------------------



Date of last issue: 06.03.2025
Revision Date: 11.03.2025

Version 5.5

Print Date 11.03.2025

Carc. Eye Irrit. Resp. Sens. Skin Irrit. Skin Sens.	 Carcinogenicity Eye irritation Respiratory sensitisation Skin irritation Skin sensitisation
STOT RE STOT SE 98/24/EC I	 Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values
GB EH40 GB EH40 BAT 98/24/EC I / STEL 98/24/EC I / TWA	 UK. EH40 WEL - Workplace Exposure Limits UK. Biological monitoring guidance values Limit values Short-term Limit values 8 hours
GB EH40 / TWA GB EH40 / STEL ADR	 Long-term exposure limit (8-hour TWA reference period) Short-term exposure limit (15-minute reference period) European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS DNEL EC50 GHS	 Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System
IATA IMDG LD50	 International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	 Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	 International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL PBT PNEC REACH	 Occupational Exposure Limit Persistent, bioaccumulative and toxic Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC vPvB	 Substances of Very High Concern Very persistent and very bioaccumulative

Further information

Classification o	f the mixture:	Classification procedure:
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method



Date of last issue: 06.03.2025 Revision Date: 11.03.2025		Version 5.5	Print Date 11.03.2025
Skin Sens. 1	H317	Calculation method	
Carc. 2	H351	Calculation method	
STOT SE 3	H335	Calculation method	
STOT RE 2	H373	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN