

PRODUCT DATA SHEET

SikaSeal® Trowel Mastic

Traditional pointing mastic for window and door frames

PRODUCT DESCRIPTION

SikaSeal® Trowel Mastic is a premium oil-based mastic for perimeter pointing around wood and metal window and door frames. SikaSeal® Trowel Mastic is ideally suited to pointing onto irregular stonework where it is difficult to apply cartridge packed sealants and for use on heritage buildings to match existing pointing.

USES

- For perimeter pointing of wood & metal frames.
- Suitable for wide and uneven joints.

PRODUCT INFORMATION

Packaging	3 kg and 6 kg tubs
Colour	Stone
Shelf Life	9 months from date of manufacture when stored according as instructed.
Storage Conditions	Store at between +5 °C and +25 °C in original containers. Any surface oil will blend in after mixing by hand.
Density	ca. 2.2 g/cm ³
Movement Capability	Low
Service Temperature	-20 °C to +50 °C
Yield	For facing, usage will be approximately 15 linear metres per kg for a triangular fillet with a 10 mm face section.
Ambient Air Temperature	+5 °C to +40 °C

CHARACTERISTICS / ADVANTAGES

- Sets hard for overpainting.
- Easier to apply than most competitive mastics.
- Added plasticiser improves adhesion and helps prevent cracking.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

Unsuitable for plastic frames or heat absorbing glass.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

SUBSTRATE PREPARATION

All surfaces must be clean, dry, free from dust, grease and other contamination.

APPLICATION

Apply using a thin pointing trowel or putty knife, working well into the joint and ensuring no voids remain. Finish smooth to a triangular fillet. When used for fillet pointing between frame and surround, joints should be a minimum width of 10 mm with a minimum depth of 6 mm.

OVERPAINTING AND MAINTENANCE

Product may be fully protected with an undercoat and top coat after a surface skin has formed. Allow 28 days drying before overpainting. Only use oil based paints. This will prolong the working life, but is not essential. Make good any defects on an annual basis.

CLEANING OF TOOLS

Use Sika® Wonder Wipes or white spirit to clean tools immediately after use

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

SikaSeal® Trowel Mastic
September 2026, Version 01.01
020511080000265626

SikaSealTrowelMastic-en-GB-(09-2026)-1-1.pdf