

S-Vap 5000 E SA

DECLARATION OF PERFORMANCE

No. 73170221

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	73170221
2	INTENDED USE/S	EN 13970:2004/A1:2006 Bitumen water vapor control layers
3	MANUFACTURER:	Sika Ltd Watchmead Welwyn Garden City AL7 1BQ
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3 System 4
6a	HARMONISED STANDARD:	EN 13970:2004/A1:2006
	Notified body/ies:	1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	EN 13970:2004/A 1:2006
Watertightness	Pass	System 3	
Tensile strength:			
Longitudinal (md) ¹	≥ 500 N/50 mm	System 4	
Transversal (cmd) ²	≥ 500 N/50 mm		
Impact resistance	≥ 150 mm	System 4	
Shear resistance of joints	≥ 400/50 N	System 4	
Low temperature flexibility	≤ - 20°C	System 4	
Tear resistance:			
Longitudinal (md) ¹	≥ 100 N	System 4	
Transversal (cmd) ²	≥ 100 N		
Durability against artificial ageing	Pass	System 4	
Durability against alkaline	Pass	System 4	
Water vapor permeability	≥ 1800 m	System 3	
Dangerous substances	NPD	System 4	

¹ md = machine direction

² cmd = cross machine direction

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Dean Grady
Function: Senior Product Engineer SPM
At Preston on 09 September 2025

Name : Alex Coward
Function: Head of Technical Roofing
At Preston on 09 September 2025



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

S-Vap 5000 E SA

73170221

2025.09 , ver. 1



06

Sika Services AG, Zurich, Switzerland

73170221

EN 13970:2004/A1:2006

Notified Body 1213

Bitumen water vapor control layers

Reaction to fire	Class E
Watertightness	Pass
Tensile strength:	
Longitudinal (md) ¹	≥ 500 N/50 mm
Transversal (cmd) ²	≥ 500 N/50 mm
Impact resistance	≥ 150 mm
Shear resistance of joints	≥ 400/50 N
Low temperature flexibility	≤ - 20°C
Tear resistance:	
Longitudinal (md) ¹	≥ 100 N
Transversal (cmd) ²	≥ 100 N
Durability against artificial ageing	Pass
Durability against alkaline	Pass
Water vapor permeability	≥ 1800 m

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

Declaration of Performance

S-Vap 5000 E SA

73170221

2025.09 , ver. 1

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

S-Vap 5000 E SA

73170221

2025.09 , ver. 1

Declaration of Performance

S-Vap 5000 E SA

73170221

2025.09 , ver. 1

