

S-Felt T 300

Separation, levelling and protection-layer

Product Description S-Felt T 300 is a separation, levelling and protection layer made of polyester (PES).

Uses S-Felt T 300 is used as a separation and levelling layer between Sika-Trocal® membranes and incompatible substrates.
S-Felt T 300 can also be used as a protection layer between Sika-Trocal® membranes and any protective topping or pavement.

Characteristics / Advantages

- UV stable
- Bitumen resistant
- Non decaying
- High resistance to bacterial infestation
- Suitable for mechanical fastening (drill proved)
- Long lifespan
- Ease of application
- Recyclable

Tests

Approvals / Standards

- Reaction to fire according to EN 13501-1
- Quality management system EN ISO 9001/14001

Product Data

Form

Appearance Surface: structured

Colour white

Packaging S-Felt T 300 rolls are wrapped individually in transparant/blue PE-foil.

Roll length: 50.00 m
Roll width: 2.00 m
Roll weight: 30.00 kg

Storage

Storage Conditions S-Felt T 300 rolls should be stored in dry conditions and in horizontal position. Do not stack pallets of rolls during transport or storage.

Shelf-Life S-Felt T 300 does not expire during correct storage.



Technical Data

Material Basis	100 % PES fibres	
Length	50.00 m	
Width	2.00 m (+/- 2 %)	
Thickness	2.50 mm (+/- 10 %)	EN 29073-2
Mass per unit area	300 g/m ² (+/- 10 %)	EN 29073-1
Reaction to fire:		EN ISO 11925-2: 2002, Classification to EN 13501-1
Freely suspend	E-d2	
On polystyrene board	E	
On wood	E	
On concrete	E	
Tensile strength:		
Longitudinal	≥ 300 N/50 mm	EN 29073-3
Transversal	≥ 350 N/50 mm	EN 29073-3
Elongation:		
Longitudinal	≤ 90 %	EN 29073-3
Transversal	≤ 90 %	EN 29073-3

System Information

System Structure	Ancillary products:	- Sarnacol [®] 2170 - Sarnacol [®] T 660
	Compatible products:	All types of Sika-Trocal [®] membranes

Installation Instructions

Application Method	S-Felt T 300 is loose laid according to the valid installation instructions for Sika-Trocal [®] . Adjoining sheets must overlap at least 50 mm.
---------------------------	---

Notes on Installation / Limits

Installation works must be carried out only by Sika instructed contractors for roofing.

Temperature limits for the installation of the S-Felt T 300:
Substrate temperature: -30 °C min. / +60 °C max.
Ambient temperature: -20 °C min. / +60 °C max

Installation of some ancillary products, e.g. contact adhesives / cleaners is limited to temperatures above +5 °C. Please observe information given by Product Data Sheets.

Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

Value Base	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
Local Restrictions	Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.
Ecology, Health and Safety Information	The product does not fall within the EC-regulation of hazardous goods. As a result, a material safety data sheet following EC-Guideline 91/155 EWG is not needed to bring the product to the market, transport or use it. The product does not damage the environment when used as specified.
Protective Measures	Fresh air ventilation must be ensured, when working (welding) in closed rooms. Local safety regulations must be observed.
Transportation Class	The product is not classified as hazardous good for transport.
Disposal	The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

Legal note: The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Limited
 Watchmead
 Welwyn Garden City
 Hertfordshire
 AL7 1BQ
 United Kingdom
 Phone +44 1707 394444
 Telefax +44 1707 329129
www.sika.co.uk
 email: sales@uk.sika.com



Certificate No. EMS 4308



Certificate No. FM 12504