

# PRODUCT DATA SHEET

# Sika® One Strike Filler®

Ready-mixed, quick drying, revolutionary lightweight filler.

# PRODUCT DESCRIPTION

Sika® One Strike Filler® is a ready-mixed lightweight filler for the preparation of numerous surfaces prior to painting or wallpapering.

Based on high strength lightweight polymeric fillers, the product outperforms conventional fillers in most applications. Designed for professional and D.I.Y use. Sika® One Strike Filler® finished soft and flexible, requiring little or no sanding. Ready to paint or wallpaper in just 30 minutes.

# **USES**

Fills gaps and holes in:

- Plaster
- Brick
- Stone
- Wood
- Render

# **CHARACTERISTICS / ADVANTAGES**

- Fills up to 75 mm deep in one application No need to build up layers of filler.
- Easy to use lightweight paste is incredibly easy to apply.
- No sanding required finished to a smooth surface.
- No sagging the lightweight properties of Sika® One Strike Filler® prevent sagging even on ceilings.
- Non-shrink will not shrink back whilst drying.
- Quick drying ready to paint or paper in just 30 minutes.
- Overpaintable with most solvent based and emulsion paints.
- Overstainable.
- Internal and external use.
- Dries brilliant white.

# PRODUCT INFORMATION

Packaging	250 mL, 450 mL, 1 L, 2.5 L & 5 L Tubs
Appearance / Colour	Lightweight brilliant white paste
Shelf Life	24 months from date of manufacture when stored according to manufacturers instructions.
Storage Conditions	Store between +5 °C to +25 °C
Density	0.28 - 0.35 g/cm <sup>3</sup>
Movement Capability	Low

#### APPLICATION INFORMATION

Ambient Air Temperature	+5 °C to +30 °C
Hole dimension	Maximum width 50 mm Maximum depth 75 mm

Product Data Sheet Sika® One Strike Filler®

May 2025, Version 01.01 021840303000000012

#### **VALUE BASE**

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

# **USES**

- Do not use to fill plastic or metals.
- Do not apply when rain is imminent (external use).
- Do not apply in temperatures (ambient and surface) below +5 °C.
- Freezing damages the product.

# **ECOLOGY, HEALTH AND SAFETY**

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

#### APPLICATION INSTRUCTIONS

#### **SUBSTRATE QUALITY / PRE-TREATMENT**

All surfaces must be clean, dry and free from dust, grease and other contamination.

#### **APPLICATION**

Apply direct from tub with spatula/spreader. Smooth over surface and allow to dry. Sanding is not normally required although the product may be sanded if required.

#### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields

#### **LEGAL NOTES**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

# SIKA LIMITED

Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ Tel: 01707 394444 Web: www.sika.co.uk Twitter: @SikaLimited







Product Data Sheet Sika® One Strike Filler® May 2025, Version 01.01 021840303000000012



SikaOneStrikeFiller-en-GB-(05-2025)-1-1.pdf