

## PRODUCT DATA SHEET

# SikaRoof® Aluminium Edging Adhesive

## ALUMINIUM EDGING ADHESIVE

## PRODUCT DESCRIPTION

SikaRoof® Aluminium Edging Adhesive is a one part general purpose high modulus building sealant based on hybrid polymer technology. Designed as a general purpose joint sealer for perimeter edge sealing in suitable glazing application.

## USES

General purpose joint sealer for perimeter edge sealant.

## CHARACTERISTICS / ADVANTAGES

- Waterproof and weatherproof
- Quick curing
- Solvent free

## APPROVALS / STANDARDS

Conforms to ISO 11600 accreditations of class F25HM

## PRODUCT INFORMATION

Chemical Base	Polysiloxane
Packaging	Cartridge
Appearance / Colour	Black
Shelf Life	12 months in original unopened containers
Storage Conditions	Store in cool dry conditions between +5°C and 25°C
Density	Approximately 1.24g/ml
Consistency	Stable paste
Service Temperature	-60°C + 180°C

## APPLICATION INFORMATION

Yield	Approximately 27 linear metres per cartridge
Ambient Air Temperature	5°C to 35°C
Tack Free Time	Skin formation after 5 minutes at 23°C with 50% relative humidity

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### APPLICATION

- All surfaces must be cleaned and free from dust, grease and frost. The surface can be damp, but have no standing water.
- Do not use on surfaces that bleed oils or plasticisers.
- Do not use in joints that are to be continually immersed.
- Do not use on Polypropylene, Polyethylene or Teflon.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



Product Data Sheet  
SikaRoof® Aluminium Edging Adhesive  
May 2021, Version 01.01  
020945079000000013

SikaRoofAluminiumEdgingAdhesive-en-GB-(05-2021)-1-1.pdf

