

PRODUCT DATA SHEET

SS Waterstop

WESTEC STAINLESS STEEL CHEMICALLY RESISTANT WATERSTOP

PRODUCT DESCRIPTION

316 Stainless Steel Waterstop for joint waterproofing.

USES

High temperature environments that exceed 250°F or for the most severe chemical applications

CHARACTERISTICS / ADVANTAGES

Embedded in concrete, across and/or along the joint, waterstops form a watertight diaphragm that prevents the passage of liquid through the joint. Suitable for high temperature applications and contact with a wide range of chemicals including oils, fuels, acids, bases, and numerous solvents.

PRODUCT INFORMATION

Packaging	Various profiles, provided in 10 ft lengths
Shelf Life	N/A
Storage Conditions	N/A

TECHNICAL INFORMATION

Tensile Strength	75000 psi	(ASTM A370)
Elongation	40% Duct Elongation in 2" min.	(ASTM A370)
Tear Strength	30000 psi Yield Strength	(ASTM A370)
Chemical Resistance	Resistant to a wide range of chemicals. Please refer to the Westec® Chemical Resistance Chart available at usa.sika.com for commonly used chemicals or contact the waterproofing engineering department for any chemicals not shown.	
Maximum Water Pressure	Varies depending on profile selection	
Ambient Maximum Temperature of Liquids	> 250°F	

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Westec® Stainless Steel Waterstop must be installed prior to concrete placement to ensure proper positioning and concrete consolidation around the waterstop. All transitions, intersections, and splices should be tig welded to maintain continuity. Factory Made Fabrications are recommended for all intersections and changes of direction. Specific installation requirements will vary depending on the style of profile, please refer to Sika's Stainless Steel Waterstop Installation Guide available at usa.sika.com.

FURTHER DOCUMENTS

Many applications that have traditionally used Stainless Steel Waterstop can be served with Westec TPER Waterstop, including ozone contact structures.

LIMITATIONS

The size, shape, and style of waterstop should be based on specific application needs. Please consult Sika Waterproofing on 01707 394444 for assistance with profile selection.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika

products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED
Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED
Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland



Product Data Sheet
SS Waterstop
November 2019, Version 01.01
020703100100000305

SSWaterstop-en-GB-(11-2019)-1-1.pdf