

PRODUCT DATA SHEET

CromaSlate Dry Fix Slate Verge

Dry fix verge and connector.

PRODUCT DESCRIPTION

Provides a clean, traditional slate verge finish while eliminating maintenance issues associated with mortar.

Mortar free dry fix verge system designed for natural and man made slates up to 6 mm thick.

USES

- Protects and covers the ends of slating battens for a traditional verge appearance.
- Provides a weatherproof, maintenance free verge solution.
- Can be used in new build and refurbishment applications.

PRODUCT INFORMATION

Packaging	Both the verge and the connector are in cardboard boxes of 10 units.
Colour	Black
Shelf Life	Physical plastic items have not had their shelf life determined due to longevity.
Storage Conditions	Store in a cool dry place, away from direct sunlight.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Only suitable for slates up to 6 mm thick - not intended for larger or thicker slate types.
- Not designed for roof tiles; CromaSlate is slate-specific, for tile verges use CromaVerge.
- Must only be installed on roofs where battens are flush with brickwork or bargeboard, otherwise cor-

CHARACTERISTICS / ADVANTAGES

- Verge supplied in 2 m lengths, lightweight and easy to handle.
- Quick installation - significantly faster than traditional mortar bedding.
- Improved profile for enhanced roofline appearance.
- Fully weatherproof & maintenance free system.
- Suitable for fitting in any weather.
- Requires no specialist tools or skills.

- rect seating and alignment may not be achievable.
- Verge connector must be used on runs longer than 2 m: omitting it may compromise performance.
- If overhang into the gutter is restricted, trimming is required, meaning installations with fixed or unusual gutter profiles may require adjustment.
- While installable in poor weather, application of sealant at connection joints requires conditions where sealant can bond properly.
- Not suitable for roofs where slates are not fixed into the verge overlap, as this is required for mechanical restraint.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

- Ensure battens are installed flush to the gable edge.
- Fix verge directly on top of battens, allowing 50 mm gutter overhang (trimming may be required).
- After verge is set out, lay and fix slates into the overlap of the verge unit.
- The connector must be used whenever the verge run exceeds 2 m.
- Insert the connector between adjoining verge lengths to maintain alignment and continuity.
- Apply a small bead of clear waterproof sealant at the joint to ensure weather protection.
- Continue installing the remaining verge lengths, ensuring each section is properly seated within the connector

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
CromaSlate Dry Fix Slate Verge
March 2026, Version 02.01
020945201000247381

CromaSlateDryFixSlateVerge-en-GB-(03-2026)-2-1.pdf