

Date of last issue: 16.06.2023	Version 5.3	Print Date 29.02.2024
Revision Date: 25.01.2024		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : EVERBUILD B1 Gungrade Fire Foam

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Fire protection system

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited
		Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person	:	EHS@uk.sika.com
responsible for the SDS		

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Effects on or via lactation	H362: May cause harm to breast-fed children.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.



Date of last issue: 16.06.2023 Revision Date: 25.01.2024			Version 5.3	Print Date 29.02.2024
Specific target organ toxicity - repeated exposure, Category 2		H373: May cause damage to organs through pro- longed or repeated exposure if inhaled.		
Long-term (chronic) aquatic egory 3	Long-term (chronic) aquatic hazard, Cat- egory 3		H412: Harmful to aquatic life with fects.	th long lasting ef-
2.2 Label elements				
Labelling (REGULATION (EC) No	o 1272/20	08)	
Hazard pictograms	:	*		
Signal word	: [Danger		
Hazard statements	+ + + + + + + + + +	H222 H229 H315 H317 H319 H334 H335 H351 H362 H373 H412	Extremely flammable aero Pressurised container: Ma Causes skin irritation. May cause an allergic skii Causes serious eye irritat May cause allergy or asth breathing difficulties if inh May cause respiratory irri Suspected of causing car May cause harm to breas May cause damage to org longed or repeated expos Harmful to aquatic life with fects.	ay burst if heated. n reaction. ion. ma symptoms or aled. tation. hcer. t-fed children. gans through pro- bure if inhaled.
Precautionary statements		P101 P102	If medical advice is neede container or label at hand Keep out of reach of child	
	F	Preventio	n:	
		P201	Obtain special instruction	s before use.
		P210	Keep away from heat, hot open flames and other igr smoking.	t surfaces, sparks,
	F	P211	Do not spray on an open tion source.	flame or other igni-
		P251	Do not pierce or burn, eve	
	F	P260	Do not breathe dust/ fume pours/ spray.	e/ gas/ mist/ va-
		P263	Avoid contact during preg nursing.	nancy and while
		P271	Use only outdoors or in a ea.	well-ventilated ar-
		2000		

P280

Wear protective gloves/ protective clothing/



Date of last issue: 16.06.2023 Revision Date: 25.01.2024	Version 5.3		Print Date 29.02.2024
		eye protection/ face protection.	
	Response:		
	P304 + P340 +	P312 IF INHALED: Remove pe air and keep comfortable for bro POISON CENTER/ doctor if yo	eathing. Call a
	P308 + P313 IF exposed or concerned: Get medical ad- vice/ attention.		
	Storage:		
	P405 P410 + P412	Store locked up. Protect from sunlight. Do not ex peratures exceeding 50 °C/ 122	•
	Disposal:		
	P501	Dispose of contents/container in with local regulation.	n accordance

Hazardous components which must be listed on the label:

Formaldehyde, oligomeric reaction products with aniline and phosgene alkanes, C14-17, chloro

Additional Labelling

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Date of last issue: 16.06.2023 Revision Date: 25.01.2024 Version 5.3

Print Date 29.02.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
tris(2-chloro-1-methylethyl) phos- phate	13674-84-5 237-158-7 01-2119486772-26- XXXX (covered by EC 807-935-0)	Acute Tox. 4; H302 Aquatic Chronic 3; H412	>= 20 - < 25
Formaldehyde, oligomeric reac- tion products with aniline and phosgene	32055-14-4 500-079-6 01-2119457024-46- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H314 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 \longrightarrow SPECIFIC concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 % Acute toxicity estimate Acute inhalation tox- icity (dust/mist): 1,5 mg/l	>= 10 - < 20
propane	74-98-6 200-827-9 01-2119486944-21- XXXX	Flam. Gas 1A; H220	>= 10 - < 20
isobutane	75-28-5 200-857-2 01-2119485395-27- XXXX	Flam. Gas 1A; H220	>= 10 - < 20



Date of last issue: 16.06.2023
Revision Date: 25.01.2024

Version 5.3

alkanes, C14-17, chloro	85535-85-9 287-477-0 01-2119519269-33- XXXX	Lact.H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH066 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	>= 1 - < 2,5
Substances with a workplace expo	sure limit :		
dimethyl ether	115-10-6 204-065-8 01-2119472128-37- XXXX	Flam. Gas 1A; H220	>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important sympton	ns and effects, both acute and delayed
Symptoms	: Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema



Date of last issue: 16.06.2023 Revision Date: 25.01.2024	Version 5.3	Print Date 29.02.2024
	Dermatitis See Section 11 for more detailed informatio and symptoms.	n on health effects
Risks	: irritant effects sensitising effects	
	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or l ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause harm to breast-fed children. May cause damage to organs through prolo exposure if inhaled.	-
•	edical attention and special treatment need	ed
Treatment	: Treat symptomatically.	
SECTION 5: Firefighting measu	Ires	
5.1 Extinguishing media		
Suitable extinguishing media	: Use extinguishing measures that are approprotection of the surrounding environment	
Unsuitable extinguishing media	: Water	
5.2 Special hazards arising from t	he substance or mixture	
Hazardous combustion prod- ucts	: No hazardous combustion products are kno	own
5.3 Advice for firefighters		
Special protective equipment for firefighters	: In the event of fire, wear self-contained brea	athing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment.
		Deny access to unprotected persons.



Date of last issue: 16.06.2023	Version 5.3	Print Date 29.02.2024
Revision Date: 25.01.2024		

6.2 Environmental precautions

Environmental precautions

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label



Date of last issue: 16.06.2023 Revision Date: 25.01.2024		Version 5.3	Print Date 29.02.2024	
		precautions. Store in accordance with local regul	ations.	
Further information on stor- age stability	:	No decomposition if stored and applied as direct	ed.	

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC
	Further inform	Further information: Indicative		
		TWA	400 ppm 766 mg/m3	GB EH40
		STEL	500 ppm 958 mg/m3	GB EH40

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers).
Respiratory protection :	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances



Date of last issue: 16.06.2023 Revision Date: 25.01.2024	Version 5.3	Print Date 29.02.2024
	Ensure adequate ventilation, especially in confine When workers are facing concentrations above t limit they must use appropriate certified respirato	he exposure
Environmental exposure control	ols	
General advice :	Do not flush into surface water or sanitary sewer If the product contaminates rivers and lakes or do respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

an	
:	aerosol pink
:	slight
:	No data available
:	No data available
:	No data available
exp	losive limits
:	No data available
:	No data available
:	-4 °C Method: closed cup
:	No data available
:	No data available
:	Not applicable
	: : : :

Viscosity



Date of last issue: 16.06.2023 Revision Date: 25.01.2024		Version 5.3	Print Date 29.02.2024
Viscosity, kinematic	:	No data available	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	8300 hPa	
Density	:	ca. 1 g/cm3	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions					
	Stable under recommended storage conditions.				

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.



Date of last issue: 16.06.2023
Revision Date: 25.01.2024

Version 5.3

Print Date 29.02.2024

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Formaldehyde, oligomeric reaction products with aniline and phosgene:

Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement
		Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

Skin corrosion/irritation

Causes skin irritation.

Components:

alkanes, C14-17, chloro:

Assessment

: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

May cause harm to breast-fed children.

STOT - single exposure

May cause respiratory irritation.



Date of last issue: 16.06.2023	Version 5.3	Print Date 29.02.2024
Revision Date: 25.01.2024		

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

Components:

alkanes, C14-17, chloro:

M-Factor (Acute aquatic tox- : 1 icity)

M-Factor (Chronic aquatic : 10 toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.



Date of last issue: 16.06.2023 Revision Date: 25.01.2024 Version 5.3

Print Date 29.02.2024

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Р	r∩	Ч		ct
Γ.	ιu	u	u	Cι

:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional
	local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 1950	
IMDG	:	UN 1950	
ΙΑΤΑ	:	UN 1950	
14.2 UN proper shipping name			
ADR	:	AEROSOLS	
IMDG	:	AEROSOLS	
ΙΑΤΑ	:	Aerosols, flammable	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	2	2.1
IMDG	:	2.1	
ΙΑΤΑ	:	2.1	
14.4 Packing group			
ADR Packing group Classification Code Labels Tunnel restriction code IMDG		Not assigned by regul 5F 2.1 (D)	lation



Date of last issue: 16.06.2023 Revision Date: 25.01.2024	Version 5.3	Print Date 29.02.2024
Packing group Labels EmS Code	 Not assigned by regulation 2.1 F-D, S-U 	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	 203 Y203 Not assigned by regulation Flammable Gas 	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	 203 Y203 Not assigned by regulation Flammable Gas 	
14.5 Environmental hazards		
ADR Environmentally hazardous IMDG Marine pollutant	: no	
IATA (Passenger) Environmentally hazardous	: no	

IATA (Cargo) Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable



Date of last issue: 16.06.2023 Revision Date: 25.01.2024	Version 5.3	Print Date 29.02.2024
International Chemical Weapons Schedules of Toxic Chemicals an	· · ·	
Regulation (EC) No 1005/2009 or plete the ozone layer	n substances that de- : Not applicable	
UK REACH List of substances su (Annex XIV)	bject to authorisation : Not applicable	
Volatile organic compounds :	Law on the incentive tax for volatile organic (VOCV) Volatile organic compounds (VOC) content Directive 2010/75/EU of 24 November 2010 emissions (integrated pollution prevention a Volatile organic compounds (VOC) content 35% w/w, 350 g/l VOC content excluding water	: 35% w/w D on industrial and control)

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ-	: Environmental Protection Act 1990 & Subsidiary Regulations
mental regulation/legislation	Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or	Control of Substances Hazardous to Health Regulations
mixture:	(COSHH)
	May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Other regulations:

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H220	: Extremely flammable gas.
H302	: Harmful if swallowed.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficul-



Date of last issue: 16.06.2023 Revision Date: 25.01.2024		Version 5.3	Print Date 29.02.2024
		ties if inhaled.	
H335		May cause respiratory irritation.	
H351	:	Suspected of causing cancer.	
	:		
H362	÷	May cause harm to breast-fed children.	
H373	:	May cause damage to organs through performing exposure if inhaled.	prolonged or repeated
H400	:	Very toxic to aquatic life.	
H410	:	Very toxic to aquatic life with long lastin	ng effects.
H412	:	Harmful to aquatic life with long lasting	
Full text of other abbreviat	tions		
Acute Tox.	:	Acute toxicity	
Aquatic Acute	:	Short-term (acute) aquatic hazard	
Aquatic Chronic	:	Long-term (chronic) aquatic hazard	
Carc.		Carcinogenicity	
Eye Irrit.	:	Eye irritation	
Flam. Gas	:	Flammable gases	
Lact.	:	Effects on or via lactation	
	:		
Resp. Sens.		Respiratory sensitisation	
Skin Irrit.	:	Skin irritation	
Skin Sens.	:	Skin sensitisation	
STOT RE	:	Specific target organ toxicity - repeated	
STOT SE	:	Specific target organ toxicity - single ex	posure
2000/39/EC	:	Europe. Commission Directive 2000/39	/EC establishing a first
		list of indicative occupational exposure	limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure	
2000/39/EC / TWA		Limit Value - eight hours	
GB EH40 / TWA		Long-term exposure limit (8-hour TWA	reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute re	
ADR	:	European Agreement concerning the In	
ADK	•		itemational Carnage of
040		Dangerous Goods by Road	
CAS	:	Chemical Abstracts Service	
DNEL	:	Derived no-effect level	
EC50	:	Half maximal effective concentration	
GHS	:	Globally Harmonized System	
ΙΑΤΑ	:	International Air Transport Association	
IMDG	:	International Maritime Code for Danger	ous Goods
LD50	:	Median lethal dosis (the amount of a m	aterial, given all at
		once, which causes the death of 50% (
		test animals)	
LC50		Median lethal concentration (concentra	tions of the chemical in
2030	•	air that kills 50% of the test animals dur	
			ning the observation
		period)	
MARPOL	:	International Convention for the Preven	
		Ships, 1973 as modified by the Protoco	ol of 1978
OEL	:	Occupational Exposure Limit	
PBT	:	Persistent, bioaccumulative and toxic	
PNEC	:	Predicted no effect concentration	
REACH	:	Regulation (EC) No 1907/2006 of the E	uropean Parliament
· · · • •	•	and of the Council of 18 December 200	
		istration, Evaluation, Authorisation and	
		cals (REACH), establishing a Europear	



Date of last issue: 16.06.2023 Revision Date: 25.01.2024		Version 5.3	Print Date 29.02.2024
SVHC vPvB		f Very High Concern nt and very bioaccumulative	
Further information			
Classification of the mixtu	ıre:	Classification proced	ure:
Aerosol 1	H222, H229	Calculation method	
Skin Irrit. 2	H315	Calculation method	
Eye Irrit. 2	H319	Calculation method	
Resp. Sens. 1	H334	Calculation method	
Skin Sens. 1	H317	Calculation method	
Carc. 2	H351	Calculation method	
Lact.	H362	Calculation method	
STOT SE 3	H335	Calculation method	
STOT RE 2	H373	Calculation method	
Aquatic Chronic 3	H412	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN