according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Separol® W-160

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Special system

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com

responsible for the SDS

1.4 Emergency telephone number

+44 (0)1707 363899 (available during office hours).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : **Prevention:**

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/container in accordance


with local regulation.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160





SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
ethanediol	107-21-1 203-473-3 01-2119456816-28- XXXX	Acute Tox. 4; H302 STOT RE 2; H373	>= 2,5 - < 5
Ethanol, 2,2'-iminobis-, N-C12-18-alkyl derivs.	71786-60-2 276-014-8 01-2119957489-17- XXXX	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,025 - < 0,25
Phosphoric acid, isotridecyl ester Contains: Alcohols, C11-14-iso-, C13-rich >= 0,1 - <= 5 %	52933-07-0 258-261-3	Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 1B; H360 Aquatic Chronic 2; H411	>= 0,025 - < 0,25

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : See Section 11 for more detailed information on health effects

and symptoms.

according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160



Risks No known significant effects or hazards.

4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. Treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : For personal protection see section 8.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Wipe up with absorbent material (e.g. cloth, fleece).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling For personal protection see section 8.

Follow standard hygiene measures when handling chemical

according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160

Version 1.0 Print Date 27.02.2019

products

Advice on protection against

fire and explosion

Revision Date 27.02.2019

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
ethanediol	107-21-1	STEL	40 ppm 104 mg/m3	2000/39/EC	
Further information	Identifies the possibility of significant uptake through the skin, Indicative				
		TWA	20 ppm 52 mg/m3	2000/39/EC	
Further information	Identifies the possibility of significant uptake through the skin, Indicative				
		TWA (Vapour)	20 ppm 52 mg/m3	GB EH40	
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		TWA (particles)	10 mg/m3	GB EH40	
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		STEL (Vapour)	40 ppm 104 mg/m3	GB EH40	
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160



Revision Date 27.02.2019 Version 1.0 Print Date 27.02.2019

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : white

Odour : characteristic

Odour Threshold : No data available

pH : not determined

Melting point/range / Freezing : No data available

point

according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160

Revision Date 27.02.2019 Version 1.0

Boiling point/boiling range : No data available

Flash point : > 101 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper : No data available

flammability limit

Lower explosion limit / Lower : No data available

flammability limit

Vapour pressure : 23 hPa

Relative vapour density : No data available

: ca. 0,99 g/cm3 (20 °C) Density

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : < 10 mPa.s (20 °C)

Viscosity, kinematic : < 6,9 mm2/s (40 °C)

Explosive properties : No data available

: No data available Oxidizing properties

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160

Revision Date 27.02.2019 Version 1.0 Print Date



10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

ethanediol:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg

Method: Converted acute toxicity point estimate

Ethanol, 2,2'-iminobis-, N-C12-18-alkyl derivs.:

Acute oral toxicity : LD50 Oral (Rat): 500 - 2.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160

Revision Date 27.02.2019 Version 1.0



Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Ethanol, 2,2'-iminobis-, N-C12-18-alkyl derivs.:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0,1 mg/l

Exposure time: 96 h

M-Factor (Acute aquatic tox- : 10

icity)

Toxicity to daphnia and other : EC50: 0,84 mg/l

aquatic invertebrates (Chron-

ic toxicity)

Exposure time: 48 d

Species: Daphnia magna (Water flea)

M-Factor (Chronic aquatic

toxicity)

: 10

Phosphoric acid, isotridecyl ester:

Toxicity to daphnia and other : EC50: 6,4 mg/l aquatic invertebrates (Chron-

Exposure time: 48 h

ic toxicity) Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Product:

Biodegradability Result: Biodegradable

Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160



Revision Date 27.02.2019

Assessment

This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160

Revision Date 27.02.2019 Version 1.0 Print D



14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: < 0,01 %

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content:

0,23 %, 7,89 g/l

according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160



Revision Date 27.02.2019 Version 1.0 Print Date 27.02.2019

VOC content excluding water

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H318 : Causes serious eye damage.

H360 : May damage fertility or the unborn child.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Repr. : Reproductive toxicity Skin Corr. : Skin corrosion Skin Irrit. : Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

according to Regulation (EC) No. 1907/2006

Sika® Separol® W-160



Revision Date 27.02.2019 Version 1.0 Print Date 27.02.2019

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Aquatic Chronic 3 H412 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GB / EN