

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sika Boom® Fire Guard B2

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane foam

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
Telephone : +44 (0)1707 394444  
Telefax : +44 (0)1707 329129  
E-mail address of person : EHS@uk.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)  
24 Hour Emergency Telephone Number +44 870 190 6777

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|                                                                                  |                                                                                         |
|----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Aerosols, Category 1                                                             | H222: Extremely flammable aerosol.<br>H229: Pressurised container: May burst if heated. |
| Skin irritation, Category 2                                                      | H315: Causes skin irritation.                                                           |
| Eye irritation, Category 2                                                       | H319: Causes serious eye irritation.                                                    |
| Respiratory sensitisation, Category 1                                            | H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.        |
| Skin sensitisation, Category 1                                                   | H317: May cause an allergic skin reaction.                                              |
| Carcinogenicity, Category 2                                                      | H351: Suspected of causing cancer.                                                      |
| Effects on or via lactation                                                      | H362: May cause harm to breast-fed children.                                            |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation.                                                 |
| Specific target organ toxicity - repeated exposure, Category 2                   | H373: May cause damage to organs through prolonged or repeated exposure if inhaled.     |
| Long-term (chronic) aquatic hazard, Category 4                                   | H413: May cause long lasting harmful effects to aquatic life.                           |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H362 May cause harm to breast-fed children.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.  
H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements :

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
**Prevention:**  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe dust or mist.  
P263 Avoid contact during pregnancy and while nursing.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

### Storage:

P405 Store locked up.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

P410 + P412      Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Disposal:

P501      Dispose of contents/container in accordance with local regulation.

### Hazardous components which must be listed on the label:

Reaction products of phosphoryl trichloride and 2-methyloxirane  
Diphenylmethanediisocyanate, isomeres and oligomeric  
alkanes, C14-17, chloro

### Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

### 2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name                                                   | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number         | Classification                                                                                                                                                                                                                                                                                                                                                                                                                                      | Concentration<br>(% w/w) |
|-----------------------------------------------------------------|---------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Reaction products of phosphoryl trichloride and 2-methyloxirane | 1244733-77-4<br>807-935-0<br>01-2119486772-26-XXXX            | Acute Tox. 4; H302<br>Carc. 2; H351<br>Aquatic Chronic 3; H412<br><br>Acute toxicity estimate<br><br>Acute oral toxicity: 630 mg/kg                                                                                                                                                                                                                                                                                                                 | >= 10 - < 20             |
| Diphenylmethanediisocyanate, isomeres and oligomerics           | 32055-14-4<br>Not Assigned<br>01-2119457024-46-XXXX           | Acute Tox. 4; H332<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>Carc. 2; H351<br>STOT SE 3; H335 (Respiratory system)<br>STOT RE 2; H373<br><br>specific concentration limit<br>Eye Irrit. 2; H319<br>>= 5 %<br>Resp. Sens. 1; H334<br>>= 0,1 %<br>Skin Irrit. 2; H315<br>>= 5 %<br>STOT SE 3; H335<br>>= 5 %<br><br>Acute toxicity estimate<br><br>Acute inhalation toxicity (dust/mist): 1,5 mg/l | >= 10 - < 20             |
| isobutane                                                       | 75-28-5<br>200-857-2<br>601-004-00-0<br>01-2119485395-27-XXXX | Flam. Gas 1A; H220                                                                                                                                                                                                                                                                                                                                                                                                                                  | >= 5 - < 10              |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

|                                              |                                                                  |                                                                                                                                                                      |                  |
|----------------------------------------------|------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| propane                                      | 74-98-6<br>200-827-9<br>601-003-00-5<br>01-2119486944-21-XXXX    | Flam. Gas 1A; H220                                                                                                                                                   | $\geq 2,5 - < 5$ |
| alkanes, C14-17, chloro                      | 85535-85-9<br>287-477-0<br>602-095-00-X<br>01-2119519269-33-XXXX | Lact.H362<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br>EUH066<br><br>M-Factor (Acute aquatic toxicity): 1<br>M-Factor (Chronic aquatic toxicity): 10 | $\geq 1 - < 2,5$ |
| Substances with a workplace exposure limit : |                                                                  |                                                                                                                                                                      |                  |
| dimethyl ether                               | 115-10-6<br>204-065-8<br>603-019-00-8<br>01-2119472128-37-XXXX   | Flam. Gas 1A; H220                                                                                                                                                   | $\geq 10 - < 20$ |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms | : Asthmatic appearance<br>Cough<br>Respiratory disorder<br>Allergic reactions<br>Excessive lachrymation<br>Erythema<br>Dermatitis<br>See Section 11 for more detailed information on health effects and symptoms.                                                                                                                                                                                                                |
| Risks    | : irritant effects<br>sensitising effects<br><br>Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye irritation.<br>May cause allergy or asthma symptoms or breathing difficulties if inhaled.<br>May cause respiratory irritation.<br>Suspected of causing cancer.<br>May cause harm to breast-fed children.<br>May cause damage to organs through prolonged or repeated exposure if inhaled. |

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray jet  
Dry powder  
Foam  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Nitrogen oxides (NO<sub>x</sub>)  
Hydrogen cyanide (hydrocyanic acid)  
Chlorine compounds

### 5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

for firefighters

Further information : Use water spray to cool unopened containers.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Allow to solidify, use mechanical handling equipment.  
Ventilate the area.

#### 6.4 Reference to other sections

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components                      | CAS-No.  | Value type (Form of exposure) | Control parameters *                 | Basis *    |
|---------------------------------|----------|-------------------------------|--------------------------------------|------------|
| dimethyl ether                  | 115-10-6 | TWA                           | 1.000 ppm<br>1.920 mg/m <sup>3</sup> | 2000/39/EC |
| Further information: Indicative |          |                               |                                      |            |
|                                 |          | TWA                           | 400 ppm<br>766 mg/m <sup>3</sup>     | GB EH40    |
|                                 |          | STEL                          | 500 ppm<br>958 mg/m <sup>3</sup>     | GB EH40    |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Appropriate engineering controls

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Safety glasses with side-shields conforming to EN166  
Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers).
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor (Type A) and particulate filter  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
P1: Inert material; P2, P3: hazardous substances  
Ensure adequate ventilation, especially in confined areas.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

### Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : aerosol  
Colour : various  
Odour : No data available
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flammability : Extremely flammable aerosol.

### Upper/lower flammability or explosive limits

- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Flash point : Not applicable
- Auto-ignition temperature : No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

Decomposition temperature : No data available  
pH : Not applicable  
substance/mixture reacts with water

### Viscosity

Viscosity, kinematic : Not applicable

### Solubility(ies)

Water solubility : No data available  
Partition coefficient: n-octanol/water : No data available  
Vapour pressure : 5100 hPa  
Density : ca. 1,00 g/cm<sup>3</sup> (23 °C)  
Relative vapour density : No data available  
Particle characteristics : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

:  
No hazardous decomposition products are known.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified due to lack of data.

##### Components:

##### Reaction products of phosphoryl trichloride and 2-methyloxirane:

Acute oral toxicity : LD50 Oral (Rat): > 630 mg/kg

##### Diphenylmethanediisocyanate, isomeres and oligomerics:

Acute inhalation toxicity : LC50: 1,5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l  
Test atmosphere: dust/mist  
Method: Calculation method

##### Skin corrosion/irritation

Causes skin irritation.

##### Components:

##### alkanes, C14-17, chloro:

Assessment : Repeated exposure may cause skin dryness or cracking.

##### Serious eye damage/eye irritation

Causes serious eye irritation.

##### Respiratory or skin sensitisation

##### Skin sensitisation

May cause an allergic skin reaction.

##### Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

##### Germ cell mutagenicity

Not classified due to lack of data.

##### Carcinogenicity

Suspected of causing cancer.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

### Reproductive toxicity

May cause harm to breast-fed children.

### STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

### Aspiration hazard

Not classified due to lack of data.

## 11.2 Information on other hazards

### Endocrine disrupting properties

Not classified due to lack of data.

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

### Product:

### Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

### Components:

### Reaction products of phosphoryl trichloride and 2-methyloxirane:

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 82 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 13 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 202

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

---

### alkanes, C14-17, chloro:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 10

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB)..

#### Components:

### alkanes, C14-17, chloro:

Assessment : Persistent, Bioaccumulative and Toxic (PBT)..  
: Very persistent and very bioaccumulative (vPvB).

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
May cause long lasting harmful effects to aquatic life.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

### Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

#### Components:

##### propane:

20-year global warming potential: 0,072  
100-year global warming potential: 0,02  
500-year global warming potential: 0,006  
Atmospheric lifetime: 0,036 yr  
Radiative efficiency: 0 Wm<sup>2</sup>ppb  
Further information: Miscellaneous compounds

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- |                          |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|--------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product                  | : | The generation of waste should be avoided or minimized wherever possible.<br>Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.<br>Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.<br>Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.<br>Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |
| European Waste Catalogue | : | 16 05 04* gases in pressure containers (including halons) containing dangerous substances                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Contaminated packaging   | : | 15 01 10* packaging containing residues of or contaminated by dangerous substances                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

- |      |   |         |
|------|---|---------|
| ADR  | : | UN 1950 |
| IMDG | : | UN 1950 |
| IATA | : | UN 1950 |

### 14.2 UN proper shipping name

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

**ADR** : AEROSOLS  
**IMDG** : AEROSOLS  
**IATA** : Aerosols, flammable

### 14.3 Transport hazard class(es)

|             | Class | Subsidiary risks |
|-------------|-------|------------------|
| <b>ADR</b>  | : 2   | 2.1              |
| <b>IMDG</b> | : 2.1 |                  |
| <b>IATA</b> | : 2.1 |                  |

### 14.4 Packing group

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)  
Remarks : Transport according to chapter 3.4 (LQ) possible

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Remarks : Transport according to chapter 3.4 (LQ) possible

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### 14.5 Environmental hazards

**ADR**  
Environmentally hazardous : no

**IMDG**  
Marine pollutant : no

**IATA (Passenger)**  
Environmentally hazardous : no

**IATA (Cargo)**  
Environmentally hazardous : no

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) P3a FLAMMABLE AEROSOLS

Volatile organic compounds : Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC)  
Volatile organic compounds (VOC) content: 20,8% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 20,8% w/w

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### Other regulations:

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H220 : Extremely flammable gas.  
H302 : Harmful if swallowed.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 : May cause respiratory irritation.  
H351 : Suspected of causing cancer.  
H362 : May cause harm to breast-fed children.  
H373 : May cause damage to organs through prolonged or repeated exposure if inhaled.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Carc. : Carcinogenicity  
Eye Irrit. : Eye irritation  
Flam. Gas : Flammable gases  
Lact. : Effects on or via lactation  
Resp. Sens. : Respiratory sensitisation  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026  
Revision Date: 04.08.2026

Version 6.2

Print Date 04.08.2026

|                  |                                                                                                                                                                                                                                        |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                  | list of indicative occupational exposure limit values                                                                                                                                                                                  |
| GB EH40          | : UK. EH40 WEL - Workplace Exposure Limits                                                                                                                                                                                             |
| 2000/39/EC / TWA | : Limit Value - eight hours                                                                                                                                                                                                            |
| GB EH40 / TWA    | : Long-term exposure limit (8-hour TWA reference period)                                                                                                                                                                               |
| GB EH40 / STEL   | : Short-term exposure limit (15-minute reference period)                                                                                                                                                                               |
| ADR              | : European Agreement concerning the International Carriage of Dangerous Goods by Road                                                                                                                                                  |
| CAS              | : Chemical Abstracts Service                                                                                                                                                                                                           |
| DNEL             | : Derived no-effect level                                                                                                                                                                                                              |
| EC50             | : Half maximal effective concentration                                                                                                                                                                                                 |
| GHS              | : Globally Harmonized System                                                                                                                                                                                                           |
| IATA             | : International Air Transport Association                                                                                                                                                                                              |
| IMDG             | : International Maritime Code for Dangerous Goods                                                                                                                                                                                      |
| LD50             | : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)                                                                                               |
| LC50             | : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)                                                                                                 |
| MARPOL           | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978                                                                                                                        |
| OEL              | : Occupational Exposure Limit                                                                                                                                                                                                          |
| PBT              | : Persistent, bioaccumulative and toxic                                                                                                                                                                                                |
| PNEC             | : Predicted no effect concentration                                                                                                                                                                                                    |
| REACH            | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC             | : Substances of Very High Concern                                                                                                                                                                                                      |
| vPvB             | : Very persistent and very bioaccumulative                                                                                                                                                                                             |

### Further information

#### Classification of the mixture:

|                   |            |
|-------------------|------------|
| Aerosol 1         | H222, H229 |
| Skin Irrit. 2     | H315       |
| Eye Irrit. 2      | H319       |
| Resp. Sens. 1     | H334       |
| Skin Sens. 1      | H317       |
| Carc. 2           | H351       |
| Lact.             | H362       |
| STOT SE 3         | H335       |
| STOT RE 2         | H373       |
| Aquatic Chronic 4 | H413       |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Based on product data or assessment |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sika Boom® Fire Guard B2

Date of last issue: 11.06.2026

Version 6.2

Print Date 04.08.2026

Revision Date: 04.08.2026

---

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GB / EN