

---

# SikaProof® A-08

---

## DECLARATION OF PERFORMANCE

### No. 49965829

---

<b>1</b>	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	49965829
<b>2</b>	<b>INTENDED USE/S</b>	EN 13967:2012 Plastic and rubber sheets intended for use as damp proofing in buildings
<b>3</b>	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich
<b>4</b>	<b>AUTHORISED REPRESENTATIVE:</b>	
<b>5</b>	<b>SYSTEM/S OF AVCP:</b>	System 2+ System 3
<b>6a</b>	<b>HARMONISED STANDARD:</b>	EN 13967:2012
	Notified body/ies:	1508, 1213

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	
Watertightness	Pass	System 2+	
Tear resistance:			
Machine direction	≥ 400 N		
Cross direction	≥ 450 N		
Joint strength	≥ 200N/50 mm	System 2+	
Impact resistance	≥ 250 mm	System 2+	
Tensile strength:			
Machine direction	≥ 450 N/50mm	System 2+	EN
Cross direction	≥ 450 N/50mm		13967:2012
Resistance to static loading	≥ 20 kg	System 2+	
Durability:			
Watertightness after artificial ageing	Pass	System 2+	
Watertightness after exposure to chemicals	Pass		
Dangerous substances	NPD	System 2+	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski  
 Function: Corporate Standardization and Approvals  
 At Warsaw on 24 July 2018

Name : Tatiana Ageyeva  
 Function: Standardization and Approvals  
 At Warsaw on 24 July 2018




End of information as required by Regulation (EU) No 305/2011





11

Sika Services AG, Zurich, Switzerland

DoP No. 49965829

EN 13967:2012

Notified Body 1508, 1213

Plastic and rubber sheets intended for use as damp proofing in buildings

Reaction to fire	Class E
Watertightness	Pass
Tear resistance:	
Machine direction	≥ 400 N
Cross direction	≥ 450 N
Joint strength	≥ 200N/50 mm
Impact resistance	≥ 250 mm
Tensile strength:	
Machine direction	≥ 450 N/50mm
Cross direction	≥ 450 N/50mm
Resistance to static loading	≥ 20 kg
Durability:	
Watertightness after artificial ageing	Pass
Watertightness after exposure to chemicals	Pass

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

SikaProof® A-08  
49965829  
2018.07 , ver. 2  
1005, 1193

Template for translation. Only for  
internal use

**Sika Services AG**  
Tüffenwies 16-22  
8064 Zürich  
Switzerland  
[www.sika.com](http://www.sika.com)

**Declaration of Performance**  
SikaProof® A-08  
49965829  
2018.07 , ver. 2  
1005, 1193

**4/4**

Template for translation. Only for  
internal use

**BUILDING TRUST**

