

PRODUCT DATA SHEET

Sika® Multi-Purpose Wood Filler

Ready mixed wood filler for permanent wood repairs

PRODUCT DESCRIPTION

Sika® Multi-Purpose Wood Filler is an easy to use, ready mixed premium wood filler, ideal for filling small imperfections in wood. Once dry, the filler leaves a sandable surface which can be painted, stained or varnished, including with micro-porous stains. Sika® Multi-Purpose Wood Filler is waterproof when dry, which means it is suitable for both interior and exterior applications.

USES

- Filling small holes, splits, surface imperfections and damaged areas in wood.
- Covering nail and screw holes.

PRODUCT INFORMATION

Chemical Base	Styrene/acrylate polymer with selected fillers and additives
Packaging	250 ml tubs
Shelf Life	24 months stored in original containers
Storage Conditions	Store in cool, dry conditions between +5 °C and +25 °C. Keep out of direct sunlight and protect from frost.
Density	1.73 - 1.83 g/cm ³
Thermal resistance	-5 °C to +70 °C once fully cured

APPLICATION INFORMATION

Layer Thickness	Maximum 5 mm
Ambient Air Temperature	+5 °C to +40 °C, optimum application temperature +20 °C

VALUE BASE

vary due to circumstances beyond our control.

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may

LIMITATIONS

- If you intend to overstain the wood once filled, ALWAYS CHOOSE THE COLOUR OF FILLER THAT NEAREST MATCHES THE WOOD YOU ARE FILLING, NOT THE STAIN YOU INTEND TO USE.
- As the filler may absorb some stains at different rates to the surrounding timber, always test a small area first. Note: filler may dry darker.
- Do not exceed 5 mm in one coat. For holes deeper than 5 mm, or for areas subject to impact such as door and window frames, use Sika® Two-Part Wood Filler which can be applied to any depth and is shatterproof.
- Protect from rain, when used externally, for at least five hours.
- Do not apply below + 5 °C.
- As the manufacturer cannot know all the uses their products may be put to, it is the user's responsibility to determine the suitability for use. If in doubt, contact Technical Services for advice.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Before applying, ensure surfaces are clean, dry, sound and free from dust or any contaminants which may affect adhesion.

APPLICATION

Stir well before use and apply with a spreader or knife. Fill the hole proud to allow for sanding. Once dry, sand to a smooth finish and apply required stain, paint or varnish.

CLEANING OF TOOLS

Any excess can be removed with a damp sponge. Clean all tools immediately after use with water.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

Sika® Multi-Purpose Wood Filler
October 2026, Version 01.01
021840303000265634

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SikaMulti-PurposeWoodFiller-en-GB-(10-2026)-1-1.pdf