

PRODUCT DATA SHEET

EVERBUILD® Quick Mac Cold Joint Sealer

Bitumen cold joint sealer and tack coat

PRODUCT DESCRIPTION

EVERBUILD® Quick Mac Cold Joint Sealer is a high specification tarmacadam repair compound designed to seal and waterproof vertical joints, that can also be used as a tack coat before applying tarmac. EVERBUILD® Quick Mac Cold Joint Sealer will also improve the bond strength to existing macadam, ironwork and concrete, thus prolonging repair life.

USES

- To seal and waterproof reinstatement vertical edges.
- As a tack coat before the application of macadam.
- Repairing tarmac roads, driveways etc.
- Repairing tarmac footpaths.
- Remedial work around ironworks i.e. drains, man-hole covers etc.

PRODUCT INFORMATION

Packaging	750ml aerosol
Appearance / Colour	Black
Shelf Life	12 months from the date of manufacture in the original unopened packaging
Storage Conditions	Store in cool dry conditions between + 5°C and 25°C. Storage outside these parameters will significantly reduce shelf life.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Correct preparation is the key to maximum durability. Suitable for application where minimum depth is 20mm to 60mm maximum. Compact base with suitable aggregate to required depth below wearing course, and sweep clean of dirt or loose debris. Apply EVERBUILD® Quick Mac Cold Joint Sealer to any clean-

CHARACTERISTICS / ADVANTAGES

- Clean and efficient
- Ready-to-use cold-lay product – just fill and compact down
- Prevents water ingress instantly
- Instantly trafficable
- Will not displace – stays where it is put

cut vertical surfaces.

APPLICATION

High traffic public areas: (carriageways, footpaths, cycle tracks, tennis courts etc)
For maximum durability a 60mm wearing course is recommended. Apply EVERBUILD® Quick Mac Cold Joint Sealer into recess and rake to a depth of 45mm (ie 50% greater than compacted depth). Compact to 30mm in accordance with Appendix 8 of the Re-In-

statement of Openings in Highways 1992. Re-seal vertical surfaces with EVERBUILD® Quick Mac Cold Joint Sealer, re-apply and rake to 45mm, and compact as above back to 30mm level with the existing surface.

Low traffic domestic areas: (eg driveways, garden paths)

Prepare, compact base, and prime vertical surfaces in the same way as above, but lesser depths of EVERBUILD® Quick Mac Cold Joint Sealer may be used if required. Holes are filled to 50% greater than their depth and compacted level. NOTE: do not use as a final wearing course at less than 20mm in compacted depth.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

Contains bitumen. Wear suitable industrial gloves and coveralls and avoid direct contact with this product. Ensure good ventilation during use. Wash hands after use. Remove product from skin with EVERBUILD HAND CLEANER or similar. If product enters eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice immediately showing this container. Data sheet available for professional user on request.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited