
according to Regulation (EC) No. 1907/2006

Sika Boom®-GS



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika Boom®-GS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane foam

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1

Carcinogenicity, Category 2

Specific target organ toxicity - single ex
H317: May cause an allergic skin reaction.

H351: Suspected of causing cancer.

H335: May cause respiratory irritation.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

Specific target organ toxicity - repeated

opecine target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS

Signal word

Print Date 01 Revision Date 01.11.2016 Version 2.0

Hazard pictograms







Danger

Hazard statements H222 Extremely flammable aerosol.

> Pressurised container: May burst if heated. H229

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through pro-

longed or repeated exposure.

Precautionary statements P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smokina.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ va-P260

pours/ spray.

Use only outdoors or in a well-ventilated P271

area.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

In case of inadequate ventilation wear res-P284

piratory protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

> air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel un-

well.

P308 + P313 IF exposed or concerned: Get medical ad-

vice/ attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with wa-

ter for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an ap-

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS

Revision Date 01.11.2016 Version 2.0



proved waste disposal plant.

Hazardous components which must be listed on the label:

• 9016-87-9 Diphenylmethanediisocyanate, isomeres and homologues

Additional Labelling:

EUH204 Contains isocyanates. May produce an allergic reaction.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components


Chemical name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Diphenylmethanediisocyanate, isomeres and homologues 9016-87-9	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Irrit.2; H319 Resp. Sens.1; H334 Skin Sens.1; H317 Carc.2; H351 STOT SE3; H335 STOT RE2; H373	>= 10 - < 20
tris(2-chloro-1-methylethyl) phosphate 911-815-4 01-2119486772-26-XXXX	Acute Tox.4; H302	>= 5 - < 10
propane 74-98-6 200-827-9	Flam. Gas1; H220	>= 5 - < 10
isobutane 75-28-5 200-857-2	Flam. Gas1; H220	>= 5 - < 10

Revision Date 01.11.2016

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS





For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS





May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. Treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

: Water

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

6.4 Reference to other sections

For personal protection see section 8.

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS

Revision Date 01.11.2016 Version 2.0 F



SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

: Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Follow standard hygiene measures when handling chemical products

Advice on protection against

fire and explosion

: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic

discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parame-	Basis *
			ters *	
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3	GB EH40
		STEL	0,07 mg/m3	GB EH40

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS



Revision Date 01.11.2016 Version 2.0 Print Date 01.11.2016

dimethyl ether	115-10-6	TWA	400 ppm 766 mg/m3	GB EH40
		STEL	500 ppm 958 mg/m3	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Diphenylmethanediisocy-	9016-87-9	urinary diamine:	Post task	GB EH40
anate, isomeres and		1µmol/mol creati-		BAT
homologues		nine		
		(Urine)		

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS



General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : various

Odour : characteristic

Odour Threshold : No data available

Flash point : Not applicable

Autoignition temperature : > 230 °C

Decomposition temperature : No data available

Lower explosion limit : 1 %(V)

Upper explosion limit : 18,6 %(V)

Flammability : No data available

Explosive properties : No data available

Oxidizing properties : No data available

pH : Not applicable

Melting point/range / Freez-

ing point

Boiling point/boiling range : No data available

Vapour pressure : 5.500 - 6.000 hPa

at 20 °C

No data available

Density : ca.1 g/cm3

at 20°C

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Relative vapour density : No data available

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS

Revision Date 01.11.2016 Version 2.0 Print Date 01.11.2016

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Country GB 100000010087

9 / 14

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS





Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

mation

Additional ecological infor- : There is no data available for this product.

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS

Revision Date 01.11.2016 Version 2.0 Print



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1950

14.2 Description of the goods : AEROSOLS

14.3 Class: 2Classification Code: 5FLabels: 2.1Tunnel restriction code: (D)14.5 Environmentally hazard-: no

ous

IATA

14.1 UN number : 1950

14.2 Description of the goods : Aerosols, flammable

14.3 Class: 2.1Labels: 2.114.5 Environmentally hazard-: no

ous

IMDG

14.1 UN number : 1950 **14.2 Description of the goods** : AEROSOLS

 14.3 Class
 : 2.1

 Labels
 : 2.1

 EmS Number 1
 : F-D

 EmS Number 2
 : S-U

 14.5 Marine pollutant
 : no

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS

Revision Date 01.11.2016 Version 2.0



14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

of Very High

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(Diphenylmethanediisocyanate,

isomeres and homologues)

: Banned and/or restricted

(=> 0.1 %).

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

REACH Information:

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

All substances contained in our Products are

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma-


jor-accident hazards involving dangerous substances.

Quantity 1 Quantity 2 Р3а FLAMMABLE AEROSOLS 500 t 150 t 34 Petroleum products: (a) 2.500 t 25.000 t gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

VOC-CH (VOCV) : 17,8 %

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS



VOC-EU (solvent) : 17,8 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002

Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations

1999

Health and Safety at Work Act 1974

Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H220	Extremely flammable gas.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure

Full text of other abbreviations

Acute Tox. Acute toxicity
Carc. Carcinogenicity
Eye Irrit. Eye irritation
Flam. Gas Flammable gases
Press. Gas Gases under pressure
Resp. Sens. Respiratory sensitisation

if inhaled.

Skin Irrit. Skin irritation
Skin Sens. Skin sensitisation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service DNEL Derived no-effect level

according to Regulation (EC) No. 1907/2006

Sika Boom®-GS



Revision Date 01.11.2016	Version 2.0	Print Date 01.11.2016

EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at once, which
	causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that
	kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships,
	1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the
	Council of 18 December 2006 concerning the Registration, Evaluation,
	Authorisation and Restriction of Chemicals (REACH), establishing a
	European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!