

SIKA
MARINE



THE
PROFESSIONAL'S
CHOICE



Sikaflex[®]-298

THE RELIABLE BEDDING COMPOUND

- Self levelling
- Simple application
- Wide adhesion range
- Multi-purpose
- IMO certified

BUILDING TRUST



Sikaflex[®]-298

Sikaflex[®]-298 is a 1-component polyurethane based adhesive and sealant which cures on exposure to atmospheric humidity to form a durable elastomer. Sikaflex[®]-298 is suitable for bonding deck covering materials and bedding-in and sealing of teak plank decking laid on top of the subdeck surface.

For specific applications consult the product data sheet or contact your Sika Technical Service.

PRODUCT BENEFITS

- Elastic behaviour
- Slightly thixotropic
- Contains no highly inflammable solvents
- Sound deadening
- Long open time

AREAS OF APPLICATION

- Synthetic resin deck coverings (1)
- Suitable for a wide range of substrates including GRP, marine plywood, steel, aluminium (2) and stainless steel



Typical Product Data

Chemical base	1-C Polyurethane
Cure mechanism	Humidity curing
Application temperature	10 - 35°C
Skin time (CQP019-1)	100 minutes approx ^A
Tensile strength (CQP036-1)	1.2 N/mm ² approx
Elongation at break (CQP036-1)	600% approx
Shelf life (storage below 25°C) (CQP016-1)	9 months for pail

CQP = Corporate Quality Procedure ^A23°C/50% r.h

Our most current General Sales Conditions shall apply.

Please consult the most current local Product Data Sheet prior to any use..



SIKA LIMITED

Head Office
Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
United Kingdom

Contact

Phone +44 1 707 394444
E-Mail sealingandbondingenquiries@uk.sika.com
www.sika.co.uk/sealantsandadhesives
@SikaLimited

SIKA IRELAND LIMITED

Sika House
Ballymun Industrial Estate
Dublin 11
D11 DA2V
Ireland

Contact

Phone +353 1 862 0709
Fax +353 1 862 0707
E-Mail info@ie.sika.com
www.sika.ie
@SikaIreland

BUILDING TRUST

