

# SikaMelt<sup>®</sup>-9902 (VP)

## Cleaner for PUR Hotmelt

### Technical Product Data:

Chemical base	Plasticizer
Colour	White
Solids content	100%
Cleaning mechanism	Dissolving of PUR reactive hot melt
Density at 20°C (DIN 51757) <sup>1)</sup>	1,15 kg / l approx.
Viscosity	Low viscous
Melting temperature	49°C
Application temperature range	60 - 140°C (maximally 150°C)
Shelf life (under dry conditions at 5 - 25°C in sealed container)	24 months after production. An excess of the recommended storage temperature during transport is not critical, but not higher than 45°C

<sup>1)</sup> Based on

### Description

SikaMelt<sup>®</sup>-9902 (VP) is a cleaner for polyurethane reactive hot melt application equipment.

SikaMelt<sup>®</sup>-9902 (VP) is manufactured in accordance with the ISO 9001/14001 quality assurance system.

### Product benefits

- Dissolving and swelling of cured polyurethane hotmelt
- Solvent free
- Particularly suitable for cleaning of roller coater

### Areas of application

SikaMelt<sup>®</sup>-9902 (VP) is able to swell already cured polyurethane hot melt. The swelled material can then be easily removed from the application equipment. Please note, that a complete dissolving of the cured polyurethane hot melt with SikaMelt<sup>®</sup>-9902 (VP) is not possible.

Industry



Sika Automotive GmbH  
Reichsbahnstr. 99  
22525 Hamburg  
Germany  
Tel: +49 40 54002 0  
Fax: +49 40 54002 241

## Method of application

See Manual "Cleaning of application tools for SikaMelt® reactive polyurethane hot melts".

## Further information

Copies of the following publications are available on request:

- Material Safety Data Sheet
- Manual "Cleaning of application tools for SikaMelt® reactive polyurethane hot melts".

## Packaging information

Fiber drum	15 kg
------------	-------

## Value Bases

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## Health and Safety Information

For information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Material Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

## Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

