

PRODUCT DATA SHEET

Cromar® Standard Raised Edge Trim 127 mm Drop

Standard raised edge trim

PRODUCT DESCRIPTION

Standard raised edge trim, fitted to the roof edge to prevent water run-off.

The Cromar® Standard Raised Edge Trim 127 mm Drop is designed to be used on the non-drainage side of a flat roof to direct the flow of water off the substrate. Made for using on flat roofs as a component of Glassfibre Roofing Systems.

USES

- To prevent water run off on flat roofs.
- Compatible with C1 external and C4 internal universal corners.

PRODUCT INFORMATION

Packaging	Boxed
Colour	Grey
Shelf Life	Physical plastic items have not had their shelf life determined due to longevity.
Storage Conditions	The product must be stored undamaged in packaging, in dry conditions at temperatures between +5 °C and +30 °C.
Length	3 m
Width	127 mm
Thickness	1 mm

VALUE BASE

CHARACTERISTICS / ADVANTAGES

- Consistent weight and thickness.
- Excellent finish and appearance.
- High strength and flexibility.
- Excellent long-term durability.
- Easy jointing.
- Facilitates roof void ventilation.
- Unique high adhesion finish.
- U.V. stabilisation.
- Suitable for use with Cromar PROGRP and Flexi-glass Systems.

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may

vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION METHOD / TOOLS

A single batten is fixed level with the top edge of the deck. Apply 30 mm beads of trim adhesive to the batten every 300 mm, rub the trim into place and nail through the top of the trim into the decking. Do not nail through the front of the trim.

If a ladder is likely to be leant against a B type trim for regular access to the roof, the trim will need to be reinforced to avoid deformation. The trim can either be doubled up by slotting a section of extra trim within the section where the ladder will be used or it can be reinforced with an extra layer of GRP laminate and then tissue to maintain a smooth finish. Alternatively, a wooden batten can be shaped and fitted into the ridge of the trim to ensure that it remains rigid.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

Cromar® Standard Raised Edge Trim 127 mm
Drop
February 2026, Version 01.01
020915955000247269