



EN 12004:2007

13

1289

DECLARATION OF PERFORMANCE

Sika[®] Ceram Flexible Rapid Set Tile Adhesive (White)

02	03	06	02	001	0	000118	1220
----	----	----	----	-----	---	--------	------

1. Product Type: Unique identification code of the product-type:	Sika[®] Ceram
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	Flexible Rapid Set Tile Adhesive (White) -(Batch No. - see packaging)
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Improved deformable fast setting cementitious adhesive with reduced slip, conforming to BS EN 12004:2007 +A1:2012 C2FT-S1
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sika[®] Ceram Flexible Rapid Set Tile Adhesive (White) Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant (see 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 3
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	Notified testing laboratory NB 1289, performed under AVCP System 3 type testing regarding Sika Ceram Flexible Rapid Set Tile Adhesive (White) and issued: Testing report Nr: (131338)-5703

Declaration of Performance



<p>8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:</p>	<p>Not relevant (see 7)</p>
---	------------------------------------

9. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
Reaction to Fire	Class F	EN 12004:2007 +A1:2012
Initial tensile adhesion strength	≥ 1.0 mm ²	
Tensile adhesion strength after water immersion	≥ 1.0 mm ²	
Tensile adhesion strength after heat aging	≥ 1.0 mm ²	
Tensile adhesion strength after freeze thaw cycles	≥ 1.0 mm ²	
Open time: tensile adhesion strength	≥ 0.5 mm ² after not less than 20 min	
Early tensile adhesion strength	≥ 0.5 mm ²	
Open time: tensile adhesion strength	≥ 0.5 mm ² after not less than 10 min	
Slip	≥ 0.5 mm	
Deformable adhesive: Transverse deformation	≥ 2.5 mm and < 5.0 mm	



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

SIGNED
R&D Manager

SIGNED
Technical Manager

05, 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire
AL7 1BQ
United Kingdom
Phone +44 1707 394444
Telefax +44 1707 329129
www.sika.co.uk
email: sales@uk.sika.com



Certificate No. EMS 4308



Certificate No. FM 12504