

# Sikafloor®-122 Level Universal

## DECLARATION OF PERFORMANCE No. 19090311

|    |  |   |
|----|--|---|
| 1  | <b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b> | 19090311  |
| 2  | <b>INTENDED USE/S</b>                                  | Floor screed materials - cementitious screeds       |
| 3  | <b>MANUFACTURER:</b>                                   | Sika Services AG<br>Tüffenwies 16-22<br>8064 Zürich |
| 4  | <b>AUTHORISED REPRESENTATIVE:</b>                      |   |
| 5  | <b>SYSTEM/S OF AVCP:</b>                               | 4   |
| 6a | <b>HARMONISED STANDARD:</b>                            | EN 13813:2002                                       |
|    | Notified body/ies:                                     | N/A   |

**7 DECLARED PERFORMANCE/S**

| Essential Characteristics       | Performance      | AVCP | Harmonised Technical Specification |
|---------------------------------|------------------|------|------------------------------------|
| Reaction to fire                | A1 <sub>fl</sub> |      | EN 13813: 2002                     |
| Release of corrosive substances | CT               |      |                                    |
| Water permeability              | NPD              |      |                                    |
| Water Vapour permeability       | NPD              |      |                                    |
| Compressive Strength            | C20              |      |                                    |
| Flexural Strength               | F5               |      |                                    |
| Abrasion / Wear Resistance      | NPD              |      |                                    |
| Sound insulation                | NPD              |      |                                    |
| Sound absorption                | NPD              |      |                                    |
| Thermal resistance              | NPD              |      |                                    |
| Chemical resistance             | NPD              |      |                                    |

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas  
 Function: Technical Product Coordinator  
 At Leeds on 12 September 2024

Name : Sarah Buchanan  
 Function: Product Manager  
 At Leeds on 12 September 2024

*S Buchanan*

End of information as required by Regulation (EU) No 305/2011





24

Sika Services AG, Zurich, Switzerland

DoP No. 19090311

EN 13813:2002

Notified Body N/A

Cementitious screed material for use internally

|                                 |      |
|---------------------------------|------|
| Reaction to fire                | A1fl |
| Release of corrosive substances | CT   |
| Water permeability              | NPD  |
| Water Vapour permeability       | NPD  |
| Compressive Strength            | C20  |
| Flexural Strength               | F5   |
| Abrasion / Wear Resistance      | NPD  |
| Sound insulation                | NPD  |
| Sound absorption                | NPD  |
| Thermal resistance              | NPD  |
| Chemical resistance             | NPD  |

[sika.co.uk](http://sika.co.uk)

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

Sikafloor®-122 Level Universal

19090311

2024/09 , ver. 01

1088

3/4

**BUILDING TRUST**



**Declaration of Performance**  
Sikafloor®-122 Level Universal  
19090311  
2024/09 , ver. 01  
1088

