

PRODUCT DATA SHEET

Sika® Fibermesh®-150

MICRO-SYNTHETIC MONOFILAMENT FIBRE

PRODUCT DESCRIPTION

Sika® Fibermesh®-150, micro-reinforcement system for concrete is manufactured with 100 percent virgin polypropylene monofilament fibers. Specifically engineered and manufactured in an ISO 9001 certified manufacturing facility. Sika® Fibermesh®-150 is designed to control plastic shrinkage and settlement cracking in concrete. Sika® Fibermesh®-150 was previously SikaFiber PPM.

USES

Sika® Fibermesh®-150 act mechanically by supporting the aggregate within the concrete with multidimensional fibre network and developing a uniform bleed system. The fibre does not affect the curing process and does not absorb water. Sika® Fibermesh®-150 can be used in all types of concrete applications to control plastic shrinkage and settlement cracking. Typical applications include:

- Ground-supported slabs
- Residential applications: pavements, driveways, curbs
- Precast elements,
- Overlays / toppings
- Shotcrete
- Roads / Pavements
- Bridge Decks
- Structural metal decking (Sika® Fibermesh®-150ML, formerly Sika® Fibermesh®-150e3)

PRODUCT INFORMATION

Packaging	Sika® Fibermesh®-150 fibers are available in a variety of packaging options. The bags are packed into cartons and palletized.
Shelf Life	When stored in dry conditions shelf life is 5 years
Storage Conditions	Sika® Fibermesh®-150 should be stored in a dry environment. Protect product from the rain.
Appearance / Colour	▪ Fiber Type: Monofilament micro synthetic fiber

CHARACTERISTICS / ADVANTAGES

- Reduces plastic shrinkage cracking
- Reduces plastic settlement cracking
- Improves impact, shatter and abrasion resistance
- Enhances durability
- Promotes uniform bleed and reduces bleed water
- Increases cohesion and reduces segregation
- Reduces freeze/thaw damage

APPROVALS / STANDARDS

- Conforms to the requirements of EN 14889-2:2006 Fibres for Concrete - Polymer Fibres, Class 1a.
- **Sika® Fibermesh®-150 ML**, (formerly **e3**): DoP 61855570, certified by Factory Production Control Body 1301 and provided with the CE mark
- **Sika® Fibermesh®-150 12mm**: DoP 62804076, certified by Factory Production Control Body 1301 and provided with the CE mark
- **Sika® Fibermesh®-150 6mm**: DoP 62804076, certified by Factory Production Control Body 1301 and provided with the CE mark

Dimensions	<ul style="list-style-type: none"> ▪ Single length: 6 & 12mm ▪ Multi length: 12 - 19mm graded (Sika® Fibermesh®-150ML, formerly e3) ▪ Diameter: 0.03 & 0.05 mm. Also available in single equivalent diameter
Density	0.91 kg/lt
Melting Point	162 °C (324 °F)

TECHNICAL INFORMATION

Resistance to Alkalinity	Excellent
---------------------------------	-----------

APPLICATION INFORMATION

Recommended Dosage	The dosage of the Sika® Fibermesh®-150 will vary according to the type of application and performance requirements. Standard recommended dosage of Sika® Fibermesh®-150 is 0.6 - 0.9 kg/m ³ of concrete. Dosages outside the recommended dosage range can be used to meet project specific requirements. If this is the case please contact your Sika representative for technical support.
---------------------------	--

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Sika® Fibermesh®-150
November 2023, Version 01.04
021408021010000056

SikaFibermesh-150-en-GB-(11-2023)-1-4.pdf