

Date of last issue: 03.09.2021	Version 1.2	Print Date 11.05.2023
Revision Date: 27.09.2022		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ADEKIT A 300 NF/400 Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ
Telephone Telefax E-mail address of person	:	+44 (0)1707 394444 +44 (0)1707 329129 EHS@uk.sika.com
responsible for the SDS		

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12	
Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin corrosion, Sub-category 1A	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting ef- fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



Date of last issue: 03.09.2021 Revision Date: 27.09.2022		Version 1.2	Print Date 11.05.2023
Hazard pictograms			
Signal word	Danger		
Hazard statements :	H225 H314 H317 H335 H412	Highly flammable liqui Causes severe skin bu May cause an allergic May cause respiratory Harmful to aquatic life fects.	urns and eye damage. skin reaction. / irritation.
Precautionary statements :	Prevention:		
	P210	Keep away from heat, open flames and othe smoking.	
	P280	Wear protective glove eye protection/ face pl	
	Response:		
	P303 + P361	+ P353 IF ON SKIN (or ately all contaminated with water.	hair): Take off immedi- clothing. Rinse skin
	P304 + P340	+ P310 IF INHALED: Re air and keep comforta mediately call a POIS	ble for breathing. Im-
	P305 + P351	+ P338 + P310 IF IN E	YES: Rinse cautiously minutes. Remove con- and easy to do. Con-
	P370 + P378		y sand, dry chemical or n to extinguish.

Hazardous components which must be listed on the label:

methyl methacrylate methacrylic acid 2,2'-ethylenedioxydiethyl dimethacrylate 6,6'-di-tert-butyl-4,4'-thiodi-m-cresol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Date of last issue: 03.09.2021 Revision Date: 27.09.2022 Version 1.2

Print Date 11.05.2023

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
methyl methacrylate	80-62-6 201-297-1 01-2119452498-28- XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412	>= 40 - < 60
methacrylic acid	79-41-4 201-204-4 01-2119463884-26- XXXX	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Acute Tox. 3; H311 STOT SE 3; H335 Acute Tox. 4; H332 	>= 10 - < 20
p-toluenesulphonic acid, (contain- ing more than 5 % H2SO4)	104-15-4 203-180-0 01-2119538811-39- XXXX	Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 	>= 10 - < 20
2,2'-ethylenedioxydiethyl di- methacrylate	109-16-0 203-652-6 01-2119969287-21- XXXX	Skin Sens. 1B; H317	>= 10 - < 20



Date of last issue: 03.09.2021 Revision Date: 27.09.2022 Version 1.2

α, α-dimethylbenzyl hydroperox- ide	80-15-9 201-254-7	Org. Perox. E; H242 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 STOT RE 2; H373 Aquatic Chronic 2; H411 = specific concentration limit Skin Corr. 1B; H314 >= 10 % Skin Irrit. 2; H315 3 - < 10 % Eye Dam. 1; H318 3 - < 10 % Eye Irrit. 2; H319 1 - < 3 % STOT SE 3; H335 >= 1 %	>= 1 - < 2,5
2,6-di-tert-butyl-p-cresol	128-37-0 204-881-4 01-2119565113-46- XXXX	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2,5
6,6'-di-tert-butyl-4,4'-thiodi-m- cresol	96-69-5 202-525-2	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	 Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. 	
If inhaled	: Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficult 	ul-



Date of last issue: 03.09.2021 Revision Date: 27.09.2022	Version 1.2	Print Date 11.05.2023
	ty.	
In case of eye contact	 Small amounts splashed into eyes can cause sue damage and blindness. In the case of contact with eyes, rinse immer of water and seek medical advice. Continue rinsing eyes during transport to hose Remove contact lenses. Keep eye wide open while rinsing. 	diately with plenty
If swallowed	 Do not induce vomiting without medical advised Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconservational sectors. 	
4.2 Most important symptoms and	effects, both acute and delayed	
Symptoms	 Cough Respiratory disorder Allergic reactions Dermatitis See Section 11 for more detailed information and symptoms. 	ו on health effects
Risks	 Health injuries may be delayed. corrosive effects irritant effects sensitising effects 	
	May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Causes severe burns.	
4.2 Indication of any immediate m	adical attention and anopial treatment needs	

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Treat symptomatically.	
-----------	--------------------------	--

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water



Date of last issue: 03.09.2021 Revision Date: 27.09.2022		Version 1.2	Print Date 11.05.2023
5.2 Special hazards arising from	the	substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing	apparatus.
Further information	:	Use water spray to cool unopened containers.	
SECTION 6: Accidental releas	se r	neasures	

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
---------------------------	---	---

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
		miculite) and place in container for disposal according to local
		/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
--	--



_

Date of last issue: 03.09.2021 Revision Date: 27.09.2022	Version 1.2	Print Date 11.05.2023		
	Smoking, eating and drinking should be p plication area. Take precautionary measures against sta Open drum carefully as content may be u Take necessary action to avoid static elec (which might cause ignition of organic val Follow standard hygiene measures when products	atic discharge. Inder pressure. ctricity discharge pours).		
Advice on protection against : fire and explosion	Use explosion-proof equipment. Keep aw open flames/ hot surfaces. No smoking. ⁻ measures against electrostatic discharge	Take precautionary		
Hygiene measures :	Handle in accordance with good industria practice. When using do not eat or drink. smoke. Wash hands before breaks and a	When using do not		
7.2 Conditions for safe storage, including any incompatibilities				
Requirements for storage : areas and containers	Store in cool place. Containers which are carefully resealed and kept upright to pre in accordance with local regulations.			
Further information on stor- : age stability	No decomposition if stored and applied a	s directed.		

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU
	Further infor	mation: Indicative		
		STEL	100 ppm	2009/161/EU
		STEL	100 ppm 416 mg/m3	GB EH40
		TWA	50 ppm 208 mg/m3	GB EH40
methacrylic acid	79-41-4	TWA	20 ppm 72 mg/m3	GB EH40
		STEL	40 ppm 143 mg/m3	GB EH40
2,6-di-tert-butyl-p-cresol	128-37-0	TWA	10 mg/m3	GB EH40
		mation: Where no sp re three times the lon		



GB EH40

20 mg/m3

ADEKIT A 300 NF/400 Part A

Date of last issue: 03.09.2021 Revision Date: 27.09.2022	Vers	ion 1.2	Print	Print Date 11.05.2023		
6,6'-di-tert-butyl-4,4'-thiodi-m-cresol	96-69-5	TWA	10 mg/m3	GB EH40		

STEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment					
Eye protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.				
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.				
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.				
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.				
Respiratory protection	 In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. 				
Environmental exposure controls					
General advice	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.				

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties



Date of last issue: 03.09.2021 Revision Date: 27.09.2022	Version 1.2	Print Date 11.05.2023
Physical state Appearance Colour	: liquid : gel : white	
Odour	: strong	
Melting point/range / Freezing point	: No data available	
Boiling point/boiling range	: No data available	
Flammability (solid, gas)	: No data available	
Upper/lower flammability or o	explosive limits	
Upper explosion limit / Up- per flammability limit	: No data available	
Lower explosion limit / Lower flammability limit	: No data available	
Flash point	: ca. 10 °C Method: closed cup	
Auto-ignition temperature	: 68 °C	
Decomposition temperature	: No data available	
рН	: No data available	
Viscosity		
Viscosity, dynamic	: ca. 500.000 mPa.s (20 °C)	
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	: No data available	
Partition coefficient: n- octanol/water	: No data available	



Date of last issue: 03.09.2021 Revision Date: 27.09.2022	Version 1.2	Print Date 11.05.2023
Vapour pressure	: 40 hPa	
Density	: ca. 0,98 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
9.2 Other information No data available		

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous rea	ctio	ons
Hazardous reactions : Stable under recomme		Stable under recommended storage conditions.
		Vapours may form explosive mixture with air.
10.4 Conditions to avoid		
Conditions to avoid	:	Heat, flames and sparks.
0.5 Incompatible materials		
Materials to avoid	:	No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

methyl methacrylate:



Date of last issue: 03.09.2021 Revision Date: 27.09.2022	Version 1.2	Print Date 11.05.2023		
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg			
Acute inhalation toxicity	: LC50 (Rat): 29,8 mg/l Exposure time: 4 h Test atmosphere: vapour			
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 5.000 mg/kg			
2,6-di-tert-butyl-p-cresol: Acute oral toxicity	: LD50 Oral (Rat): 2.930 mg/kg			
Skin corrosion/irritation Causes severe burns.				
Serious eye damage/eye irr Causes serious eye damage.	ation			
Respiratory or skin sensitis	tion			
Skin sensitisation May cause an allergic skin re	ction.			
Respiratory sensitisation Not classified based on availa	le information.			
Germ cell mutagenicity Not classified based on availa	Germ cell mutagenicity Not classified based on available information.			
Carcinogenicity Not classified based on availa	ble information.			
Reproductive toxicity Not classified based on availa	ble information.			
STOT - single exposure May cause respiratory irritation				
STOT - repeated exposure Not classified based on availa	le information.			
Aspiration toxicity Not classified based on availa 11.2 Information on other hazard				



Date of last issue: 03.09.2021 Revision Date: 27.09.2022 Version 1.2

SECTION 12: Ecological information

12.1 Toxicity

Components:	
methyl methacrylate:	
Toxicity to fish :	LC50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
	NOEC (Danio rerio (zebra fish)): 9,4 mg/l
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): 69 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
	NOEC : 37 mg/l Exposure time: 21 d Method: OECD Test Guideline 202

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.



Date of last issue: 03.09.2021 Revision Date: 27.09.2022 Version 1.2

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Ρ	rod	luct
	iuu	iuuu

:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number				
ADR	:	UN 2924		
IMDG	:	UN 2924		
ΙΑΤΑ	:	UN 2924		
14.2 UN proper shipping name				
ADR	:	FLAMMABLE LIQUID, CORROSIVE, N.O.S.		
IMDG	:	FLAMMABLE LIQUID, CORROSIVE, N.O.S.		
ΙΑΤΑ	:	Flammable liquid, corrosive, n.o.s.		
14.3 Transport hazard class(es)				
ADR	:	3		
IMDG	:	3		
ΙΑΤΑ	:	3		
14.4 Packing group				
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code IMDG	:	II FC 338 3 (8) (D/E)		



Date of last issue: 03.09.2021 Revision Date: 27.09.2022	Version 1.2	Print Date 11.05.2023
Packing group Labels EmS Code	: II : 3 (8) : F-E, S-C	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	: 363 : Y340 : II : Flammable Liquids, Corrosive	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	: 352 : Y340 : II : Flammable Liquids, Corrosive	
14.5 Environmental hazards		
ADR Environmentally hazardous	: no	
IMDG Marine pollutant	: no	
IATA (Passenger) Environmentally hazardous	: no	

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable



Date of last issue: 03.09.2021 Revision Date: 27.09.2022	Version 1.2	Print Date 11.05.2023		
Volatile organic compounds :	Law on the incentive tax for volatile organic comp (VOCV) Volatile organic compounds (VOC) content: 0,5% no VOC duties Directive 2010/75/EU of 24 November 2010 on in emissions (integrated pollution prevention and co Volatile organic compounds (VOC) content: 0,5%	6 w/w ndustrial ontrol)		
If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.				
Health, safety and environ- : mental regulation/legislation	Environmental Protection Act 1990 & Subsidiary Health and Safety at Work Act 1974 & Subsidiary	0		

Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations
(COSHH)
May be subject to the Control of Major Accident Hazards
Regulations (COMAH), and amendments.

Other regulations:

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H242	:	Heating may cause a fire.
H302	:	Harmful if swallowed.
H311	:	Toxic in contact with skin.
H312	:	Harmful in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H331	:	Toxic if inhaled.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H373	:	May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.



Full text of other abbreviations

Date of last issue: 03.09.2021 Revision Date: 27.09.2022 Version 1.2

Print Date 11.05.2023

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic		Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
	:	
Eye Irrit.	•	Eye irritation
Flam. Liq.	:	Flammable liquids
Org. Perox.	:	Organic peroxides
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2009/161/EU	:	Europe. COMMISSION DIRECTIVE 2009/161/EU establishing
		a third list of indicative occupational exposure limit values in
		implementation of Council Directive 98/24/EC and amending
		Commission Directive 2000/39/EC
GB EH40	÷	UK. EH40 WEL - Workplace Exposure Limits
2009/161/EU / TWA	•	Limit Value - eight hours
2009/161/EU / STEL		Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50		Median lethal concentration (concentrations of the chemical in
2030	•	air that kills 50% of the test animals during the observation
		•
		period)
MARPOL	÷	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
<u>еу/ше</u>		Substances of Very High Concern

: Substances of Very High Concern

: Very persistent and very bioaccumulative

Further information Classification of the mixture:

Classification procedure:

SVHC

vPvB



Date of last issue: 03.09.2021 Revision Date: 27.09.2022		Version 1.2	Print Date 11.05.2023
Flam. Liq. 2	H225	Based on product data	a or assessment
Skin Corr. 1A	H314	Calculation method	
Eye Dam. 1	H318	Calculation method	
Skin Sens. 1	H317	Calculation method	
STOT SE 3	H335	Calculation method	
Aquatic Chronic 3	H412	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN