

PRODUCT DATA SHEET

Incozol®-341 LV

REACTIVE DILUENT

DESCRIPTION

Incozol®-341 LV is a low-viscosity, reactive diluent specifically designed to help formulators develop low VOC polyurethane coatings and sealants.

USES

It is typically used in two-component systems, where it replaces a portion of the polyol component and reduces the amount of solvent needed in the formulation resulting in a reduction of VOC content without compromising performance.

FEATURES

- Low Viscosity: Enables low-viscosity formulations without increasing VOC.
- VOC Reduction: Supports high solids, low VOC polyurethane coatings and sealants.
- Helps in achieving smooth, defect-free finishes by preferentially reacting with atmospheric moisture and thereby preventing CO₂ formation resulting from the reaction of water with the isocyanate hardener.
- Moisture Tolerance: The prevention of CO₂ gas is enhanced during application in humid conditions.

PRODUCT INFORMATION

Packaging	25kg
	200kg
	1000kg
Colour	max 250 Hazen
Shelf life	24 months
Storage conditions	Keep container tightly closed in a dry and well-ventilated place.
Density	1.014 g/cm ³
Viscosity	75 cP
Active content	82 g/eq

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

This product is sensitive to moisture. After use, purge the container with dry Nitrogen before resealing.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.