

PRODUCT DATA SHEET

CromaSlate Angled Ridge Tile Slate

Ridge tile intended for use on roof ridges

PRODUCT DESCRIPTION

CromaSlate Angled Ridge is manufactured from a composite material engineered for durability and safety.

USES

- CromaSlate Angled Ridge Tile Slate can be used on conservatories, annexes, sheds, garages, lean-to and extensions.

CHARACTERISTICS / ADVANTAGES

- Easy Fixing - screw fixed or nailed to the ridge.
- UV stabilised; fire retardant.
- Lightweight.
- Textured finish for the natural slate look.
- Easy to cut.

PRODUCT INFORMATION

Packaging	Boxed
Colour	Grey
Shelf Life	Physical plastic items have not had their shelf life determined due to longevity
Storage Conditions	The product must be stored undamaged in packaging, in dry conditions at temperatures between +5 °C and +30 °C.
Dimensions	Profile angle - 120 ° Overall length - 500 mm

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable condi-

tions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Position units along the ridge at the recommended 200 mm gauge. Fix each unit to the ridge using corrosion-resistant screws or nails as appropriate to the substrate and design. Seal, flash and ventilate (if applicable) in accordance with the project specification and local code requirements.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
CromaSlate Angled Ridge Tile Slate
March 2026, Version 01.01
020945201000247197

CromaSlateAngledRidgeTileSlate-en-GB-(03-2026)-1-1.pdf