

## PRODUCT DATA SHEET

# Cromar® 90 Degree Top Closure 70 mm

90° trough for roof valleys

### PRODUCT DESCRIPTION

Cromar® 90 Degree Top Closure 70 mm troughs are a cost effective alternative to lead gutters. The troughs can accommodate various roofing materials, including tiles and slate.

### USES

- Used with clay or concrete tiles or slate roofs.
- Used with profiled GRP or metal roofs.

### CHARACTERISTICS / ADVANTAGES

- Light weight and easy to install.
- Long-term durability.
- Virtually maintenance free.
- Suitable for all kinds of pitched roofs.

### PRODUCT INFORMATION

Packaging	Boxed
Colour	Grey
Shelf Life	Physical plastic items have not had their shelf life determined due to longevity
Storage Conditions	The product must be stored undamaged in packaging, in dry conditions at temperatures between +5 °C and +30 °C

### VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

### ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product

### APPLICATION METHOD / TOOLS

All roofing work should be conducted according to current British Standard code of conduct.

#### Product Data Sheet

Cromar® 90 Degree Top Closure 70 mm

February 2026, Version 01.01

020915955000247260

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**SIKA LIMITED**  
Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



**Product Data Sheet**  
Cromar® 90 Degree Top Closure 70 mm  
February 2026, Version 01.01  
020915955000247260

Cromar90DegreeTopClosure70mm-en-GB-(02-2026)-1-1.pdf

**BUILDING TRUST**

