Safety Data Sheet



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name : SikaRail KC340/45, Part A

Use of the substance/preparation: Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

United Kingdom

Telephone no. : 01707 394444

Fax no. : 01707 329129

e-mail address of person : EHS@uk.sika.com

responsible for this SDS

El lowak.sika.com

Emergency telephone number : +44 (0)1707 363899 (available during office hours).

2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : R43

N; R51/53

Human health hazards : May cause sensitisation by skin contact.

Environmental hazards : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Modified polyol Characteristics

Ingredient name	CAS number	%	EC number	Classification	
6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine	106264-79-3	3-7	403-240-8	Xn; R22 [R43 N; R50/53	[1]
See section 16 for the full text of the R-phrases declared above					

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] PBT-substance
- [4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

Date of issue : 10.09.2010. MSDS no. : 34683 1/6

4. FIRST AID MEASURES

First-aid measures

Inhalation : Get medical attention if adverse health effects persist or are severe.

Ingestion : Do not induce vomiting unless directed to do so by medical personnel. Maintain an

open airway. Seek immediate medical attention.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

> shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention if symptoms

occur.

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

In case of inhalation of decomposition products in a fire, symptoms may be delayed. Notes to physician

The exposed person may need to be kept under medical surveillance for 48 hours.

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable : Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

> nitrogen oxides sulfur oxides

metal oxide/oxides

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

ACCIDENTAL RELEASE MEASURES 6.

Personal precautions Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment (see section

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains **Environmental precautions**

and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to

the environment if released in large quantities.

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, Large spill

> water courses, basements or confined areas. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Small spill Stop leak if without risk. Move containers from spill area. Absorb with an inert

material and place in an appropriate waste disposal container.

7. HANDLING AND STORAGE

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

: 10.09.2010. Date of issue **MSDS no.** : 34683 2/6

7. HANDLING AND STORAGE

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Packaging materials

Recommended: Use original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

Ingredient name

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Exposure controls

Occupational exposure

controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Respiratory protection

Hand protection

: No special measures required.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates

this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance

Form : Liquid.
Colour : Various.
Odour : Characteristic.

Important health, safety and environmental information

Flash point : Closed cup: >101°C (>213.8°F)

Date of issue : 10.09.2010. MSDS no. : 34683 3/6

9. PHYSICAL AND CHEMICAL PROPERTIES

Density : ~0.87 g/cm³ [20°C (68°F)]

Solubility: Insoluble in the following materials: water

10. STABILITY AND REACTIVITY

Stability: The product is stable.

Conditions to avoid : Avoid release to the environment. Refer to special instructions/safety data sheet.

Materials to avoid : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation: May cause irritation.

Ingestion: Can cause gastrointestinal disturbances.Skin contact: May cause sensitisation by skin contact.

Eye contact : May cause eye irritation.

Chronic effects : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

12. ECOLOGICAL INFORMATION

Environmental effects : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

13. DISPOSAL CONSIDERATIONS

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil,

waterways, drains and sewers.

Packaging : Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a

licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

14. TRANSPORT INFORMATION

International transport regulations

<u>ADR</u>

UN number : UN3082

ADR Class : 9
Classification code : M6
Packing group : III

Date of issue : 10.09.2010. MSDS no. : 34683 4/6

14. TRANSPORT INFORMATION

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

Contains : 6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine

Label No. : 9

IMDG

UN number : UN3082

IMDG Class : 9
Packing group : III

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s. **Contains** : 6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine

Emergency schedules

(EmS)

: F-A, S-F

Marine pollutant : P Label no. : 9

<u>IATA</u>

UN number : UN3082

IATA Class : 9
Packing group : III

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s. **Contains** : 6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine

Label no. : 9

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols : Xi, N

Irritant, Dangerous for the environment

Contains : 6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine

Risk phrases : R43- May cause sensitisation by skin contact.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases : S24- Avoid contact with skin.

S37- Wear suitable gloves.

VOC content (EU) : VOC (w/w): 0.24%

National regulations

Regulatory information : Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (CHIP

4)

Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as

amended)

Health & Safety at Work Act 1974

The Environmental Protection (Duty of Care) Regulations 1991

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2007

Guidance Publications : Approved Code of Practice - Management of Health and Safety at Work, HSE

General Approved Code of Practice to COSHH Regulations, HSE.

Date of issue : 10.09.2010. MSDS no. : 34683 5/6

16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and

: R22- Harmful if swallowed.

R43- May cause sensitisation by skin contact.

R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications referred to in sections 2 and

: Xn - Harmful

N - Dangerous for the environment

History

Date of printing : 10.09.2010.

Date of issue : 10.09.2010.

Date of previous issue : No previous validation.

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Date of issue : 10.09.2010. MSDS no. : 34683 6/6

Safety Data Sheet



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name: SikaRail KC 340/45, Part B

Use of the substance/preparation: Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

United Kingdom

Telephone no. : 01707 394444

Fax no. : 01707 329129

e-mail address of person : EHS@uk.sika.com

responsible for this SDS

Emergency telephone number

: +44 (0)1707 363899 (available during office hours).

2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Carc. Cat. 3; R40

Xn; R20, R48/20 Xi; R36/37/38 R42/43

Human health hazards: Limited evidence of a carcinogenic effect. Harmful by inhalation. Harmful: danger of

serious damage to health by prolonged exposure through inhalation. Irritating to eyes, respiratory system and skin. May cause sensitisation by inhalation and skin contact.

Additional warning phrases: Contains isocyanates. See information supplied by the manufacturer.

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Modified aromatic isocyanate

Characteristics

Ingredient name	CAS number	%	EC number	Classification	
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	75-90		Carc. Cat. 3; R40 Xn; R20, R48/20 Xi; R36/37/38 R42/43	[1]
1,3-Butanediol, polymer with 1,1'-methylenebis[isocyanatobenzene], 2,2'-oxybis[ethanol] and 1,2-propanediol	155662-82-1	20-25		Xn; R20 Xi; R36/37/38 R42/43	[1]
See section 16 for the full text of the R-phrases declared above					

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Date of issue : 10.09.2010. MSDS no. : 43403 1/6

COMPOSITION/INFORMATION ON INGREDIENTS 3.

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

FIRST AID MEASURES 4.

First-aid measures

Inhalation : If it is suspected that fumes are still present, the rescuer should wear an appropriate

mask or self-contained breathing apparatus. Get medical attention. Get medical

attention if symptoms appear.

: Do not induce vomiting unless directed to do so by medical personnel. Maintain an Ingestion

open airway. Seek immediate medical attention.

Skin contact Flush contaminated skin with plenty of water. Remove contaminated clothing and

> shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention if symptoms

occur.

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable : Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion

products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment (see section

Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains

and sewers. Inform the relevant authorities if the product has caused environmental

pollution (sewers, waterways, soil or air).

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, Large spill

water courses, basements or confined areas. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

: Stop leak if without risk. Move containers from spill area. Absorb with an inert Small spill material and place in an appropriate waste disposal container.

: 10.09.2010. Date of issue **MSDS no.** : 43403 2/6

7. HANDLING AND STORAGE

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitisation problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Packaging materials

Recommended: Use original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

<u>Ingredient name</u> <u>Occupational exposure limits</u>

Diphenylmethanediisocyanate, isomeres and homologues

EH40/2005 WELs (United Kingdom (UK), 8/2007). Skin sensitiser. Notes: as NCO

STEL: 0.07 mg/m³, (as NCO) 15 minute(s). TWA: 0.02 mg/m³, (as NCO) 8 hour(s).

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Exposure controls

Occupational exposure controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

organic vapour filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Date of issue : 10.09.2010. MSDS no. : 43403 3/6

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance

Form : Liquid.
Colour : Brown.
Odour : Characteristic.

Important health, safety and environmental information

Flash point : Closed cup: >101°C (>213.8°F)

Density : ~1.2 g/cm³ [25°C (77°F)]

Solubility: Insoluble in the following materials: water

10. STABILITY AND REACTIVITY

Stability: The product is stable.Conditions to avoid: No specific data.Materials to avoid: No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation : Harmful by inhalation. Irritating to respiratory system. May cause sensitisation by

inhalation. May cause irritation.

Ingestion: Irritating to mouth, throat and stomach.

Skin contact: Irritating to skin. May cause sensitisation by skin contact.

Eye contact: Irritating to eyes.

Chronic effects: Harmful: danger of serious damage to health by prolonged exposure through

inhalation. Once sensitized, a severe allergic reaction may occur when subsequently

exposed to very low levels.

Carcinogenicity: May cause cancer, based on animal data. Limited evidence of a carcinogenic effect.

Risk of cancer depends on duration and level of exposure.

12. ECOLOGICAL INFORMATION

Environmental effects: Avoid contact of spilt material and runoff with soil and surface waterways. Do not

empty into drains; dispose of this material and its container in a safe way.

Date of issue : 10.09.2010. MSDS no. : 43403 4/6

13. DISPOSAL CONSIDERATIONS

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

European waste catalogue

(EWC)

: 08 04 09* waste adhesives and sealants containing organic solvents or other

dangerous substances

Packaging

: Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a

licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

15 01 10* packaging containing residues of or contaminated by dangerous substances

TRANSPORT INFORMATION 14.

International transport regulations

ADR

Not regulated.

<u>IMDG</u>

Not regulated.

Marine pollutant : No

<u>IATA</u>

Not regulated.

REGULATORY INFORMATION **15**.

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols : Xn

Harmful

Contains : Diphenylmethanediisocyanate, isomeres and homologues

1,3-Butanediol, polymer with 1,1'-methylenebis[isocyanatobenzene], 2,2'-

oxybis[ethanol] and 1,2-propanediol

Risk phrases : R40- Limited evidence of a carcinogenic effect.

R20- Harmful by inhalation.

R48/20- Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

R36/37/38- Irritating to eyes, respiratory system and skin. R42/43- May cause sensitisation by inhalation and skin contact.

: S23- Do not breathe gas/fumes/vapour/spray Safety phrases

S36/37- Wear suitable protective clothing and gloves.

S45- In case of accident or if you feel unwell, seek medical advice immediately (show

the label where possible).

Additional warning phrases : Contains isocyanates. See information supplied by the manufacturer.

VOC content (EU) : VOC (w/w): 0%

Date of issue : 10.09.2010. **MSDS no.** : 43403 5/6

15. REGULATORY INFORMATION

National regulations

Regulatory information : Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (CHIP

4)

Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as

amended)

Health & Safety at Work Act 1974

The Environmental Protection (Duty of Care) Regulations 1991

Hazardous waste regulations 2005

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2007

Guidance Publications : Approved Code of Practice - Management of Health and Safety at Work, HSE

General Approved Code of Practice to COSHH Regulations, HSE.

EH40, Workplace Exposure Limits, HSE (as updated).

HS(G) 53, Respiratory Protection Equipment - a Practical Guide for Users, HSE.

16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and

: R40- Limited evidence of a carcinogenic effect.

R20- Harmful by inhalation.

R48/20- Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

R36/37/38- Irritating to eyes, respiratory system and skin. R42/43- May cause sensitisation by inhalation and skin contact.

Full text of classifications referred to in sections 2 and

: Carc. Cat. 3 - Carcinogen category 3

Xn - Harmful Xi - Irritant

History

Date of printing : 10.09.2010.

Date of issue : 10.09.2010.

Date of previous issue : No previous validation.

▼ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Date of issue : 10.09.2010. MSDS no. : 43403 6/6