

# PRODUCT DATA SHEET

# SikaRoof® HD Attenuation Layer 170 UK

# **HD** Attenuation Layer

#### PRODUCT DESCRIPTION

SikaRoof® HD Attenuation Layer 170 UK is an attenuation layer made of recycled PP material. With high temporary retention volume when used in conjunction with a Flow Control System for specific regulation of water discharge and/or temporary water storage.

## **USES**

- For the construction of retention roofs
- Suitable for use under extensive and intensive greening and traffic areas

# **CHARACTERISTICS / ADVANTAGES**

- With closed, load-distributing structure
- For temporary and/or permanent storage of rainwater with regulated water discharge through a Flow Control System
- With Capillary Bridges to transport stored rainwater from the drainage level into the substrate layer and to increase evaporation
- High compressive strength
- With freely flowable structure for quick distribution of rainwater within the retention room
- Suitable for inverted roofs (when used on inverted insulation, no permanent water storage is possible)

#### PRODUCT INFORMATION

Chemical Base	Recycled PP	
Packaging	Disposable pallet with 24 individual elements	
Colour	Black	
Shelf Life	2 Years	
Storage Conditions	Products should be stored away from UV in dry conditions and protected from extremes of temperature.	
Dimensions	1.19 x 0.59m	
Thickness	Approximately 170mm	
Weight	11.4 kg/m²	
Compressive Strength	800 kN/m² with 10% compression	(DIN ISO 25619-2)
Water retention	Approximately 161 litres/m <sup>2</sup>	

#### **VALUE BASE**

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## **ECOLOGY, HEALTH AND SAFETY**

#### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

#### APPLICATION INSTRUCTIONS

Installation works should be carried out by suitably trained contractors in strict accordance with the project specification.

#### **LEGAL NOTES**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

# SIKA LIMITED

Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ Tel: 01707 394444 Web: www.sika.co.uk Twitter: @SikaLimited







Product Data Sheet
SikaRoof® HD Attenuation Layer 170 UK
February 2025, Version 01.01
020945051350000070

