

Date of last issue: 27.05.2023	Version 7.0	Print Date 29.02.2024
Revision Date: 02.01.2024		

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### **1.1 Product identifier**

Trade name : Decothane Root Resistant Top Coat

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Product is not intended for consumer use

## 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited
		Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person	:	EHS@uk.sika.com
responsible for the SDS		

## **1.4 Emergency telephone number**

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)				
Skin irritation, Category 2	H315: Causes skin irritation.			
Eye irritation, Category 2	H319: Causes serious eye irritation.			
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.			
Short-term (acute) aquatic hazard, Cate- gory 1	H400: Very toxic to aquatic life.			
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.			

## 2.2 Label elements

# Labelling (REGULATION (EC) No 1272/2008)



Date of last issue: 27.05.2023 Revision Date: 02.01.2024		V	Version 7.0 Print Date 29.02.20	
Hazard pictograms	:		***	
Signal word	:	Warning		
Hazard statements	:	H315 H317 H319 H410	Causes skin irritation. May cause an allergic skin re Causes serious eye irritation Very toxic to aquatic life with effects.	
Precautionary statements	:	Prevention:		
		P261 P264 P273 P280	Avoid breathing mist or vapo Wash skin thoroughly after h Avoid release to the environr Wear protective gloves/ eye protection.	andling. nent.
		Response:		
		P333 + P313	If skin irritation or rash occura advice/ attention.	s: Get medical
		P391	Collect spillage.	

# Hazardous components which must be listed on the label:

bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate Isophorondiisocyanate homopolymer 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Pentamethyl piperidylsebacate 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)

#### **Additional Labelling**

"As from 24 August 2023 adequate training is required before industrial or professional use."

# 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Date of last issue: 27.05.2023 Revision Date: 02.01.2024 Version 7.0

Print Date 29.02.2024

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenyl tolyl phosphate MCS	Not Assigned 945-730-9 01-2119511174-52- XXXX	Aquatic Acute 1; H400 Aquatic Chronic 3; H412	>= 10 - < 20
2-methoxy-1-methylethyl acetate Contains: 2-methoxypropyl acetate <= 1 %	108-65-6 203-603-9 01-2119475791-29- XXXX	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10 - < 20
bis[2-[2-(1-methylethyl)-3- oxazolidinyl]ethyl] hexane-1,2- diylbiscarbamate	59719-67-4 261-879-6 UK-01-6693092877- 6-0001	Eye Irrit. 2; H319 Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 5 - < 10
Isophorondiisocyanate homopol- ymer Contains: 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate <= 0,49 %	53880-05-0 931-312-3 500-125-5 01-2119488734-24- XXXX	Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	>= 1 - < 2,5
Hydrocarbons, C10, aromatic, >1% Naphthalene	Not Assigned 926-273-4 265-198-5 01-2119463588-24- XXXX [corresponding group CAS 64742-94- 5]	Carc. 2; H351 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 0,25 - < 0,5



\_

ate of last issue: 27.05.2023 evision Date: 02.01.2024	Version 7.0		Print Date 29.02.2024
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H317 STOT SE 3; H337 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 0,031 mg/l	>= 0,25 - < 0,5
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,25 - < 0,5
2-ethylhexanoic acid, zirconium salt	22464-99-9 245-018-1 01-2119979088-21- XXXX	Repr. 2; H361d	>= 0,1 - < 0,5



Date of last issue: 27.05.2023 Revision Date: 02.01.2024	Version 7.0	)	Print Date 29.02.2024
4,5-dichloro-2-octyl-2H-isothiazol- 3-one (DCOIT)	64359-81-5 264-843-8	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,1 - < 0,25
		M-Factor (Acute aquatic toxicity): 100100 M-Factor (Chronic aquatic toxicity): 100100	
		specific concentration limit Skin Irrit. 2; H315 0,025 - < 5 % Eye Irrit. 2; H319 0,025 - < 3 % Skin Sens. 1A; H317 >= 0,0015 %	
		Acute toxicity esti- mate	
		Acute oral toxicity: 567 mg/kg 567 mg/kg Acute inhalation tox- icity (dust/mist): 0,16 mg/l 0,16 mg/l	

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air.



Date of last issue: 27.05.2023 Revision Date: 02.01.2024	Version 7.0	Print Date 29.02.2024
	Consult a physician after significant exposu	re.
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes in</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>	nmediately.
In case of eye contact	Immediately flush eye(s) with plenty of wate Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	r.
If swallowed	Do not induce vomiting without medical advi Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconse	
4.2 Most important symptoms and	effects, both acute and delayed	
Symptoms	Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information and symptoms.	n on health effects
Risks	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.	
	irritant effects sensitising effects	
4.3 Indication of any immediate m	edical attention and special treatment need	ed
Treatment	Treat symptomatically.	
SECTION 5: Firefighting measu	ires	
5.1 Extinguishing media		
Suitable extinguishing media	In case of fire, use water/water spray/water ide/sand/foam/alcohol resistant foam/chemic extinction.	
5.2 Special hazards arising from the	ne substance or mixture	
Specific hazards during fire-	Do not allow run-off from fire fighting to enter courses.	er drains or water
Hazardous combustion prod-	No hazardous combustion products are kno	wn



Date of last issue: 27.05.2023 Revision Date: 02.01.2024	Version 7.0	Print Date 29.02.2024

# 5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

# **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Deny access	protective equipment. to unprotected persons.
	nto surface water or sanitary sewer system. contaminates rivers and lakes or drains inform thorities.

# 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel,
	acid binder, universal binder, sawdust).
	Keep in suitable, closed containers for disposal.

# 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
	Smoking, eating and drinking should be prohibited in the ap- plication area.
	Follow standard hygiene measures when handling chemical products



Date of last issue: 27.05.2023 Revision Date: 02.01.2024		Version 7.0	Print Date 29.02.2024
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Hygiene measures	:	Handle in accordance with good industrial hygien practice. When using do not eat or drink. When u smoke. Wash hands before breaks and at the en	ising do not
7.2 Conditions for safe storage, in	nc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ver place. Containers which are opened must be car sealed and kept upright to prevent leakage. Store ance with local regulations.	efully re-
Further information on stor- age stability	:	No decomposition if stored and applied as directed	ed.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet pruse.	ior to any

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

# **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *			
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC			
		Further information: Identifies the possibility of significant uptake					
	through the sl	kin, indicative					
		TWA	50 ppm 275 mg/m3	2000/39/EC			
		TWA	50 ppm 274 mg/m3	GB EH40			
	Further information: Can be absorbed through the skin. The as-						
		signed substances are those for which there are concerns that					
		ermal absorption will lead to systemic toxicity.					
		STEL	100 ppm 548 mg/m3	GB EH40			
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,02 mg/m3 (NCO)	GB EH40			
	asthma (also can induce a immunologica become hype	ation: Substances t known as asthmage state of specific airw I irritant or other me r-responsive, further en in tiny quantities	ns and respiratory ay hyper-respons chanism. Once the exposure to the s	/ sensitisers) iveness via an e airways have substance,			



Date of last issue: 27.05.2023 Revision Date: 02.01.2024 Version 7.0

Print Date 29.02.2024

STEL 0,07 mg/m3 GB EH40 (NCO)
-------------------------------

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### **Biological occupational exposure limits**

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	isocyanate- derived diamine (Isocyanates): 1 µmol/mol creati- nine (Urine)	At the end of the period of expo- sure	GB EH40 BAT

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
bis[2-[2-(1-methylethyl)- 3-oxazolidinyl]ethyl] hexane-1,2- diylbiscarbamate	Workers	Inhalation	Long-term systemic effects	29,4 mg/m3
	Workers	Skin contact	Long-term systemic effects	16,7 mg/kg



Date of last issue: 27 Revision Date: 02.01		Version 7	<sup>7</sup> .0	Print Date 29.02.2024
	Consumers	Inhalation	Long-term systemic effects	6,25 mg/m3
	Consumers	Skin contact	Long-term systemic effects	8,3 mg/kg
	Consumers	Ingestion	Long-term systemic effects	4,2 mg/kg

## Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
bis[2-[2-(1-methylethyl)-3- oxazolidinyl]ethyl] hexane-1,2- diylbiscarbamate	Fresh water	0,0186 mg/l
	Marine water	0,00186 mg/l
	Fresh water sediment	0,709 mg/kg
	Marine sediment	0,0709 mg/kg
	Soil	1,131 mg/kg

## 8.2 Exposure controls

# Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par-



Date of last issue: 27.05.2023 Revision Date: 02.01.2024	Version 7.0	Print Date 29.02.2024
	ticular to the mixing / stirring area. In case to keep the concentrations under the occup limits then respiration protection measures	pational exposure
Environmental exposure contr	ols	
General advice :	Do not flush into surface water or sanitary s If the product contaminates rivers and lake respective authorities.	

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

	nysical state blour	:	liquid black
0	dour	:	hydrocarbon-like
	elting point/range / Freezing pint	:	No data available
Bo	biling point/boiling range	:	No data available
Fl	ammability (solid, gas)	:	No data available
U	oper/lower flammability or e	exp	losive limits
	Linner evelopion limit / Lin		No data available
	Upper explosion limit / Up- per flammability limit	:	NO Gala avaliable
		:	
Fl	per flammability limit Lower explosion limit /		
	per flammability limit Lower explosion limit / Lower flammability limit		No data available 62 °C Method: closed cup

Decomposition temperature	:	No data available

pH : Not applicable

# Viscosity



Date of last issue: 27.05.2023 Revision Date: 02.01.2024		Version 7.0	Print Date 29.02.2024
Viscosity, kinematic	:	> 7 mm2/s (40 °C)	
<b>Solubility(ies)</b> Water solubility	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	3,1 hPa	
Density	:	1,4 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

# 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

# 10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions				
Hazardous reactions	:	Stable under recommended storage conditions.		

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

# 10.5 Incompatible materials

Materials to avoid : No data available

# **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.



Date of last issue: 27.05.2023
Revision Date: 02.01.2024

Version 7.0

Print Date 29.02.2024

# **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

# Acute toxicity

Not classified due to lack of data.

#### **Components:**

Diphenyl tolyl phosphate	ICS:			
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg			
Acute dermal toxicity	: LD50 Dermal (Rat): > 2.000 mg/kg			
2-methoxy-1-methylethyl a	cetate:			
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg			
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 5.000 mg/kg			
bis[2-[2-(1-methylethyl)-3-o	oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:			
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg			
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2.000 mg/kg			
3-isocyanatomethyl-3,5,5-t	rimethylcyclohexyl isocyanate:			
Acute oral toxicity	: LD50 Oral (Rat): 4.814 mg/kg			
Acute inhalation toxicity	: LC50 (Rat): 0,031 mg/l Exposure time: 4 h Test atmosphere: dust/mist			
	Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method			
Acute dermal toxicity	: LD50 Dermal (Rat): > 7.000 mg/kg			
Pentamethyl piperidylsebacate:				
Acute oral toxicity	: LD50 Oral (Rat): 3.230 mg/kg			
4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):				
Acute oral toxicity	: Acute toxicity estimate: 567 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008			
	Acute toxicity estimate: 567 mg/kg Method: Acute toxicity estimate according to Regulation (EC)			



e of last issue: 27.05.2023 ision Date: 02.01.2024	Version 7.0	Print Date 29.02.
	No. 1272/2008	
Acute inhalation toxicity	: Acute toxicity estimate: 0,16 mg/l Test atmosphere: dust/mist Method: Acute toxicity estimate ac No. 1272/2008	cording to Regulation (EC)
	Acute toxicity estimate: 0,16 mg/l Test atmosphere: dust/mist Method: Acute toxicity estimate acc No. 1272/2008	cording to Regulation (EC)
Skin corrosion/irritation Causes skin irritation.		
Components:		
Hydrocarbons, C10, aroma	tic, >1% Naphthalene:	
Result	: Repeated exposure may cause ski	in dryness or cracking.
Causes serious eye irritation Respiratory or skin sensiti		
Skin sensitisation		
May cause an allergic skin re Respiratory sensitisation Not classified due to lack of c		
Germ cell mutagenicity Not classified due to lack of c	data.	
Carcinogenicity Not classified due to lack of c	data.	
Reproductive toxicity Not classified due to lack of c	data.	
STOT - single exposure Not classified due to lack of c	data.	
STOT - repeated exposure		
Not classified due to lack of c	data.	



Date of last issue: 27.05.2023 Revision Date: 02.01.2024	Version 7.0	Print Date 29.02.2024
11.2 Information on other hazards		

#### 11.2 Information on other hazards

## Endocrine disrupting properties

## Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

## **Components:**

## bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 87,1 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Scenedesmus capricornutum (fresh water algae)): 18,6 mg/l Exposure time: 72 h

# Pentamethyl piperidylsebacate:

Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h
M-Factor (Acute aquatic tox- icity)	:	1

M-Factor (Chronic aquatic : 1 toxicity)

# 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT):

Toxicity to fish	:	LC50 (Fish): 0,0027 mg/l Exposure time: 96 h
M-Factor (Acute aquatic tox- icity)	:	100
		100
M-Factor (Chronic aquatic toxicity)	:	100
		100



Date of last issue: 27.05.2023	Version 7.0	Print Date 29.02.2024
Revision Date: 02.01.2024		
12.2 Persistence and degradability		
No data available		
12.3 Bioaccumulative potential		
No data available		

#### 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

## 12.6 Endocrine disrupting properties

	Product:		
	Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.	7 Other adverse effects		
	Product:		
	Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

#### **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods Product The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.



Date of last issue: 27.05.2023 Revision Date: 02.01.2024		Version 7.0	Print Date 29.02.2024
		Avoid dispersal of spilled material and runoff and soil, waterways, drains and sewers.	d contact with
European Waste Catalogue	:	08 01 11* waste paint and varnish containing or vents or other dangerous substances	ganic sol-
Contaminated packaging	:	15 01 10* packaging containing residues of or contract by dangerous substances	ontaminated

# **SECTION 14: Transport information**

14.1 UN number or ID number			
ADR	:	UN 3082	
IMDG	:	UN 3082	
ΙΑΤΑ	:	UN 3082	
14.2 UN proper shipping name			
ADR	:	N.O.S.	Y HAZARDOUS SUBSTANCE, LIQUID, nate, triphenyl phosphate)
IMDG	:	N.O.S.	Y HAZARDOUS SUBSTANCE, LIQUID, nate, triphenyl phosphate)
ΙΑΤΑ	:		rdous substance, liquid, n.o.s. nate, triphenyl phosphate)
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	9	
IMDG	:	9	
ΙΑΤΑ	:	9	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code IMDG Packing group Labels EmS Code	· · · · · · · · · · · · · · · · · · ·	III M6 90 9 (-) III 9 F-A, S-F	



Date of last issue: 27.05.2023 Revision Date: 02.01.2024		Version 7.0	Print Date 29.02.2024
<b>IATA (Cargo)</b> Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	964 Y964 III Miscellaneous	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	964 Y964 III Miscellaneous	
14.5 Environmental hazards			
<b>ADR</b> Environmentally hazardous	:	yes	
<b>IMDG</b> Marine pollutant	:	yes	
IATA (Passenger) Environmentally hazardous	:	yes	
IATA (Cargo) Environmentally hazardous	:	yes	
14.6 Special precautions for use	er		

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the fol- lowing entries should be considered: 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate (Number on list 74)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable



Date of last issue: 27.05.2023 Revision Date: 02.01.2024	Version 7.0		Print Date 29.02.2024
The Persistent Organic Pollutants Regulation (EU) 2019/1021 as ar ain)		Not applicable	
International Chemical Weapons Schedules of Toxic Chemicals ar		Not applicable	
Regulation (EC) No 1005/2009 or plete the ozone layer	n substances that de- :	Not applicable	
UK REACH List of substances su (Annex XIV)	bject to authorisation :	Not applicable	
GB Export and import of hazardo Informed Consent (PIC) Regulation		Not applicable	
Control of Major Accident Hazard 2015 (COMAH)	ls Regulations E1 EN	VIRONMENTAL HAZA	RDS
Volatile organic compounds :	Law on the incentive tax f (VOCV) Volatile organic compound	% w/w	
	Directive 2010/75/EU of 2 emissions (integrated poll Volatile organic compoun	ution prevention and co	ontrol)

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ-	: E	Environmental Protection Act 1990 & Subsidiary Regulations
mental regulation/legislation	ŀ	Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or	(	Control of Substances Hazardous to Health Regulations
mixture:	(	(COSHH)
	ľ	May be subject to the Control of Major Accident Hazards
	F	Regulations (COMAH), and amendments.

## Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.



Date of last issue: 27.05.2023	
Revision Date: 02.01.2024	

Version 7.0

Print Date 29.02.2024

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

# **SECTION 16: Other information**

Full text of H-Statements

Full text of H-Statements		
H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul-
		ties if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H351	:	Suspected of causing cancer.
H361d	:	Suspected of damaging the unborn child.
H361f	:	Suspected of damaging fertility.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviation	ns	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Carc.	:	Carcinogenicity
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Resp. Sens.	:	Respiratory sensitisation
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first
		list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	÷	UK. Biological monitoring guidance values
2000/39/EC / TWA	÷	Limit Value - eight hours
2000/39/EC / STEL	÷	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
 Intry CB 00000604193		20 / 2



Date of last issue: 27.05.2023 Revision Date: 02.01.2024		Version 7.0	Print Date 29.02.2024
GB EH40 / STEL		Short term expective limit (15 minute reference	pariad)
ADR	:	Short-term exposure limit (15-minute reference European Agreement concerning the Internation	
ADR	•	Dangerous Goods by Road	mai Camage of
CAS		Chemical Abstracts Service	
DNEL	:	Derived no-effect level	
EC50	:	Half maximal effective concentration	
GHS	:	Globally Harmonized System	
IATA		International Air Transport Association	
IMDG	÷	International Maritime Code for Dangerous Go	ods
LD50	:	Median lethal dosis (the amount of a material,	
		once, which causes the death of 50% (one hal	
		test animals)	, , ,
LC50	:	Median lethal concentration (concentrations of	the chemical in
		air that kills 50% of the test animals during the	observation
		period)	
MARPOL	:	International Convention for the Prevention of	Pollution from
		Ships, 1973 as modified by the Protocol of 197	'8
OEL	:	Occupational Exposure Limit	
PBT	:	Persistent, bioaccumulative and toxic	
PNEC	:	Predicted no effect concentration	
REACH	:	Regulation (EC) No 1907/2006 of the Europea	
		and of the Council of 18 December 2006 conce	
		istration, Evaluation, Authorisation and Restric	
0.410		cals (REACH), establishing a European Chem	icals Agency
SVHC	:	Substances of Very High Concern	
vPvB	:	Very persistent and very bioaccumulative	

# **Further information**

Classification of the m	nixture:	Classification procedure:		
Skin Irrit. 2	H315	Calculation method		
Skin Irrit. 2 Eye Irrit. 2	H319	Calculation method		
Skin Sens. 1	H317	Calculation method		
Aquatic Acute 1	H400	Calculation method		
Aquatic Chronic 2	H411	Calculation method		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN

Date of last issue: 27.05.2023 Revision Date: 02.01.2024 Version 7.0

Print Date 29.02.2024

**Jika**®