

PRODUCT DATA SHEET

Skid Inhibiting Grit

Specialist Dried Sand

PRODUCT DESCRIPTION

Sika Liquid Plastics Skid Inhibiting Grit is a specialist dried sand.

USES

- For use with Sika Liquid Plastics Liquid Applied Roof Membranes to provide a skid inhibiting surface.
- Used to create walkway areas on roofs.

PRODUCT INFORMATION

Packaging	25Kg bags.
Appearance / Colour	Natural sand.
Shelf Life	Unlimited shelf life when stored as per instructions
Storage Conditions	Store in original packaging in a location away from sources of dampness and extremes of temperature. Keep protected from rain.
Dimensions	1.0mm - 2.0mm

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

A safety datasheet following EC-Regulation 1907/2006, Article 31 is not needed to bring the product to market, to transport or to use it. The product does not damage the environment when used as specified.

APPLICATION INSTRUCTIONS

Minimum coverage rates: 0.25 kg/m²
Fully broadcast (broadcast to excess): 3.5 kg/m² - 4.0

CHARACTERISTICS / ADVANTAGES

- Easy application

kg/m²

APPLICATION METHOD / TOOLS

Skid Inhibiting Grit in a liquid applied membrane:

In order to achieve a 'skid inhibiting' finish to designated areas, apply an additional coat of the chosen system, in a contrasting colour to the finished waterproofing, using a minimum quantity of 0.25 l/m² and whilst wet, evenly broadcast Skid Inhibiting Grit at a minimum rate of approximately 0.25 kg per square metre (or as required to meet specific requirements). This should be allowed to dry and any non-adhered particles brushed away. Finally, apply a further coat of the chosen system, at a minimum rate of 0.3 litre per square metre and allow to dry before trafficking.

Note: Prior to commencing and where applicable, walkway borders should be masked either side with polythene sheeting to collect excess grit which may then be re-used if still dry and uncontaminated.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Skid Inhibiting Grit
March 2026, Version 01.01
020915955000000001

SkidInhibitingGrit-en-GB-(03-2026)-1-1.pdf