

Sarnavap®-2000 E

DECLARATION OF PERFORMANCE

No. 31504209

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	31504209
2	INTENDED USE/S	EN 13984:2013 Flexible sheets for waterproofing – Plastic and rubber vapor control layers
3	MANUFACTURER:	Sika Ltd Watchmead Welwyn Garden City AL7 1BQ
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 13984:2013
	Notified body/ies:	0800, 1080

Declaration of Performance

Sarnavap®-2000 E

31504209

2025.09, ver. 1

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Water tightness	Pass	System 3	EN 13984:2013
Resistance to impact	≤ 100 mm	System 3	
Durability:			
Water vapor resistance after artificial ageing	Pass	System 3	
Chemical resistance	NPD		
Resistance to tearing (Nail Shank)			
longitudinal	≥ 180 N	System 3	
transversal	≥ 180 N		
Joint strength	NPD	System 3	
Water vapor resistance	≥ 300 m	System 3	
Tensile properties:			
Tensile strength:			
longitudinal	≥ 260 N/50 mm	System 3	
transversal	≥ 260 N/50 mm		
Elongation:			
longitudinal	≥ 600 %	System 3	
transversal	≥ 600 %		
Reaction to fire	Class E	System 3	
Dangerous substances	NPD	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Dean Grady
Function: Senior Product Engineer SPM
At Preston on 09 September 2025

Name : Alex Coward
Function: Head of Technical Roofing
At Preston on 09 September 2025



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sarnavap®-2000 E
31504209
2025.09, ver. 1



06

Sika Services AG, Zurich, Switzerland

DoP No. 31504209

EN 13984:2013

Notified Body 0800, 1080

Flexible sheets for waterproofing – Plastic and rubber vapor control layers

Water tightness	Pass
Resistance to impact	≤ 100 mm
Durability:	
Water vapor resistance after artificial ageing	Pass
Resistance to tearing (Nail Shank)	
longitudinal	≥ 180 N
transversal	≥ 180 N
Water vapor resistance	≥ 300 m
Tensile properties:	
Tensile strength:	
longitudinal	≥ 260 N/50 mm
transversal	≥ 260 N/50 mm
Elongation:	
longitudinal	≥ 600 %
transversal	≥ 600 %
Reaction to fire	Class E

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sarnavap®-2000 E

31504209

2025.09, ver. 1

Declaration of Performance
Sarnavap®-2000 E
31504209
2025.09, ver. 1

