

## PRODUCT DATA SHEET

# Cromar® Top Closure Piece

A preformed GRP Top Closure Piece.

### PRODUCT DESCRIPTION

A preformed GRP valley, typically used at the top abutment where the valley meets the ridge, hip, or where a saddle detail is required.

### USES

- Provide a weatherproof termination at the top end of GRP valley troughs.
- Prevent water ingress at the head of the valley.
- Ensures a proper interface between the valley trough and the roof underlay/battens.

### PRODUCT INFORMATION

<b>Packaging</b>	Banded in 10 lengths of 3 m.
<b>Shelf Life</b>	Physical plastic items have not had their shelf life determined due to longevity.
<b>Storage Conditions</b>	The product must be stored undamaged in packaging, in dry conditions at temperatures between + 5 °C and + 30 °C

### VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this

### CHARACTERISTICS / ADVANTAGES

- Part of the dry fix accessory system.
- Lightweight and simple to install.
- Enables a clean and secure top termination to maintain weathertightness.

product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

### APPLICATION INSTRUCTIONS

- Fitted at the top termination point of the valley run.
- Installed in conjunction with the correct valley trough model.
- Must seat securely beneath roofing battens and underlay to maintain water-shedding flow.

### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from coun-

try to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



**Product Data Sheet**  
Cromar® Top Closure Piece  
February 2026, Version 01.01  
020945201000246839

CromarTopClosurePiece-en-GB-(02-2026)-1-1.pdf

