

## PRODUCT DATA SHEET

# Sika® Two-Part Wood Filler

All-Purpose two component wood filler that provides a tough, shatterproof repair to all wood

## PRODUCT DESCRIPTION

Sika® Two-Part Wood Filler is a fast-drying interior and exterior wood filler. Sika® Two-Part Wood Filler is easy to mix and apply and is completely weatherproof. Once mixed, the filler sets hard to a shatterproof finish in approximately 30 minutes, which can be stained, painted, varnished or dyed, even with microporous stains. Sika® Two-Part Wood Filler has exceptional strength and flexibility and may be drilled, nailed, planed or carved once dry.

## USES

- Repairing wood damaged by wet rot in both interior and exterior applications.
- General wood filling in windowsills and frames, doors and door frames, bannisters, MDF, laminates etc.
- Repair of corner pieces of furniture.
- Repairing chips and damage in parquet and laminate floors.

## CHARACTERISTICS / ADVANTAGES

- Durable, long-lasting and shatterproof
- Can be stained, painted, varnished or dyed
- Two-Part system gives fast curing - sets in 30 minutes to any depth
- Sandable in 30 minutes
- Can be drilled, nailed, planed and carved when dry
- Moves naturally with the wood

## PRODUCT INFORMATION

|                    |                                                                                                 |
|--------------------|-------------------------------------------------------------------------------------------------|
| Packaging          | 500 g tins                                                                                      |
| Colour             | Light stainable, medium stainable, pine, oak and white.                                         |
| Shelf Life         | 24 months from date of manufacture when stored in original containers.                          |
| Storage Conditions | Store upright between +10 °C and +20 °C in cool, dry conditions, away from sources of ignition. |
| Density            | Approx. 1.1 g/cm <sup>3</sup>                                                                   |

## APPLICATION INFORMATION

|                         |                                 |
|-------------------------|---------------------------------|
| Ambient Air Temperature | +5 °C to +30 °C, optimum +20 °C |
|-------------------------|---------------------------------|

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LIMITATIONS

- If you intend to overstain the wood once filled, ALWAYS CHOOSE THE COLOUR OF FILLER THAT NEAREST MATCHES THE WOOD YOU ARE FILLING, NOT THE STAIN YOU INTEND TO USE.
- Do not place mixed material back in to the tin. If not used, mixed material should be discarded.
- Testing of a small area for colour match is recommended.
- Discard mixed material after 10 minutes if unused.
- As the manufacturer cannot know all the uses their products may be put to, it is the users responsibility to determine suitability for use. If in doubt, contact Technical Services for advice.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

Before applying, ensure surfaces are clean, dry, sound and free from dust or any contaminants that may affect adhesion. Lightly sanding the area will improve adhesion.

### APPLICATION

Mix a golf ball volume of filler (approx. 38 mm diameter) and a 38 mm strip of hardener into a homogeneous paste using the spatula provided. Press firmly in to the surface requiring repair, leaving the filler slightly proud of the surface, ready for sanding. Leave to dry for approximately 30 minutes before sanding and finishing.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



### Product Data Sheet

Sika® Two-Part Wood Filler  
October 2026, Version 01.01  
021840303000265639

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SikaTwo-PartWoodFiller-en-GB-(10-2026)-1-1.pdf