

## PRODUCT DATA SHEET

# SikaRoof® Mineralised Grit

### Crushed Slate Aggregate

#### PRODUCT DESCRIPTION

SikaRoof® Mineralised Grit is a graded crushed slate aggregate available in a selection of colours. It is designed for use in conjunction with Sika liquid applied roofing membranes to provide a skid-resistant surface or an attractive mineral-finished roof appearance.

#### USES

- Creation of skid-resistant walkways on flat roofs
- Formation of defined pedestrian access routes
- Achievement of a decorative mineral finish to liquid applied roofing systems

SikaRoof® Mineralised Grit must be used in combination with compatible Sika liquid applied waterproofing membranes.

#### PRODUCT INFORMATION

<b>Packaging</b>	30 kg bags
<b>Shelf Life</b>	No defined shelf life when stored in accordance with the recommended storage conditions.
<b>Storage Conditions</b>	Store in original, unopened packaging in dry conditions, protected from moisture, rain, and extremes of temperature.

#### VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

#### APPLICATION

##### Roof Walkways

- Embedment coat of selected Sika liquid applied membrane: 0.3 L/m<sup>2</sup>
- SikaRoof® Mineralised Grit: 2.5 kg/m<sup>2</sup>

Excess grit should be removed once cured. Retained coverage will be approximately **2.5–3.0 kg/m<sup>2</sup>**.

#### CHARACTERISTICS / ADVANTAGES

- Provides enhanced slip resistance for roof walkways
- Suitable for aesthetic mineral-finished roofing systems
- Natural slate aggregate for long-term durability
- Compatible with Sika liquid applied roofing membranes

#### APPROVALS / STANDARDS

Slip resistance testing available to EN 13036-4 (Method of measurement of slip/skid resistance of a surface: The pendulum test)

Coverage rates are for guidance only and may vary depending on substrate and application conditions.

## APPLICATION METHOD / TOOLS

### Roof Walkways

1. Mask the designated walkway area using suitable tape to achieve clean edges.
2. It is recommended to install a 1 m wide walkway across the fully cured roofing system.
3. Apply the chosen Sika liquid applied roofing membrane at 0.3 L/m<sup>2</sup>.
4. Immediately broadcast SikaRoof® Mineralised Grit evenly into the wet membrane until fully covered.
5. Remove masking tape while the membrane is still wet to avoid edge damage.
6. Allow the system to cure, then sweep off excess grit.
7. Clean, dry grit may be collected and reused.

If grit becomes damp due to weather exposure, removal may require stiff brushing. Damp grit should be dried before reuse.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



### Product Data Sheet

SikaRoof® Mineralised Grit  
March 2026, Version 01.01  
02091595500000255

SikaRoofMineralisedGrit-en-GB-(03-2026)-1-1.pdf