

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaFast®-3081 N (cartridge) (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited
Watchmead Welwyn Garden City
Hertfordshire. AL7 1BQ
Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com
responsible for the SDS

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)
24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Organic peroxides, Type E	H242: Heating may cause a fire.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361fd: Suspected of damaging fertility. Suspected of damaging the unborn child.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

Hazard statements	:	H242	Heating may cause a fire.
		H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
		H410	Very toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention:	
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P234	Keep only in original packaging.
		P273	Avoid release to the environment.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response:	
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
	P391	Collect spillage.	

Hazardous components which must be listed on the label:

dibenzoyl peroxide
tris(methylphenyl) phosphate
bis-[4-(2,3-epoxipropoxy)phenyl]propane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
dibenzoyl peroxide	94-36-0 202-327-6 01-2119511472-50-XXXX	Org. Perox. B; H241 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	>= 26 - < 40
tris(methylphenyl) phosphate Contains: triphenyl phosphate >= 1 - <= 3 %	1330-78-5 809-930-9	Repr. 2; H361fd Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 25 - < 40
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	>= 20 - < 25

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects
- Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of damaging fertility. Suspected of damaging the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Water
High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Open drum carefully as content may be under pressure.
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in cool place. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
dibenzoyl peroxide	94-36-0	TWA	5 mg/m ³	GB EH40
Further information: Where no specific short-term exposure limit is				

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

	listed, a figure three times the long-term exposure limit should be used.
--	---

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm),
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Country GB 000000607426

7 / 16

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

Physical state : liquid
Appearance : paste
Colour : off-white
Odour : odourless

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : 85 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Self-Accelerating decomposition temperature (SADT) : > 50 °C

pH : Not applicable

Viscosity

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,3 g/cm³ (23 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Decomposes on heating.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids and bases
Reducing agents
Heavy metals

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

dibenzoyl peroxide:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 24,3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

tris(methylphenyl) phosphate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3.700 mg/kg

bis-[4-(2,3-epoxypropoxy)phenyl]propane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility. Suspected of damaging the unborn child.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

SECTION 12: Ecological information

12.1 Toxicity

Components:

dibenzoyl peroxide:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

tris(methylphenyl) phosphate:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

bis-[4-(2,3-epoxipropoxy)phenyl]propane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,8 mg/l
Exposure time: 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3269
IMDG : UN 3269
IATA : UN 3269

14.2 UN proper shipping name

ADR : POLYESTER RESIN KIT
(dibenzoyl peroxide, tris(methylphenyl) phosphate)
IMDG : POLYESTER RESIN KIT

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022

Version 4.0

Print Date 12.05.2023

Revision Date: 12.05.2023

IATA : (dibenzoyl peroxide, tris(methylphenyl) phosphate)
Polyester resin kit
(dibenzoyl peroxide, tris(methylphenyl) phosphate)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADR
Packing group : II
Classification Code : F3
Labels : 3
Tunnel restriction code : (E)

IMDG
Packing group : II
Labels : 3
EmS Code : F-E, S-D

IATA (Cargo)
Packing instruction (cargo aircraft) : 370
Packing instruction (LQ) : Y370
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 370
Packing instruction (LQ) : Y370
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADR
Environmentally hazardous : yes

IMDG
Marine pollutant : yes

IATA (Passenger)
Environmentally hazardous : yes

IATA (Cargo)
Environmentally hazardous : yes

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
E1 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022
Revision Date: 12.05.2023

Version 4.0

Print Date 12.05.2023

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H241 : Heating may cause a fire or explosion.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H361fd : Suspected of damaging fertility. Suspected of damaging the unborn child.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Irrit. : Eye irritation
Org. Perox. : Organic peroxides
Repr. : Reproductive toxicity
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



SikaFast®-3081 N (cartridge) (B)

Date of last issue: 07.10.2022

Version 4.0

Print Date 12.05.2023

Revision Date: 12.05.2023

MARPOL	:	period) International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Org. Perox. E	H242
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Repr. 2	H361fd
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

||| Changes as compared to previous version !

GB / EN