

## PRODUCT DATA SHEET

# Sikafloor® DecoFlakes

### COLORED THIN LAMELLA OR FLAKES

#### PRODUCT DESCRIPTION

Flakes or lamellas of bright colors and defined sizes that placed on a colored resin like Sikalastic 625 Trafficable system or Sikalastic Rapid Trafficable system and sealed with a translucent resin or similar serves to realize decorative floors of great variety with a good chemical resistance and mechanical.

#### USES

The system of decorative floors with Sikafloor® DecoFlakes, are used in:-

Internal applications:-

- Offices / Cafes / Restaurants / Commercial Premises.
- Veterinary clinics / Waiting areas / Commercial premises
- Warehouses / Exhibition Halls, etc.

External applications:-

- Terraces
- Balconies
- Podium decks
- Communal walkways etc.

#### CHARACTERISTICS / ADVANTAGES

- Bright colors
- Easy application
- Variety of designs
- Color combination
- Defined size

#### PRODUCT INFORMATION

<b>Packaging</b>	1kg, 22.6y 25kg
<b>Appearance / Colour</b>	<ul style="list-style-type: none"><li>▪ Neutral Gray, White, Coffee and Black</li><li>▪ Size ¼"</li></ul>
<b>Shelf Life</b>	96 months from its date of production
<b>Storage Conditions</b>	Store in its original container in a dry and clean area

## APPLICATION INSTRUCTIONS

The substrate must have a flat surface with good strength (minimum compressive strength approximately 250 kg/cm<sup>2</sup>), be healthy and dry (maximum substrate moisture 4%), free of loose parts, contamination of oils, residues of curators, grout or other foreign substances. Minimum tensile strength (pull-off): 15 kg/cm<sup>2</sup>.

After a good surface preparation, depending on the porosity of the substrate, evenly broadcast Sikafloor® DecoFlakes at a rate of 0.1kg/m<sup>2</sup> (or as required to meet specific requirements). Allow to dry and any non-adhered particles brushed away.

Apply a final coat of Sikafloor 420, as supplied or add Sika PU Accelerator, by roller, at a minimum quantity of 0.4 litres/m<sup>2</sup> (equivalent of a maximum spread rate of 2.5m<sup>2</sup>/Litre. Allow to dry.

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### TECHNICAL ENQUIRIES

Tel: 01772 255015  
Web: [www.liquidplastics.co.uk](http://www.liquidplastics.co.uk)  
Twitter: @LiquidPlastics

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



### Product Data Sheet

Sikafloor® DecoFlakes  
March 2020, Version 01.01  
020816010040000009