

PRODUCT DATA SHEET

Cromar® Trowel Mastic

Cromar® Trowel Mastic is a heavy-bodied, fibre-reinforced bituminous mastic.

PRODUCT DESCRIPTION

Designed for filling, sealing and waterproofing joints, cracks and splits in a wide range of roofing and building materials.

The product provides immediate resistance to water penetration after application, making it ideal for maintenance and remedial roofing works

USES

- Filling and sealing cracks and joints in:
 - Roofing felt.
 - Asphalt and mastic asphalt.
 - Concrete and fibre cement.
 - Asbestos cement.
 - Metal guttering and drainpipes.
- General roof maintenance and repair applications.

CHARACTERISTICS / ADVANTAGES

- Immediate water resistance after application.
- Flexible - accommodates minor movement.
- Fibre-reinforced for added strength.
- Easy to apply by trowel or putty knife.
- Suitable for exterior maintenance work.

PRODUCT INFORMATION

Packaging	Preprinted tins Available sizes: 1 Litre, 2.5 Litre, 5 Litre, 25 Litre
Shelf Life	18 months.
Storage Conditions	<ul style="list-style-type: none"> ▪ Replace lid securely after use to maintain an airtight seal ▪ Store in a dry area at temperatures between + 8°C and + 25°C.
Consumption	A typical coverage rate for a 2 mm thickness is 2 m ² per Litre
Drying time	Drying time depends on weather conditions and film thickness. Heavy applications will result in extended drying times.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other

safety-related data.

APPLICATION INSTRUCTIONS

In order to assist application, tools can be lubricated with white spirit or paraffin. Apply Cromar® Trowel Mastic by trowel or putty knife, forcing material into cracks and joints and smoothing out on either side. Cracks or joints of more than 3 mm should be reinforced with glass fibre scrim and covered with a second application of mastic.

CLEANING OF TOOLS

All tools should be cleaned immediately after use with white spirit. Hardened material can be removed by soaking in white spirit.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® Trowel Mastic
February 2026, Version 01.01
020915821000247211

CromarTrowelMastic-en-GB-(02-2026)-1-1.pdf