
Sikasil® WS-605 S

DECLARATION OF PERFORMANCE

No. 63179555

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	63179555
2	INTENDED USE/S	EN 15651-1:2012 Sealants for facade for exterior and interior application F EXT-INT CC
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8048 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 15651-1:2012
	Notified body/ies:	1119

Declaration of Performance

Sikasil® WS-605 S

63179555

2018.11 , ver. 04

1024

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Resistance to flow	≤ 3 mm	System 3	
Loss of volume	≤ 10 %	System 3	
Tensile properties (i.e. elongation) at maintained extension after water immersion (elastic)	NF at 100 % Elongation	System 3	
Tensile properties (i.e. at secant tensile modulus) for non-structural low modulus sealants used in joints in cold climate areas (-30°)	≤ 0.9 MPa at 100 % Elongation	System 3	
Tensile properties (i.e. at maintained elongation) for non-structural sealants used in joints in cold climate areas (-30°)	NF at 100 % Elongation	System 3	
Durability	Pass	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Ulli Mueller
 Function: Head Market Field Engineering
 At Peschiera Borromeo on 25 September 2019

Name: Caterina Malanchini
 Function: CFO Manager
 At Peschiera Borromeo on 25 September 2019

.....


.....


End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonized technical specification	DoP Number
Sikasil® WS-605 S	EN 15651-2: 2012	75326371

Declaration of Performance

Sikasil® WS-605 S
 63179555
 2018.11 , ver. 04
 1024





18

Sika Services AG, Zurich, Switzerland

DoP No. 63179555

EN 15651-1:2012

Notified Body 1119

Sealants for facade for exterior and interior application
F EXT-INT CC

Reaction to fire	Class E
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10 %
Tensile properties (i.e. elongation) at maintained extension after water immersion (elastic)	NF at 100 % Elongation
Tensile properties (i.e. at secant tensile modulus) for non-structural low modulus sealants used in joints in cold climate areas (-30°)	≤ 0.9 MPa at 100 % Elongation
Tensile properties (i.e. at maintained elongation) for non-structural sealants used in joints in cold climate areas (-30°)	NF at 100 % Elongation
Durability	Pass

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikasil® WS-605 S
63179555
2018.11 , ver. 04
1024

Sika Engineering Silicones S.r.l.
Via L. Einaudi, 6
I-20068 Peschiera Borromeo
(MI)
Italy
www.sika.com

Declaration of Performance
Sikasil® WS-605 S
63179555
2018.11 , ver. 04
1024

4/4

BUILDING TRUST

