

Date of last issue: 12.10.2022	Version 4.1	Print Date 15.03.2023
Revision Date: 15.03.2023		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Aktivator-309P

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 Eye irritation, Category 2 Specific target organ toxicity - single ex- posure, Category 3, Central nervous	H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.
system	

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms		
Signal word	: Danger	•
Hazard statements	: H225 H319 H336	Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.



Date of last issue: 12.10.2022 Revision Date: 15.03.2023		Ve	ersion 4.1	Print Date 15.03.2023
Supplemental Hazard Statements	:	EUH066	Repeated exposure may cause or cracking.	skin dryness
Precautionary statements	:	Prevention:		
		P210	Keep away from heat, hot surface open flames and other ignition s smoking.	
		P233	Keep container tightly closed.	
		P261	Avoid breathing mist or vapours	
		P280	Wear protective gloves/ protective eye protection/ face protection.	ve clothing/
		Response:		
		P303 + P361 + F	P353 IF ON SKIN (or hair): Take ately all contaminated clothing. I with water.	
		P370 + P378	In case of fire: Use dry sand, dry alcohol-resistant foam to exting	

Hazardous components which must be listed on the label:

ethyl acetate

Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Date of last issue: 12.10.2022 Revision Date: 15.03.2023 Version 4.1

Print Date 15.03.2023

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		(
ethyl acetate	141-78-6	Flam. Liq. 2; H225	>=80
	205-500-4	Eye Irrit. 2; H319	
	01-2119475103-46-	STOT SE 3; H336	
	XXXX	(Central nervous	
		system)	
		EUH066	
tris(p-isocyanatophenyl) thiophos-	4151-51-3	Acute Tox. 4; H302	>= 5 - < 10
phate	223-981-9		
Contains:	01-2119948848-16-	Acute toxicity esti-	
chlorobenzene <= 3,57 %	XXXX	mate	
		Acute oral toxicity:	
		675 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.



Date of last issue: 12.10.2022 Revision Date: 15.03.2023	Version 4.1	Print Date 15.03.2023
4.2 Most important symptoms and	effects. both acute and delaved	
Symptoms	Excessive lachrymation Erythema Loss of balance Vertigo See Section 11 for more detailed in and symptoms.	nformation on health effects
Risks	irritant effects	
	Causes serious eye irritation. May cause drowsiness or dizzines Repeated exposure may cause sk	
4.3 Indication of any immediate m	edical attention and special treatmo	ent needed
	Treat symptomatically.	
5.1 Extinguishing media Suitable extinguishing media	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	Water High volume water jet	
5.2 Special hazards arising from t	ne substance or mixture	
Specific hazards during fire- fighting	Do not use a solid water stream as fire.	s it may scatter and spread
Hazardous combustion prod- ucts	No hazardous combustion product	ts are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	In the event of fire, wear self-conta	ained breathing apparatus.
– <i>n</i> – <i>n</i>		

: Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

1 / 1			
Personal precautions	:	Use personal protective equipment. Remove all sources of ignition.	
		5	

Further information



Date of last issue: 12.10.2022 Revision Date: 15.03.2023	Version 4.1	Print Date 15.03.2023
	Deny access to unprotected persons. Beware of vapours accumulating to form explos tions. Vapours can accumulate in low areas.	ive concentra-
6.2 Environmental precautions		
Environmental precautions :	Prevent product from entering drains. If the product contaminates rivers and lakes or o respective authorities.	drains inform
6.3 Methods and material for conta	inment and cleaning up	
Methods for cleaning up :		us earth, ver-
6 1 Potoronco to other costions		

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	: Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, in	cluding any incompatibilities
Requirements for storage areas and containers	 Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.



Date of last issue: 12.10.2022 Revision Date: 15.03.2023	Version 4.1	Print Date 15.03.2023
Further information on stor- age stability	: No decomposition if stored and applied	d as directed.
7.3 Specific end use(s) Specific use(s)	: Consult most current local Product Dat use.	ta Sheet prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m3	2017/164/EU
	Further inform	ation: Indicative	J	
		TWA	200 ppm 734 mg/m3	2017/164/EU
		TWA	200 ppm 734 mg/m3	GB EH40
		STEL	400 ppm 1.468 mg/m3	GB EH40
tris(p-isocyanatophenyl) thiophosphate	4151-51-3	TWA	0,02 mg/m3 (NCO)	GB EH40
	asthma (also I can induce a s immunologica become hyper sometimes ev toms. These s asthma. Not a come hyper-re those who are that can cause substances wh with pre-existi include the dis classified as a mation can be assessments asthma., Whe stances that c Where this is a standards of c responsive. Fo COSHH requi sonably practi	ation: Substances t known as asthmage state of specific airw l irritant or other me r-responsive, further en in tiny quantities symptoms can range Il workers who are e esponsive and it is in e likely to become hy e occupational asthr hich may trigger the ng airway hyper-resp sease themselves. The sthmagens or respination of the evidence for a rever it is reasonable an cause occupation not possible, the pri- control to prevent wo for substances that of res that exposure be cable. Activities givination ould receive particu-	ins and respiratory yay hyper-respons chanism. Once the exposure to the s may cause respiration is severity from a exposed to a sens mpossible to ident /per-responsive. ma should be disti symptoms of asth ponsiveness, but The latter substant ratory sensitisers. bublication Asthma agents implicated by practicable, exp nal asthma should mary aim is to app orkers from becom can cause occupate e reduced to as lo ng rise to short-te	y sensitisers) iveness via an e airways have substance, ratory symp- a runny nose to itiser will be- ify in advance Substances nguished from ma in people which do not ces are not Further infor- agen? Critical in occupational osure to sub- d be prevented. bly adequate ning hyper- tional asthma, w as is rea- rm peak con-



ment is being considered. Health surveillance is appropriate for employees exposed or liable to be exposed to a substance whi may cause occupational asthma and there should be appropria	023
consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing oc pational asthma., The 'Sen' notation in the list of WELs has bee assigned only to those substances which may cause occupatio asthma in the categories shown in Table 1. It should be remem bered that other substances not in these tables may cause occ pational asthma. HSE's asthma web pages (www.hse.gov.uk/asthma) provide further information.	nich ate ccu- een onal m-
STEL 0,07 mg/m3 GB EH40 (NCO)	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
tris(p-isocyanatophenyl) thiophos- phate	4151-51-3	isocyanate- derived diamine (Isocyanates): 1 µmol/mol creati- nine (Urine)	At the end of the period of expo- sure	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated
ountry CB 10000017740		7/



_

Date of last issue: 12.10.2022 Revision Date: 15.03.2023	Version 4.1	Print Date 15.03.2023
	exposure levels, the hazards of the product and ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 p Ensure adequate ventilation. This can be achiev exhaust extraction or by general ventilation. (EN ods for determining inhalation exposure). This ap ticular to the mixing / stirring area. In case this is to keep the concentrations under the occupation limits then respiration protection measures must	opm ed by local 689 - Meth- pplies in par- not sufficent al exposure
Environmental exposure contro	ols	
General advice :	Prevent product from entering drains. If the product contaminates rivers and lakes or d respective authorities.	rains inform

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour Odour	:	liquid clear yellow ester-like
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	2,1 %(V)
Flash point	:	-4 °C Method: closed cup
Auto-ignition temperature	:	427 °C
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)

Viscosity



Date of last issue: 12.10.2022 Revision Date: 15.03.2023		Version 4.1	Print Date 15.03.2023
Viscosity, dynamic	:	ca. 3 mPa.s (20 °C)	
Viscosity, kinematic	:	< 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	99,9915 hPa	
Density	:	ca. 1 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
		Vapours may form explosive mixture with air.
10.4 Conditions to avoid Conditions to avoid	:	Heat, flames and sparks. Avoid moisture.
10.5 Incompatible materials Materials to avoid	:	No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.



Date of last issue: 12.10.2022 Revision Date: 15.03.2023 Version 4.1

Print Date 15.03.2023

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

<u>Components:</u>		
ethyl acetate: Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): ca. 1.600 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg
tris(p-isocyanatophenyl) th	iopl	nosphate:
Acute oral toxicity	:	LD50 Oral (Rat): > 675 mg/kg Remarks: see user defined free text
		Acute toxicity estimate: 675 mg/kg Method: Calculation method
Acute inhalation toxicity	:	LC50 (Rat): 5,721 mg/l Exposure time: 4 h Test atmosphere: dust/mist

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.



Date of last issue: 12.10.2022 Revision Date: 15.03.2023 Version 4.1

Print Date 15.03.2023

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

2

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at
	levels of 0.1% or higher.



Date of last issue: 12.10.2022 Revision Date: 15.03.2023	Version 4.1	Print Date 15.03.2023

12.7 Other adverse effects

Product:

Additional ecological infor- : There is no data available for this product. mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 01 11* waste paint and varnish containing organic sol- vents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 1173
IMDG	:	UN 1173
ΙΑΤΑ	:	UN 1173
14.2 UN proper shipping name		
ADR	:	ETHYL ACETATE
IMDG	:	ETHYL ACETATE
ΙΑΤΑ	:	Ethyl acetate
14.3 Transport hazard class(es)		

Subsidiary risks

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Sika® Aktivator-309P

Date of last issue: 12.10.2022 Revision Date: 15.03.2023	Version 4.1	Print Date 15.03.2023
ADR	3	
IMDG	3	
ΙΑΤΑ	3	
14.4 Packing group		
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	II F1 33 3 (D/E)	
IMDG Packing group Labels EmS Code	ll 3 F-E, S-D	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	364 Y341 II Flammable Liquids	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	353 Y341 II Flammable Liquids	
14.5 Environmental hazards		
ADR Environmentally hazardous	no	
IMDG Marine pollutant	no	
IATA (Passenger) Environmentally hazardous	no	
IATA (Cargo) Environmentally hazardous	no	
	ovided herein are for informational p kaged material as it is described wit	

upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.



Date of last issue: 12.10.2022 Revision Date: 15.03.2023	Version 4.1	Print Date 15.03.2023

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Ar	nnex 17)	:	Not applicable
International Chemical Weapons Schedules of Toxic Chemicals an	, , , , , , , , , , , , , , , , , , ,	:	Not applicable
Regulation (EC) No 1005/2009 or plete the ozone layer	n substances that de-	:	Not applicable
GB Export and import of hazardo Informed Consent (PIC) Regulation		:	Not applicable
Control of Major Accident Hazard 2015 (COMAH)	s Regulations P5c F	=LA	AMMABLE LIQUIDS
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: 90,4% w/w
	emissions (integrated p	ollu	4 November 2010 on industrial ution prevention and control) ds (VOC) content: 90,4% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ- mental regulation/legislation specific for the substance or mixture:	 Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH) May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.
	······································

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225 :	Highly flammable liquid and vapour.
H302 :	Harmful if swallowed.
H319 :	Causes serious eye irritation.

H336

STOT SE 3

Sika[®] Aktivator-309P

of last issue: 12.10.2022 ion Date: 15.03.2023		Version 4.1	Print Date 15.03.2
H336	· May cause	e drowsiness or dizziness.	
Full text of other abbrevia	-		
Acute Tox.	: Acute toxic	sity	
Eye Irrit.	: Eye irritati		
Flam. Liq.	: Flammable		
STOT SE		rget organ toxicity - single e	N DOGURO
2017/164/EU		ommission Directive 2017/1	
	fourth list of	of indicative occupational ex	posure limit values
GB EH40		WEL - Workplace Exposure	
GB EH40 BAT		ical monitoring guidance va	alues
2017/164/EU / STEL	: Short term	exposure limit	
2017/164/EU / TWA		e - eight hours	
GB EH40 / TWA		exposure limit (8-hour TWA	
GB EH40 / STEL	: Short-term	exposure limit (15-minute	reference period)
ADR		Agreement concerning the s Goods by Road	International Carriage of
CAS		Abstracts Service	
DNEL		o-effect level	
EC50		nal effective concentration	
GHS		armonized System	
IATA		al Air Transport Association	h
IMDG		al Maritime Code for Dange	
LD50		hal dosis (the amount of a r	
2000		h causes the death of 50%	
	test anima		
LC50		hal concentration (concentr s 50% of the test animals d	
MARPOL	: Internation	al Convention for the Preve 3 as modified by the Protoc	
OEL		nal Exposure Limit	50101 1970
PBT		bioaccumulative and toxic	
PNEC		no effect concentration	
REACH		(EC) No 1907/2006 of the	European Parliament
	and of the istration, E	Council of 18 December 20 valuation, Authorisation and CH), establishing a Europea	006 concerning the Reg- d Restriction of Chemi-
SVHC		s of Very High Concern	
vPvB		stent and very bioaccumula	tive
Further information			
Classification of the mixtu	ıre:	Classificatio	on procedure:
Flam. Liq. 2	H225	Based on pro	oduct data or assessment

Calculation method





Date of last issue: 12.10.2022 Revision Date: 15.03.2023 Version 4.1

Print Date 15.03.2023

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN