

PRODUCT DATA SHEET

Sika® Scrim Tape

Premium quality, easy to apply plasterboard tape

PRODUCT DESCRIPTION

Sika® Scrim Tape is a fibreglass re-enforced plasterers tape on a roll which is backed with a pressure sensitive adhesive. Quick and easy to apply, Sika® Scrim Tape is made in Europe, to perform! With a high tack adhesive and an open mesh that will not blister or bubble.

USES

- For jointing dry walling.
- For repairing/jointing over large cracks in plaster.
- Repairing/jointing in ceiling work.

PRODUCT INFORMATION

Packaging	100 mm x 90 m Roll 48 mm X 90 m Roll
Appearance / Colour	Off White
Shelf Life	Storage life 12 months in tightly sealed, undamaged containers.
Storage Conditions	Store in original container in cool +5 °C to +25 °C dry conditions. Avoid direct sun light..
Thickness	0.26 ±0.05 mm
Tensile Strength	800 N/5 cm (-15%)

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Ensure surfaces are completely clean before applying tape.
- Never overlap the tape, always butt the joint.
- When applying jointing compound or plaster, ensure complete penetration through the tape to achieve optimum adhesion.

CHARACTERISTICS / ADVANTAGES

- Quick and easy to apply.
- Self-adhesive – eliminates the need for pre-plastering.
- Flexible – won't bubble or blister.
- Pressure sensitive adhesive.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For

safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

All surfaces must be clean, dry, sound and free from oil, grease and dust.

APPLICATION METHOD / TOOLS

Place tape into position and apply directly to joint or crack pressing down firmly to ensure good adhesion. For crack and hole repairs, the tape must be extended at least 25 mm from the edge of the area to be repaired, butting (never overlapping) the tape.

Once the tape is correctly positioned, apply a coat of plaster or jointing compound over the tape, extending approximately 50–100 mm wide. Ensure the plaster or jointing compound fully penetrates the tape to achieve optimum adhesion. Allow the application to dry thoroughly.

As a finishing coat, apply a further layer of plaster or jointing compound, feathering the edges to achieve a smooth, seamless finish over a total width of approximately 150–200 mm.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

Sika® Scrim Tape
September 2026, Version 01.01
020514080000265628

SikaScrimTape-en-GB-(09-2026)-1-1.pdf